První certifikační autorita, a.s.



Root Certification Authority Certificate Policy

(EC Cryptography)

The Root Certification Authority Certificate Policy (EC Cryptography) is a public document, which is the property of První certifikační autorita, a.s., and has been prepared as integral part of comprehensive security documentation. No part of this document may be reproduced without the written consent of the copyright holder.

Version 1.052

TABLE OF CONTENTS

1	Intro	duction .		11		
	1.1	Overview				
	1.2	Docum	ent name and identification	12		
	1.3	PKI par	ticipants	12		
		1.3.1	Certification authorities (also as 'CA')	12		
		1.3.2	Registration authorities (also as 'RA')	12		
		1.3.3	Subscribers	12		
		1.3.4	Relying parties	12		
		1.3.5	Other participants	13		
	1.4	Certific	ate usage	13		
		1.4.1	Appropriate certificate uses	13		
		1.4.2	Prohibited certificate uses	13		
	1.5	Policy a	administration	13		
		1.5.1	Organization administering the document			
		1.5.2	Contact person	13		
		1.5.3	Person determining CPS suitability for the policy	13		
		1.5.4	CPS approval procedures	13		
	1.6	Definitio	ons and acronyms	13		
2	Publ	plication and repository responsibilities				
	2.1	Repositories				
	2.2	Publication of certification information				
	2.3	Time o	21			
	2.4	Access	controls on repositories	21		
3	Iden	tification	and authentication	22		
	3.1	Naming)	22		
		3.1.1	Types of names	22		
		3.1.2	Need for names to be meaningful	22		
		3.1.3	Anonymity or pseudonymity of subscribers	22		
		3.1.4	Rules for interpreting various name forms	22		
		3.1.5	Uniqueness of names	22		
		3.1.6	Recognition, authentication, and role of trademarks	22		
	3.2	Initial ic	lentity validation	22		
		3.2.1	Method to prove possession of private key	22		
		3.2.2	Authentication of organization identity	23		

		3.2.3	Authentication of individual identity	23
		3.2.4	Non-verified subscriber information	23
		3.2.5	Validation of authority	23
		3.2.6	Criteria for interoperation	23
	3.3	Identific	ation and authentication for re-key requests	24
		3.3.1	Identification and authentication for routine re-key	24
		3.3.2	Identification and authentication for re-key after revocation	24
	3.4	Identific	ation and authentication for revocation request	24
4	Certif	ficate life	-cycle operational requirements	25
	4.1	Certifica	ate application	25
		4.1.1	Who can submit a certificate application	25
		4.1.2	Enrolment process and responsibilities	25
	4.2	Certifica	ate application processing	25
		4.2.1	Performing identification and authentication functions	25
		4.2.2	Approval or rejection of certificate applications	26
		4.2.3	Time to process certificate applications	26
	4.3	Certifica	ate issuance	26
		4.3.1	CA actions during certificate issuance	26
		4.3.2	Notification to subscriber by the CA of issuance of certificate	26
	4.4	Certifica	ate acceptance	26
		4.4.1	Conduct constituting certificate acceptance	26
		4.4.2	Publication of the certificate by the CA	26
		4.4.3	Notification of certificate issuance by the CA to other entities	27
	4.5	Key pair	r and certificate usage	27
		4.5.1	Subscriber private key and certificate usage	27
		4.5.2	Relying party public key and certificate usage	27
	4.6	Certifica	ate renewal	27
		4.6.1	Circumstance for certificate renewal	28
		4.6.2	Who may request renewal	28
		4.6.3	Processing certificate renewal requests	28
		4.6.4	Notification of new certificate issuance to subscriber	28
		4.6.5	Conduct constituting acceptance of a renewal certificate	28
		4.6.6	Publication of the renewal certificate by the CA	28
		4.6.7	Notification of certificate issuance by the CA to other entities	28
	4.7	Certifica	ate re-key	28
		4.7.1	Circumstance for certificate re-key	28

	4.7.2	Who may request certification of a new public key	28
	4.7.3	Processing certificate re-keying requests	29
	4.7.4	Notification of new certificate issuance to subscriber	29
	4.7.5	Conduct constituting acceptance of a re-keyed certificate	29
	4.7.6	Publication of the re-keyed certificate by the CA	29
	4.7.7	Notification of certificate issuance by the CA to other entities	29
4.8	Certifica	ate modification	29
	4.8.1	Circumstance for certificate modification	29
	4.8.2	Who may request certificate modification	29
	4.8.3	Processing certificate modification requests	29
	4.8.4	Notification of new certificate issuance to subscriber	29
	4.8.5	Conduct constituting acceptance of modified certificate	30
	4.8.6	Publication of the modified certificate by the CA	30
	4.8.7	Notification of certificate issuance by the CA to other entities	30
4.9	Certifica	ate revocation and suspension	30
	4.9.1	Circumstances for revocation	30
	4.9.2	Who can request revocation	30
	4.9.3	Procedure for revocation request	30
	4.9.4	Revocation request grace period	31
	4.9.5	Time within which CA must process the revocation request	31
	4.9.6	Revocation checking requirement for relying parties	31
	4.9.7	CRL issuance frequency	31
	4.9.8	Maximum latency for CRLs	31
	4.9.9	On-line revocation/status checking availability	31
	4.9.10	On-line revocation checking requirements	31
	4.9.11	Other forms of revocation advertisements available	31
	4.9.12	Special requirements for key compromise	31
	4.9.13	Circumstances for suspension	31
	4.9.14	Who can request suspension	32
	4.9.15	Procedure for suspension request	32
	4.9.16	Limits on suspension period	32
4.10	Certifica	ate status services	32
	4.10.1	Operational characteristics	32
	4.10.2	Service availability	32
	4.10.3	Optional features	32
4.11	End of s	subscription	32

	4.12	Key esc	row and recovery	32
		4.12.1	Key escrow and recovery policy and practices	33
		4.12.2	Session key encapsulation and recovery policy and practices	33
5	Facil	ity, mana	gement, and operational controls	34
	5.1	Physica	I controls	34
		5.1.1	Site location and construction	34
		5.1.2	Physical access	34
		5.1.3	Power and air-conditioning	34
		5.1.4	Water exposures	34
		5.1.5	Fire prevention and protection	35
		5.1.6	Media storage	35
		5.1.7	Waste disposal	35
		5.1.8	Off-site backup	35
	5.2	Procedu	ural controls	35
		5.2.1	Trusted roles	35
		5.2.2	Number of persons required per task	35
		5.2.3	Identification and authentication for each role	36
		5.2.4	Roles requiring separation of duties	36
	5.3	Personr	nel controls	36
		5.3.1	Qualification, experience, and clearance requirements	36
		5.3.2	Background check procedures	36
		5.3.3	Training requirements	36
		5.3.4	Retraining frequency and requirements	37
		5.3.5	Job rotation frequency and sequence	37
		5.3.6	Sanctions for unauthorized actions	37
		5.3.7	Independent contractor requirements	37
		5.3.8	Documentation supplied to personnel	37
	5.4	Audit log	gging procedures	37
		5.4.1	Types of events recorded	37
		5.4.2	Frequency of processing log	38
		5.4.3	Retention period for audit log	38
		5.4.4	Protection of audit log	38
		5.4.5	Audit log backup procedures	38
		5.4.6	Audit collection system (internal or external)	38
		5.4.7	Notification to event-causing subject	38
		5.4.8	Vulnerability assessments	39

	5.5	Record	s archival	39
		5.5.1	Types of records archived	39
		5.5.2	Retention period for archive	39
		5.5.3	Protection of archive	39
		5.5.4	Archive backup procedures	39
		5.5.5	Requirements for time-stamping of records	39
		5.5.6	Archive collection system (internal or external)	40
		5.5.7	Procedures to obtain and verify archive information	40
	5.6	Key cha	angeover	40
	5.7	Compro	omise and disaster recovery	40
		5.7.1	Incident and compromise handling procedures	40
		5.7.2	Computing resources, software, and/or data are corrupted	40
		5.7.3	Entity private key compromise procedures	40
		5.7.4	Business continuity capabilities after a disaster	41
	5.8	CA or F	RA termination	41
6	Tech	nnical sec	curity controls	42
	6.1	Key pai	ir generation and installation	42
		6.1.1	Key pair generation	42
		6.1.2	Private key delivery to subscriber	42
		6.1.3	Public key delivery to certificate issuer	42
		6.1.4	CA public key delivery to relying parties	42
		6.1.5	Key sizes	42
		6.1.6	Public key parameters generation and quality checking	43
		6.1.7	Key usage purposes (as per X.509 v3 key usage field)	43
	6.2	Private	key protection and cryptographic module engineering controls	43
		6.2.1	Cryptographic module standards and controls	43
		6.2.2	Private key (n out of m) multi-person control	43
		6.2.3	Private key escrow	43
		6.2.4	Private key backup	43
		6.2.5	Private key archival	43
		6.2.6	Private key transfer into or from a cryptographic module	44
		6.2.7	Private key storage on cryptographic module	44
		6.2.8	Method of activating private key	44
		6.2.9	Method of deactivating private key	44
		6.2.10	Method of destroying private key	44
		6.2.11	Cryptographic module rating	45

	6.3	Other aspects of key pair management		
		6.3.1	Public key archival	45
		6.3.2	Certificate operational periods and key pair usage periods	45
	6.4	Activatio	on data	45
		6.4.1	Activation data generation and installation	45
		6.4.2	Activation data protection	45
		6.4.3	Other aspects of activation data	46
	6.5	Comput	er security controls	46
		6.5.1	Specific computer security technical requirements	46
		6.5.2	Computer security rating	46
	6.6	Life cyc	le technical controls	48
		6.6.1	System development controls	48
		6.6.2	Security management controls	48
		6.6.3	Life cycle security controls	48
	6.7	Network	security controls	49
	6.8	Time-st	amping	49
7	Certi	ficate, Cl	RL and OCSP profiles	50
	7.1	Certifica	ate profile	50
		7.1.1	Version number(s)	51
		7.1.2	Certificate extensions	51
		7.1.3	Algorithm object identifiers	53
		7.1.4	Name forms	53
		7.1.5	Name constraints	53
		7.1.6	Certificate policy object identifier	53
		7.1.7	Usage of Policy Constraints extension	53
		7.1.8	Policy qualifiers syntax and semantics	53
		7.1.9	Processing semantics for the critical Certificate Policies exten	
	7.2	CRL pro	ofile	
		7.2.1	Version number(s)	
		7.2.2	CRL and CRL entry extensions	
	7.3	OCSP p	profile	54
		7.3.1	Version number(s)	55
		7.3.2	OCSP extensions	55
8	Com	pliance a	udit and other assesments	56
	8.1	Frequer	ncy or circumstances of assessment	56
	8.2	8.2 Identity/qualifications of assessor		

	8.3	Assess	or's relationship to assessed entity	56	
	8.4	Topics	covered by assessment	56	
	8.5	Actions	taken as a result of deficiency	56	
	8.6	Commu	unication of results	57	
9	Othe	r busine	ss and legal matters	58	
	9.1	Fees		58	
		9.1.1	Certificate issuance or renewal fees	58	
		9.1.2	Certificate access fees	58	
		9.1.3	Revocation or status information access fees	58	
		9.1.4	Fees for other services	58	
		9.1.5	Refund policy	58	
	9.2	Financi	al responsibility	58	
		9.2.1	Insurance coverage	58	
		9.2.2	Other assets	58	
		9.2.3	Insurance or warranty coverage for end-entities	59	
	9.3	Confide	entiality of business information	59	
		9.3.1	Scope of confidential information	59	
		9.3.2	Information not within the scope of confidential information	59	
		9.3.3	Responsibility to protect confidential information	59	
	9.4	Privacy	of personal information	59	
		9.4.1	Privacy plan	59	
		9.4.2	Information treated as private	59	
		9.4.3	Information not deemed private	59	
		9.4.4	Responsibility to protect private information	60	
		9.4.5	Notice and consent to use private information	60	
		9.4.6	Disclosure pursuant to judicial or administrative process	60	
		9.4.7	Other information disclosure circumstances	60	
	9.5	Intellec	tual property rights	60	
	9.6	Repres	entations and warranties	60	
		9.6.1	CA representations and warranties	60	
		9.6.2	RA representations and warranties	60	
		9.6.3	Subscriber representations and warranties	60	
		9.6.4	Relying parties representations and warranties	61	
		9.6.5	Representations and warranties of other participants	61	
	9.7	Disclair	ners of warranties	61	
	9.8	Limitations of liability61			

	9.9	Indemn	Indemnities61			
	9.10	Term ar	Term and termination			
		9.10.1	Term	61		
		9.10.2	Termination	61		
		9.10.3	Effect of termination and survival	61		
	9.11	Individu	al notices and communications with participants	61		
	9.12	Amendr	nents	62		
		9.12.1	Procedure for amendment	62		
		9.12.2	Notification mechanism and period	62		
		9.12.3	Circumstances under which OID must be changed	62		
	9.13	Dispute	s resolution provisions	62		
	9.14	Governi	ng law	62		
	9.15	Complia	ance with applicable law	62		
	9.16	Miscella	Miscellaneous provisions6			
		9.16.1	Entire agreement	62		
		9.16.2	Assignment	62		
		9.16.3	Severability	63		
		9.16.4	Enforcement (attorneys' fees and waiver of rights)	63		
		9.16.5	Force majeure	63		
	9.17	Other p	rovisions	63		
10	Final	provisio	ns	64		

Version	Date of Release	Approved by	Comments		
1.00	2 December 2016	CEO of První certifikační autorita, a.s.	First release.		
1.01	10 May 2019	CEO of První certifikační autorita, a.s.	Revision, formal errors correction.		
1.02	15 April 2020	CEO of První certifikační autorita, a.s.	Annual revision of text, formal errors correction.		
1.03	15 April 2021	CEO of První certifikační autorita, a.s.	Annual revision of text, classification of document marked.		
1.04	20 April 2022	CEO of První certifikační autorita, a.s.	Mozilla and BRG requirement added - EKU attribute in subordinate CAs' certificates (chapter 7.1.2).		

Table 1 – Document History

			BRG requirement added - ReasonCode in CRL issued by RootCA a OCSP response issued by OCSP responder of RootCA may not be unspecified (chapters 7.2.2 and 7.3).
			Procedure of issuing certificates by root certification authority modified, more specified HSM certification.
1.05	27 April 2022	CEO of První certifikační autorita, a.s.	Formal errors correction.
1.051	20 April 2023	CEO of První certifikační autorita, a.s.	Annual revision of text.
1.052	20 April 2024	CEO of První certifikační autorita, a.s.	Annual revision, clarification of the text.

1 INTRODUCTION

This document determines the principles applied by První certifikační autorita, a.s. (also as the I.CA), a qualified provider of trust services, when issuing certificates for subordinate certification authorities by the root certification authority (also as the Service or the Certificate). The EC cryptography (also as the ECC) is used for the Service provided under this certificate policy (also as the CP).

The legal requirements in respect of the Service are defined in:

- Regulation (EU) no 910/2014 of the European Parliament and of the Council on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC;
- Act of the Czech Republic No. 297/2016 Coll., on trust services for electronic transactions;
- Legislation concerning personal data protection in compliance with Regulation (EU) no 2016/679 of the European Parliament and of the Council on the protection of natural persons with regard to the processing of personal data and on the free movement of such data, and repealing Directive 95/46/EC (General Data Protection Regulation).
- Note: Any reference to technical standard, norm or legislation is always a reference to that technical standard, norm or legislation or the replacing technical standard, norm or legislation. If this document is in conflict with any technical standard, norm or legislation that replaces the current technical standard, norm or legislation, a new version will be released.

1.1 Overview

The document **Root Certification Authority Certificate Policy (EC Cryptography)**, also as the CP, is prepared by I.CA and deals with the issues related to life cycle processes of the Certificates and strictly follows a structure matching the scheme of current RFC 3647 standard while taking account of current technical standards and norms of the European Union and the laws of the Czech Republic pertinent to this sphere (therefore, each chapter is preserved in this document even if it is irrelevant to this sphere). The document is divided into nine basic chapters and these are briefly introduced in the following list:

- Chapter 1 identifies this document with the allocated unique identifier, generally describes the entities and individuals taking part in the provision of this Service, and defines the acceptable use of the Certificates available to be issued;
- Chapter 2 deals with the responsibility for the publication and information or documents;
- Chapter 3 describes the processes of identification and authentication of an applicant for the issuance or revocation of a Certificate, and defines the types and contents of the names used in Certificates;
- Chapter 4 defines life cycle processes of Certificates, i.e., application, the issuance of the Certificate, certificate revocation request, the revocation of the Certificate, the services related to the check of Certificate status, termination of the provision of the Service, etc.;
- Chapter 5 covers physical, procedural and personal security, including the definition of the set of events subject to logging, the keeping of these records and responses to emergency and compromising situations;

- Chapter 6 focuses on the technical security of the type of generating public and private keys, protection of private keys, including the computer and network protection;
- Chapter 7 defines the profile of issued Certificates and CRL;
- Chapter 8 focuses on assessing the Service delivered;
- Chapter 9 deals with commercial and legal aspects.

More detail on the fulfilment of the attributes and extensions of the certificates issued under this policy and the administration thereof can be provided in the relevant certification practice statement (also as the CPS).

Note: This is English translation of CP; Czech version always takes precedence. I.CA attests that the translation is not materially different to the original.

1.2 Document name and identification

Document's title:	Root Certification Authority Certificate Policy (E Cryptography), version 1.052	С
Policy OID:	1.3.6.1.4.1.23624.11.1.10.1.0	

1.3 PKI participants

1.3.1 Certification authorities (also as 'CA')

The root certification authority (also as the Authority) issues certificates for the certification authorities subordinate to the Authority in a two-tier certification authority structure, in accordance with current legislation and technical and other standards.

As the Authority is off line, it has no live connection to the external network at any time. The Authority's physical information system is comprised of dedicated computers.

1.3.2 Registration authorities (also as 'RA')

A special (non-public) registration authority owned by I.CA participates in the life cycle processes of the Authority-issued Certificates.

1.3.3 Subscribers

The subscriber of the Certificate to be issued is První certifikační autorita, a.s., which applied for the Certificate for itself and is identified in the Certificate as subject (holder of the private key connected with the public key specified in this Certificate).

1.3.4 Relying parties

Any entity relying in their operations on the Certificates issued under this CP is a relying party.

1.3.5 Other participants

Other participating parties are investigative, prosecuting and adjudicating bodies, supervisory bodies and other bodies recognised as such by current legislation.

1.4 Certificate usage

1.4.1 Appropriate certificate uses

Any Certificate issued under this CP may solely be used for verifying electronic seals of issued Certificates and certificate revocation lists (CRLs).

1.4.2 Prohibited certificate uses

Certificates issued under this CP may not be used contrary to the acceptable use described in 1.4.1 or contrary to law.

1.5 Policy administration

1.5.1 Organization administering the document

This CP and its CPS are administered by První certifikační autorita, a.s.

1.5.2 Contact person

The contact person of První certifikační autorita, a.s., in respect of this CP and its CPS is specified on a web page – see 2.2.

1.5.3 Person determining CPS suitability for the policy

CEO of První certifikační autorita, a.s., is the sole person responsible for making decisions about compliance of the procedures of První certifikační autorita, a.s., as set out in CPS with this CP.

1.5.4 CPS approval procedures

If it is necessary to make changes to a CPS to create a new version thereof, CEO of První certifikační autorita, a.s., appoints a person authorized to perform such changes. No new CPS version may take force unless it has been approved by CEO of První certifikační autorita, a.s.

1.6 Definitions and acronyms

Table 2 – Definitions

Term	Explanation
CA/Browser Forum	organization, consensual association of certification authorities

Classified Information Protection Act	the Czech Republic's Act No. 412/2005 Coll., regulating classified information protection and security competence, as amended
contracting partner	provider of services contracted by I.CA for certification services or parts thereof – usually, it is a contracted RA
domain name	node name in domain name system
domain name registrant/ registrant	sometimes referred to as a domain name owner, but more accurately a person or entity registered by a domain registrar as having the right to oversee the use of a domain name, a natural or legal person listed as a "Registrant" by WHOIS or a domain registrar
domain name registrar/ registrar	person or entity that registers domain names by mandate or with consent:
	 Internet Corporation for Assigning Names and Numbers (ICANN) - Administrator of DNS Root Space;
	 TLD administrator (e.gcom) or ccTLD (e.gCZ, national administrator)
domain name space	a set of all possible domain names that are subordinate to one node in the domain name system
electronic seal	advanced electronic seal or recognized electronic seal or qualified electronic seal under trust services legislation
electronic signature	advanced electronic signature or recognized electronic signature or qualified electronic signature under trust services legislation
GET method	standard preferred method for sending http requests to OCSP responder via http, the method allows caching (the second method is POST)
hash function	transformation which receives, as an input, a string of characters of arbitrary length, and the result is a string of characters of fixed length (hash)
key pair	private key and corresponding public key
Labour Code	the Czech Republic's Act No. 262/2006 Coll., Labour Code, as amended
OCSP responder	server using the OCSP protocol to provide data on public key certificate status
OCSP stapling	way of minimizing queries for OCSP Responder, RFC 4366 - TLS Extensions; allows the TLS server to return the once- received answer to the question about certificate status from the OCSP (during its validity) to all end users accessing the TLS server
phishing	in an electronic communication attempt to obtain sensitive information (usernames, passwords, and credit card details) for malicious reasons
private key	unique data to create electronic signature / seal

public key	unique data to verify electronic signature / seal
PSP registrar	authority responsible for approving or rejecting authorization of payment services providers in their state, usually National Bank, in ETSI TS 119 495 called NCA (National Competent Authority)
qualified certificate for electronic signature or for electronic seal or for website authentication	certificate defined by trust services legislation
qualified signature / seal creation device	device meeting the requirements of eIDAS, annex II, intended for electronic signature / seal creation
relying party	party relying on a certificate in its operations
root CA	certification authority which issues certificates to subordinate certification authorities
secure cryptographic device	device on which the private key is stored
softcard	software emulation of smartcard for access to private key stored in HSM
SSL certificate	certificate for identification and encryption within SSL/TLS protocol communication
subordinate CA	CA issuing certificates to end users
supervisory body	the body supervising qualified trust services providers
trust service / qualified trust service	trust service / qualified trust service defined by eIDAS
trust services legislation	current legislation on trust services
TWINS	commercial product of I.CA consisting of:
	 qualified certificate for electronic signature;
	 non-qualified certificate which issuance is based only on contractual relationship between I.CA and end-user
two-factor authentication	authentication employing two of three factors – I know something (the password), I have something (a smartcard or a hardware token) or I am something (fingerprint, retina or iris reading)
written contract	text of the contract in electronic or paper form

Table 3 – Acronyms

Acronym	Explanation
ARC	Alarm Receiving Centre
ASCII	American Standard Code for Information Interchange, table containing binary codes of English alphabets, numbers and other common symbols
BIH	Bureau International de l'Heure – The International Time Bureau

bit	from English <i>binary digit</i> – a binary system digit – the fundamental and the smallest unit of information in digital technologies
BRG	document "Baseline Requirements for the Issuance and Management of Publicly-Trusted Certificates" published by CA/Browser Forum
СА	certification authority
CAA	DNS Resource Record - see RFC 6844
ccTLD	country code TLD, national top-level domain, usually user for countries, sovereign states or dependent territories, ASCII ccTLD identifiers are two letters long
CEN	European Committee for Standardization, an association of national standardization bodies
CEO	Chief Executive Officer
COO	Chief Operating Officer
СР	certificate policy
CPS	certification practice statement
CR	Czech Republic
CRL	Certificate Revocation List – the list of revoked certificates, which are not held as valid any longer
СТ	Certificate Transparency, the system to mitigate misissuance of certificate based on adding new certificate (or rather precertificate) to public logs making possible to detect the misissuance (especially fraudulent getting the certificate by other than authorized applicant)
ČSN	Czech Technical Norm
DER, PEM	methods of certificate encoding (certificate formats)
DV	Domain Validation, SSL certificate type
DNS	Domain Name System, a hierarchical decentralized naming system implemented by DNS servers which are exchanging information via DNS protocol to translate domain names to the numerical IP addresses
EBA	European Banking Association
EC	Elliptic Curve
ECC	Elliptic Curve Cryptography
eIDAS	REGULATION (EU) no 910/2014 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 23 July 2014 on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC
EN	European Standard, a type of ETSI standard
ESI	Electronic Signatures and Infrastructures
ETSI	European Telecommunications Standards Institute, a European standardization institute for information and communication technologies
EU	European Union

EV	Extended Validation, type of SSL certificate or certificate intended for websites authentication
EVCG	document "Guidelines For The Issuance And Management Of Extended Validation Certificates" published by CA/Browser Forum
EVCP	Extended Validation Certificate Policy, type of certificate policy
FAS	Fire Alarm System
FIPS	Federal Information Processing Standard, standards for information technologies for U.S. non-military state organizations
FQDN	Fully Qualified Domain Name, domain name that specifies all domain levels in Internet domain name system
GDPR	General Data Protection Regulation, REGULATION (EU) 2016/679 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on the protection of natural persons with regard to the processing of personal data and on the free movement of such data, and repealing Directive 95/46/EC (General Data Protection Regulation)
gTLD	generic TLD, top level domain (e.gorg for non-profit organizations)
html	Hypertext Markup Language, markup language for creating hypertext documents
http	Hypertext Transfer Protocol, protocol for exchanging html documents
https	Hypertext Transfer Protocol, protocol for secure exchanging of html documents
I.CA	První certifikační autorita, a.s.
IAS	Intrusion Alarm System
ICA_OID	OID belonging to OID space allocated to I.CA
ICANN	Internet Corporation for Assigned Names and Numbers, organization which among others assigns and administrates domain names and IP addresses
IEC	International Electrotechnical Commission, the global organization publishing standards for electrical and electronic engineering, communication technologies and related industries
IP	Internet Protocol, principal communications protocol in the Internet protocol suite for relaying packets across network and routing used in the Internet
IPS	Intrusion Prevention System
ISMS	Information Security Management System
ISO	International Organization for Standardization, an international organization of national standardization organizations; designation of standards
ІТ	Information Technology
ITU	International Telecommunication Union
ITU-T	Telecommunication Standardization Sector of ITU

MPSV	Ministry of Labor and Social Affairs of the Czech Republic
NCA	National Competent Authority - authority responsible for approving or rejecting authorization of payment services providers and assigning PSP numbers to them in particular state; see also PSP registrar above
NCP	Normalized Certificate Policy, non-qualified certificates certificate policy, qualitatively the same as certificate policy for issuing qualified certificates
NCP+	Extended Normalized Certificate Policy, NCP certificate policy requiring a secure cryptographic device
OCSP	Online Certificate Status Protocol, the protocol to identify public key certificate status
OID	Object Identifier
OSVČ	self-employed person
OV	Organization Validation, SSL certificate type
PDCA	Plan-Do-Check-Act, Deming cycle, management method for control and continuous improvement
PDS	PKI Disclosure Statement
PKCS	Public Key Cryptography Standards, designation for a group of standards for public key cryptography
PKI	Public Key Infrastructure
PSD	Payment Services Directive, DIRECTIVE 2007/64/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on payment services in the internal market
PSD2	DIRECTIVE (EU) 2015/2366 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL, superseding PSD and coming into effect January 13th 2018
PSP	Payment Service Provider
PSS	Probabilistic Signature Scheme, electronic signature schema developed by M. Bellar and P. Rogaway and standardized as part of PKCS#1 v2.1
PTC	Publicly-Trusted Certificate
PUB	Publication, FIPS standard designation
QSCD	Qualified Electronic Signature/Seal Creation Device (defined by eIDAS)
QWAC	Qualified Website Authentication Certificate
RA	registration authority
RFC	Request for Comments, designation for a range of standards and other documents describing web protocols, systems, etc.
RSA	signing and encrypting public key cipher (acronym from the names of the original authors - Rivest, Shamir and Adleman)
RTS	COMMISSION DELEGATED REGULATION (EU) 2018/389 of 27 November 2017 supplementing Directive (EU) 2015/2366 of the European Parliament and of the Council with regard to regulatory

	technical standards for strong customer authentication and common and secure open standards of communication
SCT	Signed Certificate Timestamp, signed timestamp from relevant CT log which confirms adding the precertificate
sha, SHA	type of hash function
SSCD	Secure Signature Creation Device (defined by directive 1999/93/ES)
SSL	Secure Sockets Layer, communication protocol, layer inserted between transport layer and application layer, providing securing of communication via encryption and authentication of communicating parties
TLD	Top Level Domain, top-level Internet domain, in domain name the top- level domain is placed at the end
TLS	Transport Layer Security, communication protocol superseding SSL
TS	Technical Specification, type of ETSI standard
TSA	Time-Stamping Authority
TSS	Time-Stamp Server
TSU	Time-Stamp Unit
UPN	User Principal Name, user name based on RFC 822
UPS	Uninterruptible Power Supply/Source
URI	Uniform Resource Identifier, defined-structure text string for accurate specification of a source of information
UTC	Coordinated Universal Time, the standard adopted on 1 January 1972 for the global coordinated time – Bureau International de l'Heure (BIH) plays the role of the 'official keeper' of the atomic time for the whole world
WHOIS	database including domain name registrant technical, billing and administrative contact information
ZOOÚ	current personal data protection legislation

2 PUBLICATION AND REPOSITORY RESPONSIBILITIES

2.1 Repositories

První certifikační autorita, a.s., sets up and operates repositories of both public and non-public information.

2.2 Publication of certification information

The basic addresses (also as the Information Addresses) for obtaining information about První certifikační autorita, a.s., and the links to find out more information are as follows:

Registered office:

První certifikační autorita, a.s.

Podvinný mlýn 2178/6

- 190 00 Praha 9
- Czech Republic
- Website: http://www.ica.cz;
- Registered offices of the registration authorities.

Electronic address for contact between general public and I.CA: info@ica.cz, data box of I.CA ID is a69fvfb.

The aforesaid website provides information about:

- Certificates of certification authorities and time-stamping authorities;
- Public certificates of end users the following information is published (and more information can be obtained from the certificate):
 - □ Certificate number;
 - □ Content of commonName;
 - □ Valid from date (specifying the hour, minute and second);
 - Link to where the certificate can be obtained in the specified format (DER, PEM, TXT);
- Certificate revocation list (CRL) the following information is published (and more information can be obtained from the CRL):
 - Date of CRL release;
 - □ CRL number;
 - Link to where the CRL can be obtained in the specified format (DER, PEM, TXT);
- Certification and other policies, practice statements and other public information.

Http and https are the permitted protocols for access to public information. I.CA may terminate or suspend access to some information without cause.

Any revocation of the Certificate because of suspected or actual compromise of a given private key will be announced by I.CA on its web Information Address and in Hospodářské noviny or Mladá fronta Dnes, daily newspapers with national distribution.

2.3 Time or frequency of publication

I.CA publishes information as follows:

- Certificate policy after a new version is approved and issued;
- Certification practice statement immediately;
- List of the certificates issued updated every time a new certificate subject to publication is issued;
- Certificate revocation list (CRL) see 4.9.7;
- Information about Certificate revocation with the reason of revocation immediately;
- Other public information no specific time limit, the general rule is that this information must correspond to the current state of the services provided.

2.4 Access controls on repositories

All public information is made available by I.CA free of charge without any restrictions.

Non-public information is available only to authorized employees of I.CA or the parties specified by the relevant legislation. Access to such information is governed by the rules defined in internal documentation.

3 IDENTIFICATION AND AUTHENTICATION

3.1 Naming

3.1.1 Types of names

All names are construed in accordance with current technical and other standards.

3.1.2 Need for names to be meaningful

For a Certificate to be issued, all names which can be validated given in the field subject must carry a meaning. See chapter 7 for the attributes supported for this field.

3.1.3 Anonymity or pseudonymity of subscribers

The Certificates issued under this CP do not support neither anonymity nor pseudonymity.

3.1.4 Rules for interpreting various name forms

The data specified in a Certificate application (format PKCS#10) are transferred to subject field attributes of the Certificate in the form they are specified in the application.

3.1.5 Uniqueness of names

The Authority guarantees the uniqueness of a Certificate's subject and issuer fields.

3.1.6 Recognition, authentication, and role of trademarks

Any Certificate issued under this CP may only contain trademarks which are property of První certifikační autorita, a.s.

3.2 Initial identity validation

The following chapters specify the rules for the authentication of I.CA when applying for a Certificate and the identity authentication of I.CA's representative.

3.2.1 Method to prove possession of private key

The ownership of the private key matching the public key in the certificate application must be proved by submitting the application in the PKCS#10 format. The application is provided with electronic seal using this private key whereby the private key holder provides evidence that he is the holder of the private key when the electronic seal is created.

3.2.2 Authentication of organization identity

This requires the submission of the original or certified copy of the entry in the Commercial Register or in another register specified by law, of a trade license, of a deed of incorporation, or of another document of the same legal force.

This document must contain full business name, identification number (if any), registered office, the name(s) of the person(s) authorized to act on behalf of the legal entity (authorized representatives).

3.2.3 Authentication of individual identity

This chapter describes the identity authentication procedure of the person representing I.CA applying for a Certificate.

The I.CA representing person's identity authentication procedure requires two documents, a primary and a secondary one, that show the data specified further in this chapter.

Valid personal identity card or passport must be used as the primary personal document for the citizens of the Czech Republic. Valid passport is the primary personal document for foreigners; citizens of EU member countries may use their valid personal identity card they use in their country as the proof of their identity.

The following data are authenticated in this document:

- Full civil name;
- Date and place of birth or the birth certification number if shown in the primary document;
- Number of the primary personal document;
- Permanent address (if shown in the primary document).

The secondary document must contain a unique identification, such as birth certification number or personal identity card number, matching it to the primary document and must show at least one of these attributes:

- Date of birth (or birth certification number if specified);
- Permanent address;
- Photograph of the face.

The secondary personal document data must be identical to those in the primary personal document.

3.2.4 Non-verified subscriber information

All information must be duly verified.

3.2.5 Validation of authority

Not applicable for this document.

3.2.6 Criteria for interoperation

Any collaboration between První certifikační autorita, a.s., and other trust service providers is always based on a contract in writing.

3.3 Identification and authentication for re-key requests

3.3.1 Identification and authentication for routine re-key

A new Certificate with a new public key needs to be issued. The same requirements as those in the initial identity validation apply.

3.3.2 Identification and authentication for re-key after revocation

I.CA does not support re-keying of revoked Certificates. The only way is to obtain a new Certificate with a new public key. The same requirements as those in the initial identity validation apply.

3.4 Identification and authentication for revocation request

The entities authorized to request for Certificate revocation are listed in 4.9.2.

Every certificate revocation request must be made in writing and signed by CEO of I.CA or by a member of the board authorized by him. His identity must be duly authenticated with their primary personal documents.

The data required for certificate revocation request are listed in 4.9.3.

4 CERTIFICATE LIFE-CYCLE OPERATIONAL REQUIREMENTS

4.1 Certificate application

4.1.1 Who can submit a certificate application

Issuance of the Certificate may be applied by CEO of I.CA or by a member of the board authorized by him.

4.1.2 Enrolment process and responsibilities

The written application for the Certificate is submitted to the management of První certifikační autorita, a.s., by Certificate applicant and must include the business name and OID of this certificate policy and the required CA name (commonName). The application must be signed by the applicant.

I.CA's representative applying for Certificate issuance is required to do the following, among others, things:

- Get acquainted with this CP and observe it;
- Provide true and complete information for the issuance of the Certificate;
- Check whether the data specified in the certificate application and the Certificate issued are correct and correspond to the required data;
- Choose a suitable Certificate revocation password (the minimum/maximum password length is 4/32 characters; permitted characters: 0..9, A..Z, a..z).

The Service provider is required to do the following, among other things:

- During the Certificate issuance process, check with RA all the data specified in the application against the documents submitted;
- Issue a Certificate that contains materially correct data on the basis of the information available to the Service provider as at the issuance of the Certificate;
- Publish public information in accordance with 2.2;
- Publish the Certificates issued;
- Provide any Service-related activity in accordance with trust services legislation, the relevant technical standards, this CP, the relevant CPS, the System Security Policy – Trustworthy Systems and the operational documentation.

4.2 Certificate application processing

4.2.1 Performing identification and authentication functions

Certificate issuance identification and authentication are performed pursuant to 3.2.2 and 3.2.3.

4.2.2 Approval or rejection of certificate applications

The management of První certifikační autorita, a.s., considers the application and approves or dismisses the issuance of the Certificate. The result is documented.

4.2.3 Time to process certificate applications

The written certificate application must be handled within five business days after the date the application is submitted to the company management.

I.CA must issue the Certificate when Certificate issuance is granted. The Certificate is issued within units of minutes.

4.3 Certificate issuance

4.3.1 CA actions during certificate issuance

When issuing the Certificate, the RA employees do the following:

- checks described in chapter 4.2.1;
- visual check as to conformity of the data in the Certificate application (the PKCS#10 structure);
- visual check as to the formal correctness of data.

Prove of private key ownership, checking the supported hash function in the certificate application (no weaker than sha-256), the competence check and the formal data correctness check are carried out both by the software on RA employees' work stations and that on the CA system core. If any of these checks gives a fail result, the Certificate issuance procedure is terminated.

4.3.2 Notification to subscriber by the CA of issuance of certificate

During the Certificate issuance process, the subscriber, or the representative of I.CA applying for the Certificate, receives information from the RA employee and the Certificate is sent to the contact e-mail provided during enrolment as mandatory data.

4.4 Certificate acceptance

4.4.1 Conduct constituting certificate acceptance

If the Certificate issuance requirements are met, representative of I.CA must accept the Certificate. The only way to refuse to take over the Certificate is to request for the Certificate's revocation in accordance with this CP.

4.4.2 Publication of the certificate by the CA

Certificates issued under this CP are published in the manner pursuant to 2.2.

The root certification authority's certificate and the subordinate certification authorities' certificates related to trust services are handed over to the supervisory body.

4.4.3 Notification of certificate issuance by the CA to other entities

Chapter 4.4.2 applies.

4.5 Key pair and certificate usage

4.5.1 Subscriber private key and certificate usage

Subscriber must, among other things:

- Observe all relevant provisions of the contract of the provision of the Services;
- Use the private key and the corresponding Certificate issued under a specific CP solely for the purposes defined in this CP and trust services legislation;
- Handle the private key corresponding to the public key contained in the Certificate issued under a specific CP in a manner as to prevent any unauthorized use of the private key;
- Notify immediately the Service provider of everything that leads to the Certificate's revocation, in particular of:
 - Suspected abuse of the private key; and
 - □ Invalidity or inaccuracy of Certificate's attributes;

in this case apply for the Certificate's revocation and stop using the pertinent private key.

4.5.2 Relying party public key and certificate usage

Relying parties must, among others:

- Obtain the certificates of certification authorities from a secure source (www.ica.cz, RA, relevant trusted list) and verify checksum and validity of these certificates;
- Perform any action necessary for them to check that these certificates have not been revoked.

4.6 Certificate renewal

Certificate renewal under this CP means the issuance of a new Certificate for still valid Certificate or for revoked Certificate, or for expired Certificate without changing the public key or any other information in the Certificate.

Certificate renewal is not provided.

In respect of this CP, it is always the issuance of a new Certificate with a new public key, with all the information having to be duly validated. The same requirements as those in the initial identity validation apply – see 3.2.

4.6.1 Circumstance for certificate renewal

See 4.6.

4.6.2 Who may request renewal

See 4.6.

4.6.3 Processing certificate renewal requests

See 4.6.

4.6.4 Notification of new certificate issuance to subscriber

See 4.6.

4.6.5 Conduct constituting acceptance of a renewal certificate

See 4.6.

4.6.6 Publication of the renewal certificate by the CA

See 4.6.

4.6.7 Notification of certificate issuance by the CA to other entities

See 4.6.

4.7 Certificate re-key

Certificate re-key under this CP means the issuance of a new Certificate with a different public key but with identical content of the attributes under the subject field of the Certificate key of which is requested to be re-keyed.

Certificate re-key is not provided.

In respect of this CP, it is always the issuance of a new certification authority Certificate with a new public key, and all information must be duly validated in this issuance procedure. The same requirements as those in the initial identity validation apply – see 3.2.

4.7.1 Circumstance for certificate re-key

See 4.7.

4.7.2 Who may request certification of a new public key

See 4.7.

4.7.3 Processing certificate re-keying requests

See 4.7.

- 4.7.4 Notification of new certificate issuance to subscriber
- See 4.7.
- 4.7.5 Conduct constituting acceptance of a re-keyed certificate

See 4.7.

4.7.6 Publication of the re-keyed certificate by the CA

See 4.7.

4.7.7 Notification of certificate issuance by the CA to other entities

See 4.7.

4.8 Certificate modification

Certificate modification means the issuance of a subsequent Certificate with the same public key but with at least one change of attributes in subject field concerning the subscriber or with removed field or with added field, content of which must be validated.

Certificate modification is not provided.

In respect of this CP, it is always the issuance of a new certification authority Certificate with a new public key, and all information must be duly validated in this issuance procedure. The same requirements as those in the initial identity validation apply – see 3.2.

4.8.1 Circumstance for certificate modification

See 4.8.

4.8.2 Who may request certificate modification

See 4.8.

4.8.3 Processing certificate modification requests

See 4.8.

4.8.4 Notification of new certificate issuance to subscriber

See 4.8.

4.8.5 Conduct constituting acceptance of modified certificate

See 4.8.

4.8.6 Publication of the modified certificate by the CA

See 4.8.

4.8.7 Notification of certificate issuance by the CA to other entities

See 4.8.

4.9 Certificate revocation and suspension

Certificate suspension service is not provided by I.CA.

4.9.1 Circumstances for revocation

A Certificate must be revoked as a result of the following, among other things:

- If the private key corresponding to the Certificate's public key is compromised or reasonably suspected to have been compromised;
- A Certificate's technical content or format is a non-acceptable risk, such as the given cryptographic/signing algorithm or the key length;
- In any event specified in trust services legislation or the relevant technical and other standards, such as invalid Certificate data.

4.9.2 Who can request revocation

Certificate revocation request may be submitted by:

- Subscriber (authorized requestor is in this case CEO of I.CA or a member of the board authorized by him); or
- The supervisory body or other entities specified in trust services legislation, as may be the case.

4.9.3 Procedure for revocation request

The Certificate is revoked under personal participation of CEO of I.CA or a member of the board authorized by him.

Any written certificate revocation request must include the Certificate's serial number in the decimal or hexadecimal format (introduced by the string '0x'), the name of the Authority which issued the Certificate, the full name of the person authorized to request for the Certificate's revocation, and the Certificate revocation password. If the person authorized to request for revocation does not know the Certificate revocation password, s/he must explicitly state this in the written application, along with the number of the primary personal document submitted in the certificate application procedure or the number of the new primary personal document if the original document has been replaced. The person must use this primary personal document to prove their identity.

4.9.4 Revocation request grace period

Certificate revocation request must be made immediately.

4.9.5 Time within which CA must process the revocation request

If the request meets the requirements, the employee in charge immediately revokes the Certificate in the CA's system, and the date and time the request is processed are the date and time of the Certificate's revocation. The CRL containing the serial number of the revoked Certificate must be issued immediately after that Certificate's revocation.

4.9.6 Revocation checking requirement for relying parties

Relying parties must take the course of action pursuant to 4.5.2.

4.9.7 CRL issuance frequency

The list of the revoked Certificates is issued after every Certificate revocation, and also in regular intervals no longer than one year after issuing previous CRL.

4.9.8 Maximum latency for CRLs

CRL is released immediately after the issuance, conditions described in chapters 4.9.5 are 4.9.7 always observed.

4.9.9 On-line revocation/status checking availability

On-line revocation/status checking using the OCSP protocol is a service available to the general public. Every subordinated certification authority certificate issued under this CP includes a link to the pertinent (authorized) OCSP responder.

OCSP responses comply with the RFC 6960 and RFC 5019 standards. The OCSP responder's certificate includes an id-pkix-ocsp-nocheck extension as defined in RFC 6960.

4.9.10 On-line revocation checking requirements

See 4.9.9.

4.9.11 Other forms of revocation advertisements available

Not applicable for this document; no other certificate revocation notification service is provided.

4.9.12 Special requirements for key compromise

The Certificate revocation procedure in the event of private key compromise is not different from the Certificate revocation procedure described above.

4.9.13 Circumstances for suspension

Not applicable for this document; Certificate suspension is not provided.

4.9.14 Who can request suspension

Not applicable for this document; Certificate suspension is not provided.

4.9.15 Procedure for suspension request

Not applicable for this document; Certificate suspension is not provided.

4.9.16 Limits on suspension period

Not applicable for this document; Certificate suspension is not provided.

4.10 Certificate status services

4.10.1 Operational characteristics

Lists of the public Certificates issued by the Authority are provided as published information; certificate revocation lists are provided as published information and by specifying the CRL distribution points in the certificates issued by the Authority.

The fact that the Authority provides Certificate status information as OCSP is specified in the Certificates issued by it.

4.10.2 Service availability

The Authority guarantees round-the-clock (24/7) availability and integrity of the list of the Certificates it has issued and the list of revoked certificates (CRLs), plus the availability of the OCSP service.

Response time to revocation request using CRL or OCSP is normally less than 10 seconds.

Revocation records on CRL or in OCSP response are kept at least to the end of Certificate's validity period.

4.10.3 Optional features

Not applicable for this document; no other Certificate status check characteristics are provided.

4.11 End of subscription

The certificate issuance contract expires when the last certificate issued under this contract expires.

4.12 Key escrow and recovery

Not applicable for this document; key escrow and recovery service is not provided.

4.12.1 Key escrow and recovery policy and practices

See 4.12.

4.12.2 Session key encapsulation and recovery policy and practices See 4.12.

5 FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS

The management, control and operating procedures primarily deal with:

- Trustworthy systems supporting trust services;
- All processes supporting trust services.

The management, control and operating procedures are addressed in the fundamental documents Corporate Security Policy, System Security Policy Trustworthy Systems, Certification Practice Statement, Business Continuity Plan and Recovery Plan as well as the more detailed internal documentation. These documents take account of the results of periodic risk analyses.

5.1 Physical controls

5.1.1 Site location and construction

The operating site buildings are situated in geographically different locations, which are also different from the site of the company headquarters, the business and development sites, the registration authority sites and the points of sale.

The trustworthy systems supporting trust service are situated on reserved premises of operating sites. These premises are secured in a manner similar to that required by the Classified Information Protection Act for the 'Confidential' category secure areas.

5.1.2 Physical access

See the internal documentation for the respective requirements as to physical access to the reserved premises (protected with mechanical and electronic features) of operating sites. Buildings are protected with intrusion alarm system (IAS), alarm receiving centre (ARC) and, as may be the case, a special system to monitor movement of persons and vehicles.

5.1.3 Power and air-conditioning

The premises housing the trustworthy systems supporting trust services have active airconditioning of adequate capacity, which keeps the temperature at $20^{\circ}C \pm 5^{\circ}C$ all year round. The supply of electricity is backed up with a UPS (Uninterruptible Power Supply) and a diesel unit.

5.1.4 Water exposures

The trustworthy systems supporting trust services are so located as to ensure they cannot be flooded by a 100-year flood. Where it is relevant operating sites have water ingress sensors to detect heating water leakage or rainfall leakage through the roof (as a result of heavy rains).

5.1.5 Fire prevention and protection

The buildings of the operating sites and the information storage sites have electronic fire alarm system (FAS). Fireproof insulation is installed in the entrance doors to the restricted areas in which the trustworthy systems supporting trust services are situated, and fire extinguishers are fitted in these areas.

5.1.6 Media storage

Archive media containing operational backups and electronic records are stored in metal boxes or safes. Copies are kept at a site geographically different from the site of the operating office where the records originated.

Any paper media required to be kept are stored in a site geographically different from the site of the operating office where the records originated.

5.1.7 Waste disposal

Any paper office waste is shredded before it leaves I.CA operating sites.

5.1.8 Off-site backup

The copies of operating and working backups are stored in a place designated by COO of I.CA and described in internal documentation.

5.2 Procedural controls

5.2.1 Trusted roles

Trusted roles are defined for selected activities carried out at I.CA. The trusted role employee appointment procedure, the trusted roles operation and their responsibilities are defined in internal documentation.

I.CA employee appointed to a trusted role may not be in a conflict of interests that could compromise the impartiality of operations of I.CA.

5.2.2 Number of persons required per task

Jobs are defined for the processes related to the key pairs of certification authorities and these jobs must be performed with more than a single person attending. These jobs include:

- Initialization of cryptographic module;
- Generating key pairs of all certification authorities;
- Destroying private keys of all certification authorities;
- Backup and restore of private keys of all certification authorities;
- Activation and deactivation of private keys of all certification authorities.

The number of attending persons is not defined for other jobs, but all persons must be authorized persons.

5.2.3 Identification and authentication for each role

Each role's employees are assigned identification (name and certificate) and authentication (password and private key) data for those components which are necessary for their jobs.

Selected jobs require two-factor authentication by trusted role employees.

5.2.4 Roles requiring separation of duties

The roles requiring separation of duties (and the roles' job descriptions) are described in internal documentation.

5.3 Personnel controls

5.3.1 Qualification, experience, and clearance requirements

I.CA's trusted role employees are selected accepted using the following criteria:

- Clean criminal record statement of criminal conviction records or affirmation is required;
- Bachelor's or master's degree in an accredited university program and ICT job experience of three years or longer, or secondary education and ICT job experience of five years or longer, of which at least one-year job experience in the provision of trust services;
- Knowledge in public key infrastructure and information security.

Any other I.CA employee taking part in providing trust services is accepted using the following criteria:

- Bachelor's or master's degree in an accredited university program, or secondary education;
- Basic orientation in public key infrastructure and information security.

Managers must have job experience or technical training in respect of the trustworthiness of trust services, the knowledge of security procedures with security responsibility, and experience in information security and risk assessment.

5.3.2 Background check procedures

The sources of information about all employees of I.CA are:

- The employees themselves;
- Persons familiar with a particular employee;
- Public sources of information.

Initial information is provided by employees at job interviews, and this information is updated at periodic appraisal interviews with the manager during employment.

5.3.3 Training requirements

I.CA employees receive technical training in the use of specific software and specialised devices. The training takes the form of self-study combined with guidance from a trained

employee. The training covers information security, personal protection data and other relevant topics.

5.3.4 Retraining frequency and requirements

I.CA employees are provided with the current developments in their spheres of interest two times every 12 months.

Training in the processes related to RA operations is held for RA employees at least once in every three years.

5.3.5 Job rotation frequency and sequence

I.CA employees are encouraged to acquire knowledge necessary for working in other roles at I.CA, in order to ensure substitutability for cases of emergency.

5.3.6 Sanctions for unauthorized actions

If an employee is detected to have been performing unauthorized activity, the employee is subject to the procedure described in internal documentation and governed by the Labour Code (this process does not prevent criminal prosecution if the unauthorized activity exhibits that degree of gravity).

5.3.7 Independent contractor requirements

I.CA may or must procure some activities from independent contractors but remains fully responsible for their operation. These business relations are regulated in bilateral business contracts with parties such as contracted registration authorities, application software developers, hardware suppliers, system software suppliers and other parties. These parties are required to observe the pertinent certificate policies, the relevant parts of internal documentation provided for them, and the required normative documents. Contractual penalties are applied for a breach of the obligations or duties specified in the said documents, or the contract with the contractor in breach is terminated immediately.

5.3.8 Documentation supplied to personnel

In addition to the certificate policy, the certification practice statement and the security and operational documentation, I.CA employees have available any other relevant standard, policy, manual and guidance they may need for their job.

5.4 Audit logging procedures

5.4.1 Types of events recorded

Subject to logging are all the events required by trust services legislation or the relevant technical and other standards to be logged, that is, for example, the life cycle events of Certificates.

The certification authorities' key pair generating is a special case of event logging. All this process complies with trust services legislation and the relevant technical and other standards.

Generating is carried out according to a pre-determined scenario in a physically secure environment and under the control of more I.CA employees in trusted roles. Protocol on key pair generating with data required by technical standards is signed by present employees in trusted roles. When the key pair of subordinate certification authority issuing SSL type certificates for end users is generated then the process is also video recorded.

When the key pair of root certification authority is generated, an auditor qualified in accordance with current technical standards personally attends the process, signs also the created protocol to confirm that the generating followed the pre-determined scenario and the measures to ensure integrity and confidentiality were in place.

All audit records are made, kept and processed to the extent as necessary, while preserving the proof of origin and maintaining integrity, availability, confidentiality and time authenticity.

The auditing system is designed and run in a manner ensuring audit data integrity, sufficient space for audit data, automatic non-rewriting of the audit file, user-friendly presentation of audit records, and audit file access limited to the defined users only.

5.4.2 Frequency of processing log

Audit records are checked and assessed at the intervals defined in internal documentation, or immediately when a security incident occurs.

5.4.3 Retention period for audit log

Unless the relevant legislation provides otherwise, audit records are kept for a minimum of ten years of the day they are made.

5.4.4 Protection of audit log

Both electronic and printed audit records are stored in a manner ensuring they are protected against change, theft and destruction (wilful or accidental).

Electronic audit records are stored in two copies. These audit records are stored on a medium each month or more frequently and this medium is kept outside the operating premises of I.CA.

Printed audit records are kept outside the operating premises of I.CA.

The protection of the aforesaid types of audit records is described in internal documentation.

5.4.5 Audit log backup procedures

Electronic audit records are backed up similarly to how other electronic information is backed up. No backup of printed audit records takes place.

5.4.6 Audit collection system (internal or external)

The audit record collection system is an internal one relative to the CA information systems.

5.4.7 Notification to event-causing subject

Parties are not notified of that an event is registered in an audit record.

5.4.8 Vulnerability assessments

První certifikační autorita, a.s., carries out periodic vulnerability assessments as part of risk assessments. Vulnerability monitoring of the hardware and software related to trust services is described in internal documentation.

5.5 Records archival

The storage of records, i.e., information and documentation, at První certifikační autorita, a.s., is regulated in internal documentation.

5.5.1 Types of records archived

I.CA archives the following electronic or printed records pertaining to the trust services provided, such as:

- Reports / protocols on the course of certification authorities key pair generating;
- Video recording of generating key pair of the subsequent certification authority issuing SSL type certificates to end users generating;
- Records related to the life cycle of certificates (especially the documents relating to validation of certificate issuance applications and certificate revocation requests);
- Information handling records, such as takeover, handover, saving, check, conversion from printed to electronic form, etc.;
- Operational and security documentation.

5.5.2 Retention period for archive

Records relating to the certificates of all I.CA certification authorities and corresponding OCSP responders, excluding appropriate private keys, are kept throughout the existence of I.CA. Other records are kept in accordance with chapter 5.4.3.

The record storage procedures are regulated by internal documentation.

5.5.3 Protection of archive

The premises where records are stored are secured in a manner based on risk analysis results and the Classified Information Protection Act.

The procedures to protect the stored records are regulated in internal documentation.

5.5.4 Archive backup procedures

The record backup procedures are regulated in internal documentation.

5.5.5 Requirements for time-stamping of records

If time-stamp tokens are used, they are qualified electronic time-stamp tokens issued by I.CA.

5.5.6 Archive collection system (internal or external)

Records are stored in a place designated by COO of I.CA.

Internal documentation regulates how both electronic and printed records are prepared for archival and stored. Records are kept of collecting the records subject to storage.

5.5.7 Procedures to obtain and verify archive information

Archived information and records are stored at sites designated therefore and are accessible to:

- I.CA employees if they need to have such an access for their job;
- Authorized inspection entities, the investigative, prosecuting and adjudicating bodies and courts of justice if required by legislation.

A written record is made of any such permitted access.

5.6 Key changeover

In standard situations (expiration of a certification authority's certificate), the key pair is replaced by issuing a new certificate a good time in advance (no later than one year prior to the expiration).

In non-standard situations (for instance such progress in cryptanalytic methods that could compromise the security of certificate issuance e.g., changes to cryptographic algorithms or key lengths) the key pair is replaced as soon as possible.

In both standard and non-standard situations, the replacement of the public key in Certificates is suitably notified to the public a good time in advance (if practicable).

5.7 Compromise and disaster recovery

5.7.1 Incident and compromise handling procedures

In the event of incident or compromise, I.CA takes a course of action in accordance with its internal business continuity plan and recovery plan, plus any other relevant internal documentation.

5.7.2 Computing resources, software, and/or data are corrupted

See 5.7.1.

5.7.3 Entity private key compromise procedures

In the case of reasonable concern that a private key of certification authorities has been compromised, I.CA does the following:

- Stops using the private key;
- Revokes immediately and permanently the pertinent Certificate and destroys the corresponding private key;

- Revokes all valid certificates issued by specific certification authority;
- Notifies this and the reason immediately on its web Information Address, and also the list of revoked certificates is used for disclosing this information;
- Notifies the supervisory body of that the pertinent certificate has been revoked and why it has been revoked.

A similar course of action will be taken in the event of such developments in cryptanalytic methods, such as changes to cryptanalytic algorithms or key length that could immediately compromise the security of trust services.

5.7.4 Business continuity capabilities after a disaster

In the event of accident, I.CA takes a course of action in accordance with its internal business continuity plan and recovery plan, plus any other relevant internal documentation.

5.8 CA or RA termination

The following rules apply to the termination of the Authority's operations:

- The termination of the Authority's operations must be notified in writing to the supervisory body and the parties having a contract with I.CA that directly concerns the provision of services;
- The termination of the Authority's operations must be published on the web page pursuant to 2.2;
- If the Authority's certificate's expiration is part of the termination of operations, this information plus the reason for expiration must be included in that notice;
- The termination of operations is a controlled process following a pre-defined plan, which includes the description of the procedure to preserve and disclose information for judicial or administrative proceedings discovery and for arranging the continuity of services;
- The Authority or its successor must be able to revoke Certificates and publish CRLs as long as any certificate issued by the Authority is valid;
- After that the Authority must demonstrably destroy its private key, make a record of this destruction and keep this record in accordance with this CP; particular RA (see 1.3.2) corresponding with Authority will be also terminated.

Termination of subsequent CAs and corresponding RAs is described in CPs under which the certificates are issued.

In the event of withdrawal of the qualified Service provider status:

- The information must be notified in writing or electronically to all parties having a contract with I.CA that directly concerns the provision of the relevant services;
- The information must be published in accordance with 2.2. at all offices of registration authorities and must also communicate that certification authorities' certificates cannot be used in accordance with the purpose of their issuance any longer;
- The subsequent course of action will be decided by CEO of I.CA while taking account of the decision of the supervisory body.

6 TECHNICAL SECURITY CONTROLS

6.1 Key pair generation and installation

6.1.1 Key pair generation

Generating of certification authorities' and their corresponding OCSP responders' key pairs which is done in reserved areas of the operating site in compliance with the requirements of chapters 5.2 and 5.4.1 is carried out in cryptographic modules meeting the requirements of trust services legislation, that is ETSI and CEN standards.

Key pairs of the employees taking part in the issuance of Certificates to end users are generated on chip cards that meet the QSCD requirements. The private keys of these key pairs data are stored on the smartcard in non-exportable form and PIN needs to be entered to use the keys.

All the requirements on the generating of these key pairs are described in internal documentation.

6.1.2 Private key delivery to subscriber

Not applicable for this document; the private keys of certification authorities and their corresponding OCSP responders are stored in the cryptographic modules which are under sole control of I.CA.

The service of generating key pairs to employees taking part in issuing Certificates is not provided.

6.1.3 Public key delivery to certificate issuer

The public key is delivered to Certificate issuer in the Certificate application (the PKCS#10 format).

6.1.4 CA public key delivery to relying parties

The following are the options guaranteed for obtaining certification authority public key contained in its certificate:

- Receiving the key at RA;
- Receiving the key via the web information addresses of I.CA and the relevant supervisory body, or through the supervisory body's journal;
- Each certificate applicant receives the Authority's certificate when obtaining the applicant's primary certificate.

6.1.5 Key sizes

The size of the key of I.CA root certification authority using ECC cryptography is 384 bits at minimum, the size of the keys in certificates od subordinate certification authorities issued by this root certification authority is 256 bits at minimum, the size of the keys of OCSP responders is 256 bits at minimum.

6.1.6 Public key parameters generation and quality checking

Parameters of the algorithms used for creating public keys of certification authorities and their corresponding OCSP responders comply with requirements stated in trust services legislation and in the technical and other standards referred to therein. These keys are generated and checked by relevant hardware and software.

Parameters of the algorithms used for creating public keys of other subscribers must comply with these requirements too.

6.1.7 Key usage purposes (as per X.509 v3 key usage field)

The key usage options are specified in the Certificate's extension.

6.2 Private key protection and cryptographic module engineering controls

6.2.1 Cryptographic module standards and controls

The key pairs of certification authorities and their corresponding OCSP responders are generated and the corresponding private keys are stored on cryptographic modules which meet the requirements of trust services legislation, that is ETSI and CEN standards, and are used in accordance with their certification.

Employees taking part in issuing certificates use the smartcard meeting the QSCD requirements.

6.2.2 Private key (n out of m) multi-person control

If cryptographic module related operations require the presence of more persons, then each of them knows only some part of the code required for these operations.

6.2.3 Private key escrow

Not applicable for this document; private key escrow service is not provided.

6.2.4 Private key backup

Private keys of certification authorities and their corresponding OCSP responders protected by cryptographic modules are backed up in encrypted form, which provides the same level of protection as the cryptographic devices.

Not applicable for private keys of employees taking part in issuing certificates, these private keys are generated on smartcards as non-exportable.

6.2.5 Private key archival

When certification authorities' and their corresponding OCSP responders' private keys expire, they are not archived, but destroyed including their backup copies.

Archiving period of private keys of employees taking part in issuing certificates is limited by the memory capacity of the smartcard.

6.2.6 Private key transfer into or from a cryptographic module

Private keys of certification authorities and their corresponding OCSP responders are generated in cryptographic modules (as non-exportable) and cannot be exported out of these modules (operated in certified mode) in any form¹. Import of the private key into the cryptographic module is not performed.

Not applicable for private keys of employees taking part in issuing certificates, these private keys are generated on smartcards as non-exportable.

6.2.7 Private key storage on cryptographic module

Private keys of certification authorities and their corresponding OCSP responders are stored on cryptographic modules meeting the requirements of trust services legislation, that is ETSI and CEN standards. Cryptographic modules are operated in compliance with their certification.

Private keys of employees taking part in issuing certificates are stored on smartcards meeting the QSCD requirements.

6.2.8 Method of activating private key

Activation of certification authorities' and their corresponding OCSP responders' private keys (allowing the use of these private keys) is done:

- In case of smartcard activation by inserting the smartcard into card reader and entering the password;
- In case of softcard activation by entering the softcard and password.

Private keys of employees taking part in issuing certificates are activated by inserting the smartcard into and entering PIN.

6.2.9 Method of deactivating private key

Deactivation of certification authorities' and their corresponding OCSP responders' private keys is done by removing the smartcard from card reader or by terminating the specific application.

Private keys of employees taking part in issuing certificates are deactivated by removing the smartcard from card reader.

6.2.10 Method of destroying private key

After expiration of specific certification authority's private key and based on subsequent decision of CEO of I.CA this private key is destroyed according to specific procedure including all backups of this key. Destroying is documented in a written record.

¹ There is one exception – encrypted backup, which can be used only in cryptographic module (or in HA/LB modules) where the key pair was generated.

Private keys of OCSP responders are destroyed on the decision of I.CA representative when issuing OCSP responder's certificate. Destroying is documented in a written record.

Destroying private keys of employees taking part in issuing certificates is fully within the competence of these employees, it is not ordered. It is necessary only when the smartcard memory is full.

6.2.11 Cryptographic module rating

Cryptographic modules used for generating of key pairs and storing corresponding private keys of certification authorities and their corresponding OCSP responders meet the requirements of trust services legislation, that is ETSI and CEN standards and are used in accordance with their certification.

Smartcards used for generating of key pairs and storing corresponding private keys of employees taking part in issuing certificates meet QSCD requirements.

6.3 Other aspects of key pair management

6.3.1 Public key archival

All public keys as part of Certificates are archived throughout the existence of I.CA.

6.3.2 Certificate operational periods and key pair usage periods

The maximum period of validity of each Certificate issued is specified in the body of that Certificate and is the same as key pair usage period.

6.4 Activation data

6.4.1 Activation data generation and installation

Activation data of certification authorities' and their corresponding OCSP responders' private keys (smartcards or softcards) are created before or during the generating of the corresponding key pair.

Activation data of employees' taking part in issuing certificates private keys is PIN, which is under sole control of these employees.

6.4.2 Activation data protection

Activation data of certification authorities' and their corresponding OCSP responders' private keys (smartcards or softcards) are protected by passwords.

Activation data of employees taking part in issuing certificates private keys protection is fully within the competence of these employees.

6.4.3 Other aspects of activation data

Not applicable for this document.

6.5 Computer security controls

6.5.1 Specific computer security technical requirements

The level of security of the components used in providing trust services is, including the scope of necessary evaluations and assessments and also trustworthy systems configuration checks, and their periodicity, defined for qualified services in trust services legislation and the technical standards referred to therein, otherwise in the relevant technical standards.

6.5.2 Computer security rating

The assessment of I.CA computer security is based on the requirements set out in the specified technical standards and norms, in particular:

- CEN/TS 419261 Security Requirements for Trustworthy Systems Managing Certificates and Time-stamps;
- ČSN ETSI EN 319 401 Electronic Signatures and Infrastructures (ESI) General Policy Requirements for Trust Service Providers;
- ETSI EN 319 401 Electronic Signatures and Infrastructures (ESI); General Policy Requirements for Trust Service Providers;
- ČSN ETSI EN 319 403 Electronic Signatures and Infrastructures (ESI) Trust Service Provider Conformity Assessment – Requirements for Conformity Assessment Bodies Assessing Trust Service Providers;
- ETSI EN 319 403 Electronic Signatures and Infrastructures (ESI); Trust Service Provider Conformity Assessment – Requirements for Conformity Assessment Bodies Assessing Trust Service Providers;
- ČSN ETSI EN 319 411-1 Electronic Signatures and Infrastructures (ESI) Policy and Security Requirements for Trust Service Providers Issuing Certificates – Part 1: General Requirements;
- ETSI EN 319 411-1 Electronic Signatures and Infrastructures (ESI); Policy and Security Requirements for Trust Service Providers Issuing Certificates; Part 1: General Requirements;
- ČSN ETSI EN 319 411-2 Electronic Signatures and Infrastructures (ESI) Policy and Security Requirements for Trust Service Providers Issuing Certificates – Part 2: Requirements for Trust Service Providers Issuing EU Qualified Certificates;
- ETSI EN 319 411-2 Electronic Signatures and Infrastructures (ESI); Policy and Security Requirements for Trust Service Providers Issuing Certificates; Part 2: Requirements for Trust Service Providers Issuing EU Qualified Certificates;
- ČSN ETSI EN 319 412-1 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 1: Overview and Common Data Structures;
- ETSI EN 319 412-1 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 1: Overview and Common Data Structures;

- ČSN ETSI EN 319 412-2 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 2: Certificate Profile for Certificates Issued to Natural Persons;
- ETSI EN 319 412-2 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 2: Certificate Profile for Certificates Issued to Natural Persons;
- ČSN ETSI EN 319 412-3 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 3: Certificate Profile for Certificates Issued to Legal Persons;
- ETSI EN 319 412-3 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 3: Certificate Profile for Certificates Issued to Legal Persons;
- ČSN ETSI EN 319 412-4 Elektronické podpisy a infrastruktury (ESI) Profily certifikátu – Část 4: Profil certifikátu pro certifikáty webových stránek;
- ETSI EN 319 412-4 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 4: Certificate profile for web site certificates;
- ČSN ETSI EN 319 412-5 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 5: QC Statements;
- ETSI EN 319 412-5 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 5: QCStatements;
- ČSN EN 419 221-5 Protection profiles for TSP Cryptographic modules Part 5 Cryptographic Module for Trust Services;
- EN 419 221-5 Protection profiles for TSP Cryptographic modules Part 5 Cryptographic Module for Trust Services;
- FIPS PUB 140-2 Requirements for Cryptographic Modules;
- ISO/IEC 15408-1:2009 Information technology Security techniques Evaluation criteria for IT security — Part 1: Introduction and general model;
- ČSN EN ISO/IEC 15408-2 Information technology Security techniques Evaluation criteria for IT security - Part 2: Security functional components;
- ISO/IEC 15408-2:2008 Information technology Security techniques Evaluation criteria for IT security — Part 2: Security functional components;
- ČSN EN ISO/IEC 15408-2 Information technology Security techniques Evaluation criteria for IT security — Part 3: Security assurance components;
- ISO/IEC 15408-3:2008 Information technology Security techniques Evaluation criteria for IT security — Part 3: Security assurance components;
- ETSI TS 119 312 Electronic Signatures and Infrastructures (ESI); Cryptographic Suites;
- ČSN ISO/IEC 27006 Information Technology Security Techniques Requirements for Bodies Providing Audit and Certification of Information Security Management Systems.
- ISO/IEC 17021 Conformity Assessment -- Requirements for Bodies Providing Audit and Certification of Management Systems;
- ISO/IEC 17065 Conformity Assessment -- Requirements for Bodies Certifying Products, Processes and Services.
- ISO 3166-1 Codes for the Representation of Names of Countries and Their Subdivisions – Part 1: Country Codes;
- ITU-T X.501 Information Technology Open Systems Interconnection The Directory: Models;

- ITU-T X.509 Information Technology Open Systems Interconnection The Directory: Public-key and Attribute Certificate Frameworks;
- ITU-T X.520 Information Technology Open Systems Interconnection The Directory: Selected Attribute Types;
- RSA Laboratories PKCS#10: Certification Request Syntax Standard;
- RFC 6960 X.509 Internet Public Key Infrastructure Online Certificate Status Protocol OCSP;
- RFC 3647 Internet X.509 Public Key Infrastructure Certificate Policy and Certification Practices Framework;
- RFC 5019 The Lightweight Online Certificate Status Protocol (OCSP) Profile for High-Volume Environments;
- RFC 5280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile;
- EN 301 549 Accessibility requirements for ICT products and services;

6.6 Life cycle technical controls

6.6.1 System development controls

System development is carried out in accordance with internal documentation.

6.6.2 Security management controls

Information security management and compliance with technical standards are inspected as part of the periodic trust services audits and conformity assessments and also in information security management system (ISMS) audits.

Information security at I.CA is managed by the following standards:

- ČSN ISO/IEC 27000 Information Technology Security Techniques Information Security Management Systems – Overview and Vocabulary;
- ČSN ISO/IEC 27001 Information Technology Security Techniques Information Security Management Systems – Requirements;
- ČSN ISO/IEC 27002 Information Technology Security Techniques Information Security Management Systems – Code of Practice for Information Security Controls.

6.6.3 Life cycle security controls

I.CA takes the Plan-Do-Check-Act (PDCA) procedural approach to life cycle security management; the PDCA approach consists of the following consecutive processes:

- Establishing defining the scope and the boundaries for information security management, determining a security policy and plans, and choosing security controls depending on the risks identified, all this in accordance with the corporate security policy;
- Implementing and operating effective and systematic enforcement of the selected security controls;

- Monitoring and reviewing providing feedback, regular monitoring and evaluation of the successful and the poor aspects of information security management, providing the knowledge gained for the company management for assessment;
- Maintenance and improvement implementing corrective and improvement measures as decided by the company management.

6.7 Network security controls

Network infrastructure of the operating site is protected with a firewall-type commercial product with an integrated intrusion prevention system. The detailed network security management solution is described in internal documentation.

6.8 Time-stamping

See 5.5.5 for the time-stamping solution.

7 CERTIFICATE, CRL AND OCSP PROFILES

7.1 Certificate profile

Table 4 – Authority's certificate

Field	Content	Comments
version	v3 (0x2)	
serialNumber	unique serial number of the Certificate	
signatureAlgorithm	ecdsa-with-SHA384 at minimum	
issuer		
commonName	I.CA Root CA/ECC MM/YYYY	<i>MM/YYYY</i> : the month and the year when the root CA's certificate is issued
organizationName	První certifikační autorita, a.s.	
country	CZ	
organizationIdentifier	NTRCZ-26439395	
validity		
notBefore	start of Certificate's validity	UTC
notAfter	notBefore + 25 years	UTC
subject		
commonName	I.CA Root CA/ECC MM/YYYY	<i>MM/YYYY</i> : the month and the year when the root CA's certificate is issued;
organizationName	První certifikační autorita, a.s.	
country	CZ	
organizationIdentifier	NTRCZ-26439395	
subjectPublicKeyInfo		
algorithm	id-ecPublicKey, NIST P-384 (secp384r1) at minimum	
subjectPublicKey	384 bits at minimum	
extensions	certificate extensions	see Table 6
signature	advanced electronic seal of Certificate's issuer	

Field	Content	Comments
version	v3 (0x2)	
serialNumber	unique serial number of the Certificate	
signatureAlgorithm	ecdsa-with-SHA384 at minimum	
issuer	certificate issuer (Authority)	see Table 4
validity		
notBefore	start of Certificate's validity	UTC
notAfter	notBefore + 10 years	UTC
subject		
commonName	name of the subordinate certification authority	includes the string <i>MM</i> /YYYY: the month and the year the subordinate certification authority's certificate is issued
organizationName	První certifikační autorita, a.s.	
country	CZ	
organizationIdentifier	NTRCZ-26439395	
subjectPublicKeyInfo		
algorithm	id-ecPublicKey, NIST P-384 (secp384r1) at minimum	
subjectPublicKey	384 bits at minimum	
extensions	certificate extensions	see Table 7
signature	advanced electronic seal of the Certificate's issuer	

Table 5 – Subordinate certification authority's certificate

7.1.1 Version number(s)

Any certificate issued complies with standard X.509, version 3.

7.1.2 Certificate extensions

Table 6 – Authority's certificate extensions

Extension	Content	Comments
certificatePolicies		non-critical
.policyInformation (1)		
policyIdentifier	2.5.29.32.0 (anyPolicy)	

basicConstraints		critical
сА	True	
keyUsage	keyCertSign, cRLSign	critical
subjectKeyIdentifier		non-critical
keyldentifier	hash of the Authority's public key	

Table 7 – Subordinate certification authority's certificate extensions

Extension	Content	Comments
certificatePolicies .policyInformation (1)		non-critical
policyIdentifier	2.5.29.32.0 (anyPolicy)	
basicConstraints		critical
cA	True	
pathLenConstraint	0	
keyUsage	keyCertSign, cRLSign	critical
extendedKeyUsage	according to the content of subordinate certification authority certificate application	non-critical in compliance with BRG and Mozilla requirements to limit the types of certificates issued by specific subordinate certification authority
subjectKeyIdentifier		non-critical
keyldentifier	hash of this subordinate certification authority's public key	
authorityKeyIdentifier		non-critical
keyldentifier	hash of the Authority's public key	
CRLDistributionPoints*	http://qcrldp1.ica.cz/rcaYY_ecc.crl http://qcrldp2.ica.cz/rcaYY_ecc.crl http://qcrldp3.ica.cz/rcaYY_ecc.crl	non-critical
authorityInformationAccess		non-critical
id-ad-ocsp*	http://ocsp.ica.cz/rcaYY_ecc	URI (http) to root CA's OCSP responder

id-ad-calssuers*	http://r.ica.cz/rcaYY_ecc.cer	URI (http) to root CA's certificate
------------------	-------------------------------	--

YY – the last two digits of the year when the Authority's certificate is issued.

7.1.3 Algorithm object identifiers

The algorithms used in providing trust services are in compliance with the relevant technical standards.

7.1.4 Name forms

Name forms in issued Certificates comply with RFC 5280 standard. The provisions of 3.1 also apply.

7.1.5 Name constraints

Not applicable for the certificates issued under this CP.

7.1.6 Certificate policy object identifier

This document's/policy's OID is specified in 1.2. Certification authorities' certificates include a special anyPolicy policy identification, the OID of which is 2.5.29.32.0.

7.1.7 Usage of Policy Constraints extension

Not applicable for Certificates issued under this CP.

7.1.8 Policy qualifiers syntax and semantics

See Certificate extensions in 7.1.2 above.

7.1.9 Processing semantics for the critical Certificate Policies extension

Not applicable for this document - not classified as critical.

7.2 CRL profile

Table 8 – CRL profile²

Attribute	Content
version	v2(0x1)
signatureAlgorithm	ecdsa-with-SHA384 at minimum

² I.CA reserves the right to modify the set and the content of the CRL fields as may be required by updated ETSI standards or third parties (Microsoft, for example).

issuer	CRL issuer	
thisUpdate	date and time of issue (UTC)	
nextUpdate	thisUpdate + 365 days at maximum (UTC)	
revokedCertificates	list of revoked certificates	
crlEntries		
userCertificate	revoked certificate's serial number	
revocationDate	certificate revocation date and time	
crlEntryExtensions	list attribute extension – see Table 11	
crlExtensions	CRL extensions – see Table 11	
signature	advanced electronic seal of CRL's issuer	

7.2.1 Version number(s)

Certificate revocation lists are issued pursuant to X509, version 2.

7.2.2 CRL and CRL entry extensions

Table 9 – CRL extensions³

Attribute	Content	Comments
crlEntryExtensions		
CRLReason	certificate's revocation reason; the certificateHold reason is not admissible as it is out of use	non-critical, optional
	another reason than unspecified (0) is given when subordinate CA's certificate is revoked	
crlExtensions		
authorityKeyIdentifier		
keyldentifier	hash of the CRL issuer's (Authority's) public key	non-critical
CRLNumber	unique number of the CRL	non-critical

7.3 OCSP profile

Both the OCSP request profile and the OCSP response profile comply with RFC 6960 and RFC 5019.

³ I.CA reserves the right to modify the set and the content of the CRL extensions as may be required by updated ETSI standards or third parties (Microsoft, for example).

OCSP responses are of the BasicOCSPResponse type and contain all mandatory fields. An optional revocationReason field is included for revoked certificates. When subordinate certification authority certificate is revoked, another reason than unspecified (0) is given.

The unAuthorized response is given for any certificate not issued by the relevant CA. Http only is used as the transmission protocol.

See the relevant certification practice statement for more detail.

7.3.1 Version number(s)

Version 1 is specified in a certificate status request and response using the OCSP protocol.

7.3.2 OCSP extensions

The specific extensions for OCSP protocol certificate status requests and responses are given in the relevant certification practice statement.

8 COMPLIANCE AUDIT AND OTHER ASSESMENTS

8.1 Frequency or circumstances of assessment

The assessment interval and circumstances are defined in trust services legislation and the technical standards referred to therein regulating the assessment procedure.

The Microsoft Trusted Root Program assessment interval and circumstances are strictly defined by Microsoft, and the audit period is not longer than one year.

The intervals for other assessments are specified in the relevant technical standards.

8.2 Identity/qualifications of assessor

The identity (accredited conformity assessment entity) and the qualification of the assessor carrying out the assessment pursuant to trust services legislation are defined in this legislation and the technical standards referred to therein.

The identity (accredited conformity assessment entity) and the qualification of the assessor carrying out assessment defined by Microsoft Trusted Root Program are described in ETSI EN 319 403.

The identity of the assessor carrying out other assessments is specified in the relevant technical standards.

8.3 Assessor's relationship to assessed entity

Internal assessor is not subordinate to the organisational unit which provides the operation of trust services.

External assessor is an assessor without any property or personal relation to I.CA.

8.4 Topics covered by assessment

The areas to be assessed in an assessment required under trust services legislation are those as specified in that legislation.

The areas to be assessed in an assessment required for Microsoft Trusted Root Program are strictly given by requirements of Microsoft Company.

The areas to be assessed in any other assessment are specified in the technical standards under which the assessment is made.

8.5 Actions taken as a result of deficiency

The findings in any type of assessment are communicated to the I.CA security manager, who makes sure that any defect identified is remedied. If defects are identified that critically prevent the provision of a specific trust service, I.CA must suspend that service until the defects are remedied.

8.6 Communication of results

Assessment result notification is subject to the requirements of trust services legislation and the relevant technical standards; the notification of Microsoft Trusted Root Program assessment results is subject to Microsoft requirements.

Assessments results are notified as a written report handed over by the assessor to CEO and the security manager of I.CA.

The I.CA security manager calls a security committee meeting as soon as possible and communicates the final report at the meeting; company management members must attend the meeting.

9 OTHER BUSINESS AND LEGAL MATTERS

9.1 Fees

9.1.1 Certificate issuance or renewal fees

První certifikační autorita, a.s., is the operator of all the certification authorities the Certificates of which have been issued under this CP. No fee is charged for the issuance of certificates by the root certification authority.

9.1.2 Certificate access fees

No fee is charged by I.CA for electronic access to the certificates issued under this CP.

9.1.3 Revocation or status information access fees

No fee is charged by I.CA for electronic access to revocation information (CRL) and status information (OCSP) about the certificates issued under this CP.

9.1.4 Fees for other services

Not applicable for this document.

9.1.5 Refund policy

Not applicable for this document.

9.2 Financial responsibility

9.2.1 Insurance coverage

První certifikační autorita, a.s., represents it holds the valid business risk insurance policy that covers financial damage.

První certifikační autorita, a.s., has drawn an employee liability insurance policy for each employee, with a scope of coverage as determined by the company's board of directors.

9.2.2 Other assets

První certifikační autorita, a.s., represents it has available financial resources and other financial assurances sufficient for providing trust services given the risk of a liability-fordamage claim.

See the Annual Report of První certifikační autorita, a.s., published in Commercial Register for detailed information on the company's assets.

9.2.3 Insurance or warranty coverage for end-entities

Not applicable for this document.

9.3 Confidentiality of business information

9.3.1 Scope of confidential information

I.CA's confidential information covers any information other than public information and other than that published in the manner pursuant to 2.2, including:

- All private keys, which are employed in providing trust services;
- I.CA's business information;
- Any internal information and documentation;
- Any personal data.

9.3.2 Information not within the scope of confidential information

Public information is only the information designated as public and that published in the manner pursuant to 2.2.

9.3.3 Responsibility to protect confidential information

I.CA employee who comes in contact with confidential information may not disclose this information to a third party without consent of CEO of I.CA.

9.4 Privacy of personal information

9.4.1 Privacy plan

I.CA protects personal data and other non-public information in accordance with the relevant legislation, which means ZOOU and GDPR in particular.

9.4.2 Information treated as private

Any personal data subject to protection under relevant legislation are treated as private.

I.CA employees or the entities defined by current legislation that come into contact with personal data must maintain confidentiality of these data and the security controls the disclosure of which would put the security of these data at risk. The confidentiality duty survives the termination of employment or other similar relationship, or the completion of pertinent work.

9.4.3 Information not deemed private

Any information outside the scope of relevant legislation is not considered personal data.

9.4.4 Responsibility to protect private information

CEO of I.CA is responsible for the protection of personal data.

9.4.5 Notice and consent to use private information

I.CA deals with the notifying of personal data use and consents to personal data processing in accordance with the relevant legislation.

9.4.6 Disclosure pursuant to judicial or administrative process

I.CA discloses personal data for judicial or administrative purpose in accordance with the relevant legislation.

9.4.7 Other information disclosure circumstances

I.CA provides access to personal strictly as regulated in relevant legislation.

9.5 Intellectual property rights

This CP, all related documents, the website content and the procedures facilitating the operation of trustworthy systems supporting trust services are copyrighted by První certifikační autorita, a.s., and are important know-how thereof.

9.6 Representations and warranties

9.6.1 CA representations and warranties

I.CA warrants that:

- It will only use the private keys pertinent to the Authority's certificates for creating the electronic seal of the Certificates issued, of the lists of revoked certificates issued by it and of the certificates of its OCSP responder;
- The Authority-issued Certificates meets the requirements of the relevant technical standards and trust services legislation;
- It will revoke the Authority-issued Certificates if the revocation request is submitted in the manner defined in this CP.

9.6.2 RA representations and warranties

Not applicable for this document; see 1.3.2.

9.6.3 Subscriber representations and warranties

The subscriber acts in accordance with the relevant technical standards and trust services legislation and warrants that the information given by him are correct throughout the life cycle of the usage of trusted services.

9.6.4 Relying parties representations and warranties

Relying parties observe this CP.

9.6.5 Representations and warranties of other participants

Not applicable for this document.

9.7 Disclaimers of warranties

První certifikační autorita, a.s., only provides those warranties as given in 9.6.

9.8 Limitations of liability

První certifikační autorita, a.s., is not responsible for any damage suffered by relying parties where the relying party fails to meet the obligations required under the certificate policy under which the pertinent certificate is issued. První certifikační autorita, a.s., is also not responsible for any damage resulting from breach of obligations of I.CA as a result of force majeure.

9.9 Indemnities

Not applicable for this document; see policies of the authorities which issue certificates to end users.

9.10 Term and termination

9.10.1 Term

This CP takes effect on the date specified in chapter 10 and remains in effect no shorter than the expiration of the last Certificate issued under this CP.

9.10.2 Termination

CEO of První certifikační autorita, a.s., is the sole person authorized to approve the termination of this CP.

9.10.3 Effect of termination and survival

The obligations of I.CA arising from this CP survive the expiration thereof until the expiration of the last Certificate issued under this CP.

9.11 Individual notices and communications with participants

All the participating parties are organisational parts of I.CA and their mutual communication is governed by internal rules of I.CA.

9.12 Amendments

9.12.1 Procedure for amendment

This procedure is a controlled process described in internal documentation.

9.12.2 Notification mechanism and period

The release of a new CP version is always notified as published information.

9.12.3 Circumstances under which OID must be changed

CP's OID must be changed when the changes of the CP will materially reduce the assurance that the Certificate is trusted and will have a significant effect on the acceptability of the Certificate in compliance with trust services legislation.

Any change to this CP results in a new version of the document.

9.13 Disputes resolution provisions

All the participating parties are organisational components of I.CA and the resolution of their disputes is governed by internal rules of I.CA.

9.14 Governing law

The business of První certifikační autorita, a.s., is governed by the legal order of the Czech Republic.

9.15 Compliance with applicable law

The system of providing trust services is in compliance with the statutory requirements of EU and the Czech Republic and with all relevant international standards.

9.16 Miscellaneous provisions

9.16.1 Entire agreement

Not applicable for this document.

9.16.2 Assignment

Not applicable for this document.

9.16.3 Severability

If a court or a public authority with jurisdiction over the activities covered by this CP establishes that the implementation of a mandatory requirement is unlawful, the scope of that requirement will be so limited as to ensure the requirement is lawful and complies with relevant legislation.

9.16.4 Enforcement (attorneys' fees and waiver of rights)

Not applicable for this document.

9.16.5 Force majeure

První certifikační autorita, a.s., is not responsible for breaching its obligations stipulated in client contract if it is a result of force majeure, such as major natural disaster, major disaster caused by human activity, strike or civil unrest always followed by the declaration of a situation of emergency, or the declaration of a threat to the state or a state of war, or communication failure.

9.17 Other provisions

Not applicable for this document.

10 FINAL PROVISIONS

This certificate policy issued by První certifikační autorita, a.s., takes force and effect on date mentioned above in Table 1.