

První certifikační autorita, a.s.



Certification Policy

for Issuing Qualified Certificates for Electronic
Seals PSD2
(RSA Algorithm)

The Certification Policy for Issuing Qualified Certificates for Electronic Seals PSD2 (RSA Algorithm) is a public document, which is the property of První certifikační autorita, a.s., and has been prepared as integral part of comprehensive security documentation. No part of this document may be reproduced without the written consent of the copyright holder.

Version 2.14

CONTENT

- 1 Introduction 11
 - 1.1 Overview 11
 - 1.2 Document name and identification 12
 - 1.3 PKI Participants..... 12
 - 1.3.1 Certification authorities 12
 - 1.3.2 Registration authorities 12
 - 1.3.3 Subscribers 13
 - 1.3.4 Relying parties 13
 - 1.3.5 Other participants 13
 - 1.4 Certificate usage 13
 - 1.4.1 Appropriate certificate uses 13
 - 1.4.2 Prohibited certificate uses 13
 - 1.5 Policy administration 13
 - 1.5.1 Organization administering the document 13
 - 1.5.2 Contact person 13
 - 1.5.3 Person determining CPS suitability for the policy 14
 - 1.5.4 CPS approval procedures 14
 - 1.6 Definitions and acronyms 14
- 2 Publication and repository responsibilities 21
 - 2.1 Repositories 21
 - 2.2 Publication of certification information 21
 - 2.3 Time or frequency of publication 22
 - 2.4 Access controls on repositories 22
- 3 Identification and authentication 23
 - 3.1 Naming 23
 - 3.1.1 Types of names 23
 - 3.1.2 Need for names to be meaningful 23
 - 3.1.3 Anonymity or pseudonymity of subscribers 23
 - 3.1.4 Rules for interpreting various name forms 23
 - 3.1.5 Uniqueness of names 23
 - 3.1.6 Recognition, authentication, and role of trademarks 23
 - 3.2 Initial identity validation 23
 - 3.2.1 Method to prove possession of private key 23
 - 3.2.2 Authentication of organization identity 24

- 3.2.3 Authentication of individual identity24
- 3.2.4 Non-verified subscriber information24
- 3.2.5 Validation of authority25
- 3.2.6 Criteria for interoperation25
- 3.3 Identification and authentication for re-key requests.....25
 - 3.3.1 Identification and authentication for routine re-key.....25
 - 3.3.2 Identification and authentication for re-key after revocation26
- 3.4 Identification and authentication for revocation request.....26
- 4 Certificate life-cycle operational requirements28
 - 4.1 Certificate application28
 - 4.1.1 Who can submit a certificate application.....28
 - 4.1.2 Enrollment process and responsibilities28
 - 4.2 Certificate application processing29
 - 4.2.1 Performing identification and authentication functions29
 - 4.2.2 Approval or rejection of certificate applications29
 - 4.2.3 Time to process certificate applications29
 - 4.3 Certificate Issuance.....29
 - 4.3.1 CA actions during certificate issuance29
 - 4.3.2 Notification to subscriber by the CA of issuance of certificate30
 - 4.4 Certificate acceptance.....30
 - 4.4.1 Conduct constituting certificate acceptance.....30
 - 4.4.2 Publication of the certificate by the CA30
 - 4.4.3 Notification of certificate issuance by the CA to other entities30
 - 4.5 Key pair and certificate usage31
 - 4.5.1 Subscriber private key and certificate usage.....31
 - 4.5.2 Relying party public key and certificate usage31
 - 4.6 Certificate renewal31
 - 4.6.1 Circumstance for certificate renewal.....31
 - 4.6.2 Who may request renewal32
 - 4.6.3 Processing certificate renewal requests.....32
 - 4.6.4 Notification of new certificate issuance to subscriber32
 - 4.6.5 Conduct constituting acceptance of a renewal certificate.....32
 - 4.6.6 Publication of the renewal certificate by the CA32
 - 4.6.7 Notification of certificate issuance by the CA to other entities32
 - 4.7 Certificate re-key32
 - 4.7.1 Circumstance for certificate re-key32

4.7.2	Who may request certification of a new public key.....	33
4.7.3	Processing certificate re-keying requests	33
4.7.4	Notification of new certificate issuance to subscriber	33
4.7.5	Conduct constituting acceptance of a re-keyed certificate	33
4.7.6	Publication of the re-keyed certificate by the CA.....	33
4.7.7	Notification of certificate issuance by the CA to other entities	33
4.8	Certificate modification	33
4.8.1	Circumstance for certificate modification	33
4.8.2	Who may request certificate modification	34
4.8.3	Processing certificate modification requests	34
4.8.4	Notification of new certificate issuance to subscriber	34
4.8.5	Conduct constituting acceptance of modified certificate.....	34
4.8.6	Publication of the modified certificate by the CA	34
4.8.7	Notification of certificate issuance by the CA to other entities	34
4.9	Certificate revocation and suspension.....	34
4.9.1	Circumstances for revocation	34
4.9.2	Who can request revocation	35
4.9.3	Procedure for revocation request.....	35
4.9.4	Revocation request grace period	38
4.9.5	Time within which CA must process the revocation request	38
4.9.6	Revocation checking requirement for relying parties.....	38
4.9.7	CRL issuance frequency.....	38
4.9.8	Maximum latency for CRLs.....	38
4.9.9	On-line revocation/status checking availability.....	38
4.9.10	On-line revocation checking requirements.....	38
4.9.11	Other forms of revocation advertisements available	38
4.9.12	Special requirements re key compromise	39
4.9.13	Circumstances for suspension.....	39
4.9.14	Who can request suspension.....	39
4.9.15	Procedure for suspension request	39
4.9.16	Limits on suspension period	39
4.10	Certificate status services	39
4.10.1	Operational characteristics	39
4.10.2	Service availability	39
4.10.3	Optional features	39
4.11	End of subscription.....	40

4.12	Key escrow and recovery	40
4.12.1	Key escrow and recovery policy and practices	40
4.12.2	Session key encapsulation and recovery policy and practices	40
5	Facility, management, and operational controls.....	41
5.1	Physical controls	41
5.1.1	Site location and construction	41
5.1.2	Physical access	41
5.1.3	Power and air conditioning	41
5.1.4	Water exposures	41
5.1.5	Fire prevention and protection	42
5.1.6	Media storage.....	42
5.1.7	Waste disposal	42
5.1.8	Off-site backup	42
5.2	Procedural controls	42
5.2.1	Trusted roles	42
5.2.2	Number of persons required per task.....	42
5.2.3	Identification and authentication for each role.....	43
5.2.4	Roles requiring separation of duties.....	43
5.3	Personnel controls	43
5.3.1	Qualification, experience, and clearance requirements.....	43
5.3.2	Background check procedures	43
5.3.3	Training requirements.....	44
5.3.4	Retraining frequency and requirements	44
5.3.5	Job rotation frequency and sequence	44
5.3.6	Sanctions for unauthorized actions.....	44
5.3.7	Independent contractor requirements	44
5.3.8	Documentation supplied to personnel.....	44
5.4	Audit logging procedures.....	44
5.4.1	Types of events recorded	44
5.4.2	Frequency of processing log.....	45
5.4.3	Retention period for audit log.....	45
5.4.4	Protection of audit log.....	45
5.4.5	Audit log backup procedures	45
5.4.6	Audit collection system (internal vs. external)	45
5.4.7	Notification to event-causing subject.....	45
5.4.8	Vulnerability assessments	46

5.5	Records archival	46
5.5.1	Types of records archived	46
5.5.2	Retention period for archive.....	46
5.5.3	Protection of archive.....	46
5.5.4	Archive backup procedures	46
5.5.5	Requirements for time-stamping of records	46
5.5.6	Archive collection system (internal or external).....	47
5.5.7	Procedures to obtain and verify archive information	47
5.6	Key changeover	47
5.7	Compromise and disaster recovery	47
5.7.1	Incident and compromise handling procedures.....	47
5.7.2	Computing resources, software, and/or data are corrupted	47
5.7.3	Entity private key compromise procedures	47
5.7.4	Business continuity capabilities after a disaster	48
5.8	CA or RA termination	48
6	Technical security controls	49
6.1	Key pair generation and installation.....	49
6.1.1	Key pair generation	49
6.1.2	Private key delivery to subscriber	49
6.1.3	Public key delivery to certificate issuer	49
6.1.4	CA public key delivery to relying parties	49
6.1.5	Key sizes.....	50
6.1.6	Public key parameters generation and quality checking.....	50
6.1.7	Key usage purposes (as per X.509 v3 key usage extension).....	50
6.2	Private key protection and cryptographic module engineering controls	50
6.2.1	Cryptographic module standards and controls.....	50
6.2.2	Private key (n out of m) multi-person control.....	50
6.2.3	Private key escrow	50
6.2.4	Private key backup	50
6.2.5	Private key archival	51
6.2.6	Private key transfer into or from a cryptographic module	51
6.2.7	Private key storage on cryptographic module	51
6.2.8	Method of activating private key	51
6.2.9	Method of deactivating private key	51
6.2.10	Method of destroying private key	52
6.2.11	Cryptographic module rating.....	52

- 6.3 Other aspects of key pair management.....52
 - 6.3.1 Public key archival.....52
 - 6.3.2 Certificate operational periods and key pair usage periods.....52
- 6.4 Activation data.....52
 - 6.4.1 Activation data generation and installation.....52
 - 6.4.2 Activation data protection52
 - 6.4.3 Other aspects of activation data52
- 6.5 Computer security controls.....53
 - 6.5.1 Specific computer security technical requirements53
 - 6.5.2 Computer security rating.....53
- 6.6 Life cycle technical controls.....55
 - 6.6.1 System development controls.....55
 - 6.6.2 Security management controls55
 - 6.6.3 Life cycle security controls.....55
- 6.7 Network security controls55
- 6.8 Time-stamping55
- 7 Certificate Profile, CRL Profile and OCSP Profile56
 - 7.1 Certificate profile56
 - 7.1.1 Version number(s).....57
 - 7.1.2 Certificate extensions58
 - 7.1.3 Algorithm object identifiers.....60
 - 7.1.4 Name forms.....61
 - 7.1.5 Name constraints.....61
 - 7.1.6 Certificate policy object identifier61
 - 7.1.7 Usage of Policy Constraints extension.....61
 - 7.1.8 Policy qualifier syntax and semantics61
 - 7.1.9 Processing semantics for the critical certificate policies extension.....61
 - 7.2 CRL profile61
 - 7.2.1 Version number(s).....62
 - 7.2.2 CRL and CRL entry extensions62
 - 7.3 OCSP profile62
 - 7.3.1 Version number(s).....62
 - 7.3.2 OCSP extensions62
- 8 Conformity assessments and other assessments.....63
 - 8.1 Frequency or circumstances of assessment.....63
 - 8.2 Identity/qualifications of assessor.....63

- 8.3 Assessor's relationship to assessed entity 63
- 8.4 Topics covered by assessment 63
- 8.5 Actions taken as a result of deficiency 63
- 8.6 Communication of results 64
- 9 Other Business and Legal Matters 65
 - 9.1 Fees 65
 - 9.1.1 Certificate issuance or renewal fees 65
 - 9.1.2 Certificate access fees 65
 - 9.1.3 Revocation or status information access fees 65
 - 9.1.4 Fees for other services 65
 - 9.1.5 Refund policy 65
 - 9.2 Financial responsibility 65
 - 9.2.1 Insurance coverage 65
 - 9.2.2 Other assets 65
 - 9.2.3 Insurance or warranty coverage for end-entities 66
 - 9.3 Confidentiality of business information 66
 - 9.3.1 Scope of confidential information 66
 - 9.3.2 Information not within the scope of confidential information 66
 - 9.3.3 Responsibility to protect confidential information 66
 - 9.4 Privacy of personal information 66
 - 9.4.1 Privacy plan 66
 - 9.4.2 Information treated as private 66
 - 9.4.3 Information not deemed private 66
 - 9.4.4 Responsibility to protect private information 67
 - 9.4.5 Notice and consent to use private information 67
 - 9.4.6 Disclosure pursuant to judicial or administrative process 67
 - 9.4.7 Other Information disclosure circumstances 67
 - 9.5 Intellectual property rights 67
 - 9.6 Representations and warranties 67
 - 9.6.1 CA Representations and warranties 67
 - 9.6.2 RA representations and warranties 68
 - 9.6.3 Subscriber representations and warranties 68
 - 9.6.4 Relying parties representations and warranties 68
 - 9.6.5 Representations and warranties of other participants 68
 - 9.7 Disclaimers of warranties 68
 - 9.8 Limitations of liability 69

9.9	Indemnities.....	69
9.10	Term and termination	70
9.10.1	Term.....	70
9.10.2	Termination	70
9.10.3	Effect of termination and survival.....	70
9.11	Individual notices and communications with participants.....	70
9.12	Amendments.....	70
9.12.1	Amending procedure	70
9.12.2	Notification mechanism and period.....	71
9.12.3	Circumstances under which OID must be changed	71
9.13	Disputes resolution provisions.....	71
9.14	Governing law	71
9.15	Compliance with applicable law.....	71
9.16	Miscellaneous provisions	71
9.16.1	Entire agreement.....	71
9.16.2	Assignment.....	71
9.16.3	Severability.....	71
9.16.4	Enforcement (attorneys' fees and waiver of rights)	72
9.16.5	Force Majeure	72
9.17	Other provisions.....	72
10	Final Provisions.....	73

Table 1 – Document history

Version	Date of Release	Approved by	Comments
1.00	16 November 2017	CEO of První certifikační autorita, a.s.	First release.
1.01	3 May 2018	CEO of První certifikační autorita, a.s.	More detailed description of filling up subject field attribute. More detailed text in chapter 8.4.
2.00	13 September 2018	CEO of První certifikační autorita, a.s.	Requirements of ETSI TS 119 495 included.
2.10	25 March 2019	CEO of První certifikační autorita, a.s.	Requirements of ETSI TS 119 495, version 1.2.1 (2018-11) included.
2.11	13 July 2019	CEO of První certifikační autorita, a.s.	More specific text complying with ETSI TS 119 495 standard version 1.3.1 (2019-03).
2.12	22 October 2019	CEO of První certifikační autorita, a.s.	More specific description of organizationIdentifier attribute.

2.13	13 November 2019	CEO of První certifikační autorita, a.s.	More specific text complying with ETSI TS 119 495 standard version 1.4.1 (2019-11), sending information to NCA e-mail address added.
2.14	28 November 2020	CEO of První certifikační autorita, a.s.	Classification of document marked, change of CA actions during subsequent certificate issuance, revision, more accurate text.

1 INTRODUCTION

This document determines the principles applied by První certifikační autorita, a.s. (also as the I.CA), a qualified provider of trust services, in providing qualified trust service of issuing qualified certificates for electronic seals with specific PSD2 attributes (also as the Service or the Certificate) to legal persons or government authorities (also as Organization). The RSA algorithm is used for the Service provided under this certification policy (also as the CP).

The statutory requirements in respect of the Service are defined in:

- Regulation (EU) no 910/2014 of the European Parliament and of the Council on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC;
- Act of the Czech Republic No. 297/2016 Coll., on trust services for electronic transactions;
- Legislation concerning personal data protection in compliance with Regulation (EU) no 2016/679 of the European Parliament and of the Council on the protection of natural persons with regard to the processing of personal data and on the free movement of such data, and repealing Directive 95/46/EC (General Data Protection Regulation).

Note: Any reference to technical standard, norm or legislation is always a reference to that technical standard, norm or legislation or to replacing technical standard, norm or legislation. If this document is in conflict with any technical standard, norm or legislation that replaces the current technical standard, norm or legislation, a new version will be released.

The Service is provided to all end users on the basis of the contract. I.CA imposes no restrictions on potential end users, and the provision of the Service is non-discriminatory and the Service is also available to the disabled.

1.1 Overview

The document **Certification Policy for Issuing Qualified Certificates for Electronic Seals PSD2 (RSA Algorithm)** is prepared by První certifikační autorita, a.s., deals with the issues related to life cycle processes of Certificates and follows a structure matching the scheme of valid RFC 3647 standard while taking account of valid technical and other standards and norms of the European Union and the laws of the Czech Republic pertinent to this sphere (therefore, each chapter is preserved in his document even if it is irrelevant to this sphere). The document is divided into nine basic chapters and these are briefly introduced in the following list:

- Chapter 1 identifies this document with the allocated unique identifier, generally describes the entities and individuals taking part in the provision of this Service, and defines the acceptable use of the Certificates available to be issued;
- Chapter 2 deals with the responsibility for the publication and information or documents;
- Chapter 3 describes the processes of identification and authentication of an applicant for the issuance or revocation of a Certificate, and defines the types and contents of the names used in Certificates;
- Chapter 4 defines life cycle processes of Certificates, i.e. Certificate issuance application, the issuance of the Certificate, Certificate revocation request, the

revocation of the Certificate, the services related to the verification of Certification status, termination of the provision of the Service, etc.;

- Chapter 5 covers physical, procedural and personal security, including the definition of the set of events subject to logging, the keeping of these records and responses to emergency and compromising situations;
- Chapter 6 focuses on the technical security of the type of generating public and private keys, protection of private keys, including the computer and network protection;
- Chapter 7 defines the profile of issued Certificates and CRL;
- Chapter 8 focuses on assessing the Service delivered;
- Chapter 9 deals with commercial and legal aspects.

More detail on the fulfillment of fields and extensions of Certificates issued under this CP and on Certificate administration may be included in the relevant certification practice statement (also as the CPS).

Note: This is English translation of CP; Czech version always takes precedence.

1.2 Document name and identification

Document's title: Certification Policy for Issuing Qualified Certificates for Electronic Seals PSD2 (RSA Algorithm), version 2.14

Policy OID: 1.3.6.1.4.1.23624.10.1.34.2.1

1.3 PKI Participants

1.3.1 Certification authorities

The root certification authority of První certifikační autorita, a.s., issued a certificate to a subordinate certification authority (also as the Authority) operated by I.CA, in a two-tier certification authority structure, in accordance with current legislation and technical and other standards. This Authority issues Certificates under this CP and certificates for its own OCSP responder.

1.3.2 Registration authorities

The services of První certifikační autorita, a.s., are provided through registration authorities (stationary or mobile), which are either public (providing services for the general public) or client (providing services for their customers). These registration authorities:

- Accept applications for the services listed in this CP (Certificate issuance applications, in particular), arrange the handover of Certificates and certificate revocation lists, provide required information, handle complaints, etc.;
- Are authorized, for urgent operational or technical reasons, to suspend, in whole or in part, the performance of their activities;
- Are authorized to conclude Service contracts on behalf of I.CA;

- Are authorized to charge for the I.CA services provided through RA unless otherwise agreed in the contract;
- If contracted RA, exercise similar duties and responsibilities on behalf of I.CA as the RA proper, under a written contract concluded between I.CA and the operator of the contracted RA.

1.3.3 Subscribers

Subscriber of a Certificate is an Organization which applied for Certificate for itself and which is identified in the Certificate as the owner of the private key connected with the public key specified in the Certificate.

1.3.4 Relying parties

Any entity relying in their operations on the Certificates issued under this CP is a relying party.

1.3.5 Other participants

Other participating parties are on the one hand investigative, prosecuting and adjudicating bodies, supervisory bodies and other bodies recognized as such by current trust services legislation. On the other hand, it is the registrar of payment services providers (also as NCA), e.g. Czech National Bank.

1.4 Certificate usage

1.4.1 Appropriate certificate uses

Certificates issued under this CP may only be used in electronic seal verification processes in accordance with trust services legislation.

1.4.2 Prohibited certificate uses

Certificates issued under this CP may not be used contrary to the acceptable use described in 1.4.1 or contrary to law.

1.5 Policy administration

1.5.1 Organization administering the document

This CP and its CPS are administered by První certifikační autorita, a.s.

1.5.2 Contact person

The contact person of První certifikační autorita, a.s., in respect of this CP and its CPS is specified on a web page – see 2.2.

1.5.3 Person determining CPS suitability for the policy

CEO of První certifikační autorita, a.s., is the sole person responsible for making decisions about compliance of the procedures of První certifikační autorita, a.s., as set out in CPS with this CP.

1.5.4 CPS approval procedures

If it is necessary to make changes to a CPS to create a new version thereof, the CEO of První certifikační autorita, a.s., appoints a person authorized to perform such changes. No new CPS version may take force unless it has been approved by CEO of První certifikační autorita, a.s.

1.6 Definitions and acronyms

Table 2 – Definitions

Term	Explanation
CA/Browser Forum	organization, consensual association of certification authorities
Classified Information Protection Act	the Czech Republic's Act No. 412/2005 Coll., regulating classified information protection and security competence, as amended
contracting partner	provider of services contracted by I.CA for certification services or parts thereof – usually, it is a contracted RA
domain name	node name in domain name system
domain name registrant/registrant	sometimes referred to as a domain name owner, but more accurately a person or entity registered by a domain registrar as having the right to oversee the use of a domain name, a natural or legal person listed as a "Registrant" by WHOIS or a domain registrar
domain name registrar/registrar	person or entity that registers domain names by mandate or with consent: <ul style="list-style-type: none"> ▪ Internet Corporation for Assigning Names and Numbers (ICANN) - Administrator of DNS Root Space; ▪ TLD administrator (e.g. .com) or ccTLD (e.g. .CZ, national administrator)
domain name space	a set of all possible domain names that are subordinate to one node in the domain name system
electronic seal	advanced electronic seal or recognized electronic seal or qualified electronic seal under trust services legislation
electronic sign	electronic sign under trust services legislation
electronic signature	advanced electronic signature or recognized electronic signature or qualified electronic signature under trust services legislation
GET method	standard preferred method for sending http requests to OCSP responder via http, the method allows caching (the second method is POST)

hash function	transformation which receives, as an input, a string of characters of arbitrary length, and the result is a string of characters of fixed length (hash)
key pair	private key and corresponding public key
Labour Code	the Czech Republic's Act No. 262/2006 Coll., Labour Code, as amended
OCSP responder	server using the OCSP protocol to provide data on public key certificate status
OCSP stapling	way of minimizing queries for OCSP Responder, RFC 4366 - TLS Extensions; allows the TLS server to return the once-received answer to the question about certificate status from the OCSP (during its validity) to all end users accessing the TLS server
phishing	in an electronic communication attempt to obtain sensitive information (usernames, passwords, and credit card details) for malicious reasons
private key	unique data to create electronic signature / seal
public key	unique data to verify electronic signature / seal
PSP registrar	authority responsible for approving or rejecting authorization of payment services providers in their state, usually National Bank, in ETSI TS 119 495 called NCA (National Competent Authority)
qualified certificate for electronic signature or for electronic seal or for website authentication	certificate defined by trust services legislation
qualified signature / seal creation device	device meeting the requirements of eIDAS, annex II, intended for electronic signature / seal creation
relying party	party relying on a certificate in its operations
root CA	certification authority which issues certificates to subordinate certification authorities
secure cryptographic device	device on which the private key is stored
SSL certificate	certificate for identification and encryption within SSL/TLS protocol communication
subordinate CA	CA issuing certificates to end users
supervisory body	the body supervising qualified trust services providers
trust service / qualified trust service	trust service / qualified trust service defined by eIDAS
trust services legislation	current legislation on trust services
TWINS	commercial product of I.CA consisting of: <ul style="list-style-type: none"> ▪ qualified certificate for electronic signature; ▪ non-qualified certificate which issuance is based only on

	contractual relationship between I.CA and end-user
two-factor authentication	authentication employing two of three factors – I know something (the password), I have something (a smart card or a hardware token) or I am something (fingerprint, retina or iris reading)
written contract	text of the contract in electronic or paper form

Table 3 – Acronyms

Acronym	Explanation
ARC	Alarm Receiving Centre
ASCII	American Standard Code for Information Interchange, table containing binary codes of English alphabets, numbers and other common symbols
BIH	Bureau International de l'Heure – The International Time Bureau
bit	from English <i>binary digit</i> – a binary system digit – the fundamental and the smallest unit of information in digital technologies
BRG	document "Baseline Requirements for the Issuance and Management of Publicly-Trusted Certificates" published by CA/Browser Forum
CA	certification authority
CAA	DNS Resource Record - see RFC 6844
ccTLD	country code TLD, national top-level domain, usually user for countries, sovereign states or dependent territories, ASCII ccTLD identifiers are two letters long
CEN	European Committee for Standardization, an association of national standardization bodies
CEO	Chief Executive Officer
COO	Chief Operating Officer
CP	certification policy
CPS	certification practice statement
CR	Czech Republic
CRL	Certificate Revocation List – the list of revoked certificates, which are not held as valid any longer
CT	Certificate Transparency, the system to mitigate misissuance of certificate based on adding new certificate (or rather precertificate) to public logs making possible to detect the misissuance (especially fraudulent getting the certificate by other than authorized applicant)
ČSN	Czech Technical Norm
DER, PEM	methods of certificate encoding (certificate formats)
DV	Domain Validation, SSL certificate type
DNS	Domain Name System, a hierarchical decentralized naming system

	implemented by DNS servers which are exchanging information via DNS protocol to translate domain names to the numerical IP addresses
EBA	European Banking Association
EC	Elliptic Curve
ECC	Elliptic Curve Cryptography
eIDAS	REGULATION (EU) no 910/2014 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 23 July 2014 on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC
EN	European Standard, a type of ETSI standard
ESI	Electronic Signatures and Infrastructures
ETSI	European Telecommunications Standards Institute, a European standardization institute for information and communication technologies
EU	European Union
EV	Extended Validation, type of SSL certificate or certificate intended for websites authentication
EVCG	document "Guidelines For The Issuance And Management Of Extended Validation Certificates" published by CA/Browser Forum
EVCP	Extended Validation Certificate Policy, type of certification policy
FAS	Fire Alarm System
FIPS	Federal Information Processing Standard, standards for information technologies for U.S. non-military state organizations
FQDN	Fully Qualified Domain Name, domain name that specifies all domain levels in Internet domain name system
GDPR	General Data Protection Regulation, REGULATION (EU) 2016/679 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on the protection of natural persons with regard to the processing of personal data and on the free movement of such data, and repealing Directive 95/46/EC (General Data Protection Regulation)
gTLD	generic TLD, top level domain (e.g. .org for non-profit organizations)
html	Hypertext Markup Language, markup language for creating hypertext documents
http	Hypertext Transfer Protocol, protocol for exchanging html documents
https	Hypertext Transfer Protocol, protocol for secure exchanging of html documents
I.CA	První certifikační autorita, a.s.
IAS	Intrusion Alarm System
ICA_OID	OID belonging to OID space allocated to I.CA
ICANN	Internet Corporation for Assigned Names and Numbers, organization which among others assigns and administrates domain names and IP

	addresses
IEC	International Electrotechnical Commission, the global organization publishing standards for electrical and electronic engineering, communication technologies and related industries
IP	Internet Protocol, principal communications protocol in the Internet protocol suite for relaying packets across network and routing used in the Internet
IPS	Intrusion Prevention System
ISMS	Information Security Management System
ISO	International Organization for Standardization, an international organization of national standardization organizations; designation of standards
IT	Information Technology
ITU	International Telecommunication Union
ITU-T	Telecommunication Standardization Sector of ITU
MPSV	Ministry of Labor and Social Affairs
NCA	National Competent Authority - authority responsible for approving or rejecting authorization of payment services providers and assigning PSP numbers to them in particular state; see also PSP registrar above
NCP	Normalized Certificate Policy, non-qualified certificates certification policy, qualitatively the same as certification policy for issuing qualified certificates
NCP+	Extended Normalized Certificate Policy, NCP certification policy requiring a secure cryptographic device
OCSP	Online Certificate Status Protocol, the protocol to identify public key certificate status
OID	Object Identifier
OSVČ	self-employed person
OV	Organization Validation, SSL certificate type
PDCA	Plan-Do-Check-Act, Deming cycle, management method for control and continuous improvement
PDS	PKI Disclosure Statement
PKCS	Public Key Cryptography Standards, designation for a group of standards for public key cryptography
PKI	Public Key Infrastructure
PSD	Payment Services Directive, DIRECTIVE 2007/64/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on payment services in the internal market
PSD2	DIRECTIVE (EU) 2015/2366 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL, superseding PSD and coming into effect January 13th 2018

PSP	Payment Service Provider
PSS	Probabilistic Signature Scheme, electronic signature schema developed by M. Bellare and P. Rogaway and standardized as part of PKCS#1 v2.1
PTC	Publicly-Trusted Certificate
PUB	Publication, FIPS standard designation
QSCD	Qualified Electronic Signature/Seal Creation Device (defined by eIDAS)
QWAC	Qualified Website Authentication Certificate
RA	registration authority
RFC	Request for Comments, designation for a range of standards and other documents describing web protocols, systems, etc.
RSA	signing and encrypting public key cipher (acronym from the names of the original authors - Rivest, Shamir and Adleman)
RTS	COMMISSION DELEGATED REGULATION (EU) 2018/389 of 27 November 2017 supplementing Directive (EU) 2015/2366 of the European Parliament and of the Council with regard to regulatory technical standards for strong customer authentication and common and secure open standards of communication
SCT	Signed Certificate Timestamp, signed timestamp from relevant CT log which confirms adding the precertificate
sha, SHA	type of hash function
SSCD	Secure Signature Creation Device (defined by directive 1999/93/ES)
SSL	Secure Sockets Layer, communication protocol, layer inserted between transport layer and application layer, providing securing of communication via encryption and authentication of communicating parties
TLD	Top Level Domain, top level Internet domain, in domain name the top-level domain is placed at the end
TLS	Transport Layer Security, communication protocol superseding SSL
TS	Technical Specification, type of ETSI standard
TSA	Time-Stamping Authority
TSS	Time-Stamp Server
TSU	Time-Stamp Unit
UPN	User Principal Name, user name based on RFC 822
UPS	Uninterruptible Power Supply/Source
URI	Uniform Resource Identifier, defined-structure text string for accurate specification of a source of information
UTC	Coordinated Universal Time, the standard adopted on 1 January 1972 for the global coordinated time – Bureau International de l'Heure (BIH) plays the role of the 'official keeper' of the atomic time for the whole world

WHOIS	database including domain name registrant technical, billing and administrative contact information
ZOOÚ	current personal data protection legislation

2 PUBLICATION AND REPOSITORY RESPONSIBILITIES

2.1 Repositories

První certifikační autorita, a.s., sets up and operates repositories of both public and non-public information.

2.2 Publication of certification information

The basic addresses (also as the Information Addresses) for obtaining information about První certifikační autorita, a.s., are as follows:

- Registered office:
První certifikační autorita, a.s.
Podvinný mlýn 2178/6
190 00 Praha 9
The Czech Republic
- Website: <http://www.ica.cz>;
- Registered offices of the registration authorities.

Electronic address for contact between general public and I.CA is info@ica.cz, databox if I.CA ID is a69fvfb.

The aforesaid website provides information about:

- Public certificates – the following information is published (and more information can be obtained from the certificate):
 - Certificate number;
 - Content of commonName;
 - Valid from date (specifying the hour, minute and second);
 - Link to where the certificate can be obtained in the specified format (DER, PEM, TXT);
- Certificate revocation list (CRL) – the following information is published (and more information can be obtained from the CRL):
 - Date of CRL release;
 - CRL number;
 - Link to where the CRL can be obtained in the specified format (DER, PEM, TXT);
- Certification and other policies and practice statements, certificates issued or revoked and other public information.

Http and https are the permitted protocols for access to public information. I.CA may terminate or suspend access to some information without cause.

If NCA e-mail address is made public in EBA list of e-mail addresses designated for communication concerning Certificates or NCA informs I.CA of e-mail address where it can be contacted in connection with Certificates then I.CA will be sending to this address issued

Certificates containing identifier of this NCA together with a text listing of Certificates. NCA informs I.CA of this e-mail address via sending e-mail to info@ica.cz, e-mail must be electronically signed or sealed based on a qualified certificate (for NCA electronic seal or for electronic signature of natural person connected with NCA).

Any revocation of a certificate employed in issuing certificates to end users, a release of certificate revocation list, and the provision of certificate status information (also as Infrastructure Certificates) because of suspected or actual compromise of a given private key will be announced by I.CA on its web Information Address and in Hospodářské noviny or Mladá fronta Dnes, daily newspapers with national distribution.

2.3 Time or frequency of publication

I.CA publishes information as follows:

- Certification policy – after a new version is approved and issued;
- Certification practice statement – immediately;
- List of the Certificates issued – updated every time a new Certificate is issued;
- Certificate revocation list (CRL) – see 4.9.7;
- Information about infrastructure certificate revocation with the date of revocation – immediately;
- Other public information – no specific time limit, the general rule is that this information must correspond to the current state of the services provided.

2.4 Access controls on repositories

All public information is made available by I.CA free of charge without any restrictions.

Non-public information is available only to authorized employees of I.CA or the parties specified by the relevant legislation. Access to such information is governed by the rules defined in internal documentation.

3 IDENTIFICATION AND AUTHENTICATION

3.1 Naming

3.1.1 Types of names

All names are construed in accordance with valid technical and other standards.

3.1.2 Need for names to be meaningful

For a Certificate to be issued, all verifiable names given in the subject field and subjectAlternativeName extension must carry a meaning. See chapter 7 for the attributes supported for this field and the extension.

3.1.3 Anonymity or pseudonymity of subscribers

The Certificates issued under this CP do not support both anonymity and pseudonymity.

3.1.4 Rules for interpreting various name forms

The data specified in a Certificate application (format PKCS#10) are carried over in subject field or subjectAlternativeName extension of the Certificate in the form they are specified in the application.

3.1.5 Uniqueness of names

The Authority guarantees that the subject field in a Certificate of specific subscriber is unique.

3.1.6 Recognition, authentication, and role of trademarks

Any Certificate issued under this CP may only contain a trademark with evidenced ownership or license. The Certificate's subscriber bears any consequence resulting from unauthorized use of a trademark.

3.2 Initial identity validation

The entities authorized to apply for a Certificate are listed in 4.1.1. The following chapters specify the rules for the initial validation of the identity of these entities.

3.2.1 Method to prove possession of private key

The ownership of the private key matching the public key in the Certificate application must be proved by submitting the application in the PKCS#10 format. The application is electronically sealed with this private key whereby the subscriber provides evidence that he is the owner of the private key when the electronic seal is created.

3.2.2 Authentication of organization identity

The following must be submitted to verify the identity of an Organization:

- Original or certified copy of the entry in the Commercial Register or in another register specified by law, of a trade license, of a deed of incorporation, or of another document of the same legal force; or
- Printed extract from public registers to be submitted by the applicant or prepared by the RA operator.

This document must contain full business name, identification number (if any), registered office, the name(s) of the person(s) authorized to act on behalf of the legal entity (authorized representatives).

3.2.3 Authentication of individual identity

This chapter describes the methods of verifying the identity of natural person, i.e. the person representing Organization applying for the Certificate.

The person representing Organization identity authentication procedure requires two documents, a primary and a secondary one, that show the data specified further in this chapter.

Valid personal identity card or passport must be used as the primary personal document for the citizens of the Czech Republic. Valid passport is the primary personal document for foreigners; citizens of EU member countries may use their valid personal identity card they use in their country as the proof of their identity.

The following data are verified in this document:

- Full civil name;
- Date and place of birth or the birth identification number if shown in the primary document;
- Number of the primary personal document;
- Permanent address (if shown in the primary document).

The secondary document must contain a unique identification, such as birth identification number or personal identity card number, matching it to the primary document and must show at least one of these items:

- Date of birth (or birth identification number if specified);
- Permanent address;
- Photograph of the face.

The secondary personal document data uniquely identifying the person representing the Organization must be identical to those in the primary personal document.

If the person representing Organization is not an authorized representative of the Organization then his officially certified power of attorney signed by authorized representative of the Organization is required.

3.2.4 Non-verified subscriber information

Not applicable to this document - all information must be duly verified.

3.2.5 Validation of authority

Issued Certificate contains these PSD2 attributes to be validated:

- **subject.organizationIdentifier:**
 - PSP identifier in format according to ETSI TS 119 495:
 - If NCA states in PSP register the PSP identifier then it will be included in the format ***PSDcc-registrarID-PSP_identifier***; or
 - If NCA does not stated PSP identifier in PSP register then the unique PSP identifier from any other respected register will be included in compliance with EN 319 412-1 or TS 119412-1 (prefixes NTR, VAT and the like);
- **QCStatements.id-etsi-psd2-qcStatement:**
 - **.rolesOfPSP** - list of authorized PSP roles (for every authorized role the two of OID and abbreviated name of the role specified in ETSI TS 119 495);
 - **.nCAName** - full NCA Name in English; for the Czech Republic must contain the text *Czech National Bank*;
 - **.nCAId** - NCA identifier in format *cc-IDregistrar*; for the Czech Republic must contain the text *CZ-CNB*.

I.CA validates PSD2 attributes applied by subject using authentic information given by NCA - e.g. national public register (NCA), EBA PSD2 register etc.; more detailed description of attributes validation procedures is contained in internal documentation.

If NCA specifies rules for PSD2 attributes validation I.CA will follow them.

Electronic mail address may be placed in the Certificate extension, that is, in the `rfc822Name` attribute of the `subjectAlternativeName` extension, if this has been verified for the given application during the Certificate issuance procedure.

The attribute that the key pair was generated and stored on QSCD device may only be inserted in the Certificate if this has been verified for the given application during the Certificate issuance procedure.

3.2.6 Criteria for interoperation

Any collaboration between První certifikační autorita, a.s., and other trust service providers is always based on a contract in writing.

3.3 Identification and authentication for re-key requests

3.3.1 Identification and authentication for routine re-key

The identification and authentication in routine re-key request are as follows:

- The application for the issuance of subsequent Certificate in the PKCS#10 structure must also be electronically sealed with the use of a private key matching the public key contained in the valid Certificate which is to be re-keyed, or
- Must be contained in e-mail signed by private key matching the public key in signing certificate (certificate issued optionally to subscriber of Certificate which is clearly tied with Certificate).

3.3.2 Identification and authentication for re-key after revocation

This is irrelevant to this document as the service of re-keying after Certificate revocation is not supported. A new Certificate with a new public key needs to be issued. The same requirements as those in the initial identity validation apply.

3.4 Identification and authentication for revocation request

The entities authorized to make a request for Certificate revocation are listed in 4.9.2.

If the Certificate revocation request is submitted **by Subscriber** of this Certificate, then:

- If the **Certificate revocation request is submitted to RA by hand**, the application must be in writing and signed by a person whose identity must be duly verified through the primary personal document (see 3.2.3);
- The following methods of identification and authentication are permitted for **Certificate revocation requests submitted electronically**:
 - Using the form on the company's website (and using the Certificate revocation password);
 - Using an unsigned electronic message containing the Certificate revocation password and sent to revoke@ica.cz;
 - Using an electronically signed or sealed electronic message sent to revoke@ica.cz where:
 - The electronic signature must be created with the private key belonging to the signing certificate;
 - The electronic seal must be created with the private key belonging to the Certificate to be revoked;
 - Using the data box of I.CA (and using the Certificate revocation password);
 - By a defined person assigned to represent the Organization in the contractual relationship with I.CA;
- If the **Certificate revocation request is sent as a letter** (using the Certificate revocation password), the letter must be sent by registered post to registered office of I.CA.

The data required for Certificate revocation request are listed in 4.9.3.

If the Certificate revocation request is submitted by **NCA** as PDF form (content and way of submitting - see 4.9.3) then the means how to authenticate the origin of request are these:

- Verification of NCA's advanced electronic signature or advanced electronic seal of NCA based on qualified certificate (for electronic seal of NCA or for electronic signature of a person connected with NCA);
- Inserting the password (shared secret) to decrypt and view the document that I.CA gave for this purpose to NCA.

It must be also verified that:

- Certificate which should be revoked contains NCA identifier;
- Certificate with serial number specified in revocation request was issued to PSP specified in the request.

Revocation can be done only after successful authentication and validation of legitimacy and correctness of the request sent by NCA (see above).

I.CA reserves the right to accept also other Certificate revocation identification and authentication procedures, which, however, must not be contrary to trust services legislation.

4 CERTIFICATE LIFE-CYCLE OPERATIONAL REQUIREMENTS

4.1 Certificate application

4.1.1 Who can submit a certificate application

For issuing the Certificate may apply Organizations via the person representing the Organization.

4.1.2 Enrollment process and responsibilities

Process performed only in case of issuance of the primary Certificate, the person representing the Organization initiates the registration procedure by appearing at an RA office and bringing all the required documents plus the Certificate application (if already existing); at the RA office, the data in the submitted documents are entered in the Authority's information system and the Certificate application is processed.

The Certificate's subscriber is required to do the following, among other things:

- Get acquainted with this CP and sign an agreement to observe it;
- Provide true and complete information for the issuance of the Certificate;
- Check whether the data specified in the Certificate application and the Certificate issued are correct and correspond to the required data;
- Choose a suitable Certificate revocation password (the minimum/maximum password length is 4/32 characters; permitted characters: 0..9, A..Z, a..z).

The Service provider is required to do the following, among other things:

- Inform the Certificate subscriber about the terms and conditions prior to concluding the Service contract;
- Conclude with the subscriber such a Service contract that meets the requirements imposed by trust services legislation;
- During the Certificate issuance process, check with RA all the verifiable data specified in the application against the documents submitted;
- Require a proof of QSCD private key generation if the private key is QSCD-generated;
- Issue a Certificate that contains materially correct data on the basis of the information available to the Service provider as at the issuance of the Certificate;
- Publish public information in accordance with 2.2;
- Publish the Authority's certificates and the root CA's certificates;
- Provide any Service-related activity in accordance with trust services legislation, this CP, the relevant CPS, the System Security Policy – Trustworthy Systems and the operating documentation.

4.2 Certificate application processing

4.2.1 Performing identification and authentication functions

The identification and authentication procedure for the **primary Certificate** follows the rules given in 3.2.3, or 3.2.2 where applicable, and the procedure for **subsequent Certificates** follows the rules given in 3.3.1.

4.2.2 Approval or rejection of certificate applications

RA employees (also as the Employees) do the following in the procedure leading to the decision accepting or dismissing the issuance of the **primary Certificate**:

- Make a visual check as to conformity of the data in the Certificate application (the PKCS#10 structure) with the data in the documents submitted;
- Make a visual check as to the formal correctness of data.

The private key ownership verification, competence check and formal data correctness check are also carried out using the RA system software.

If any of these checks gives a fail result, the Certificate issuance procedure is terminated; otherwise the procedure continues in accordance with 4.3.

See 4.3 for the procedure for the issuance of **subsequent Certificates**.

4.2.3 Time to process certificate applications

I.CA must issue the Certificate immediately after Certificate issuance is granted. The following list gives tentative times for issuing Certificates unless other agreement is stipulated in the contract:

- Primary Certificate – issued within 15 minutes (only on business days during business hours), or a longer time exceptionally;
- Subsequent Certificates – within units of minutes.

4.3 Certificate Issuance

4.3.1 CA actions during certificate issuance

CA operators (also as the Operators) carry out the following in the **primary Certificate** issuance procedure:

- Make a visual check as to conformity of the data in the Certificate application (the PKCS#10 structure) and the data entered by an RA employee;
- Make a visual check as to the formal correctness of data.

The verification of private key ownership, the supported hash function in the Certificate application (no weaker than sha-256), the competence check and the formal data correctness check are carried out by both the software on CA operators' work stations and that on the CA system core. If any of these checks gives a fail result, the Certificate issuance procedure is terminated.

Subsequent Certificate issuance procedure is automatic without Operators' intervention. The verification of private key ownership, the supported hash function in the Certificate application (no weaker than sha-256) and the competence check are carried out by software on the CA system core. If any of these checks gives a fail result, the Certificate issuance procedure is terminated.

4.3.2 Notification to subscriber by the CA of issuance of certificate

During the **primary Certificate** issuance process, the Certificate subscriber or the person representing the Organization applying for Certificate receives information from the RA employee and the Certificate is sent to the contact e-mail provided during registration as mandatory data.

Subsequent Certificates are sent to the contact e-mail provided during registration as mandatory data.

4.4 Certificate acceptance

4.4.1 Conduct constituting certificate acceptance

If the Certificate issuance requirements are met, the Certificate's subscriber must take the Certificate over. The only way to refuse taking over the Certificate is to request for Certificate's revocation in accordance with this CP.

I.CA may agree with the Organization a procedure different from this provision of CP. However, that must not be contrary to the relevant provisions of the trust services legislation.

4.4.2 Publication of the certificate by the CA

I.CA publishes every Certificate it issues, except any Certificate:

- Containing data, the publication of which could be contrary to relevant legislation, e.g. legislation concerning personal data protection;
- Required by the subscriber not to be published.

4.4.3 Notification of certificate issuance by the CA to other entities

Chapter 4.4.2 and the requirements set out in trust services legislation apply.

Notification about Certificate issuance can usually obtain only the subscriber of this Certificate.

If e-mail address is made public in EBA list of e-mail addresses designated for communication concerning Certificates or NCA informs I.CA of its e-mail address where it can be contacted in connection with Certificates then I.CA will be sending to this address issued Certificates containing identifier if this NCA together with a text listing of Certificates (see also chapter 2).

NCA informs I.CA of this e-mail address via sending e-mail to info@ica.cz, e-mail must be electronically signed or sealed based on a qualified certificate (for NCA electronic seal or for electronic signature of natural person connected with NCA).

NCA can ask information on Certificates containing PSP authorization number assigned by this NCA. Application in PDF format with advanced electronic seal or advanced electronic signature created using a qualified certificate (NCA electronic seal or electronic signature of natural person connected with NCA) must NCA send to the e-mail address info@ica.cz; application must contain information how the answer should be sent (in written, via mail etc.).

4.5 Key pair and certificate usage

4.5.1 Subscriber private key and certificate usage

Subscribers must, among other things:

- Observe all relevant provisions of the Service contract;
- Use the private key and corresponding Certificate solely for the purposes defined in this CP;
- Handle the private key corresponding to the public key contained in the Certificate issued under this CP in a manner as to prevent any unauthorized use;
- Inform immediately the Service provider of everything that leads to the Certificate's revocation, in particular of:
 - Suspected abuse of the private key; and
 - Invalid or inaccurate attributes of Certificate;

In this case request for the Certificate's revocation and stop using the pertinent private key.

4.5.2 Relying party public key and certificate usage

Relying parties must, among other things:

- Obtain from a secure source (www.ica.cz, supervisory body web pages, RA workplace, relevant trusted list) certification authority certificates linked with the Certificate issued under this CP, and verify those certificates' fingerprint values and validity;
- Carry out any operation necessary for them to verify that the Certificate is valid;
- Observe all and any provisions of this CP and trust services legislation which relate to the relying party's duties.

4.6 Certificate renewal

Certificate renewal under this CP means the issuance of a subsequent Certificate for a still valid Certificate without changing the public key, or the issuance of other information in the Certificate, or for a revoked Certificate, or for an expired Certificate.

Certificate renewal is not provided.

4.6.1 Circumstance for certificate renewal

See 4.6.

4.6.2 Who may request renewal

See 4.6.

4.6.3 Processing certificate renewal requests

See 4.6.

4.6.4 Notification of new certificate issuance to subscriber

See 4.6.

4.6.5 Conduct constituting acceptance of a renewal certificate

See 4.6.

4.6.6 Publication of the renewal certificate by the CA

See 4.6.

4.6.7 Notification of certificate issuance by the CA to other entities

See 4.6.

4.7 Certificate re-key

Certificate public key replacement under this CP means the issuance of a new Certificate with a different public key but identical content of the attributes under the subject field, the subjectAlternativeName extension or PSD2 relevant attributes of the Certificate the public key of which is requested to be replaced. These attributes must be verified again.

If the whole new Certificate issuance procedure is handled solely electronically without requiring any natural person to be present at an RA office, it is the issuance of a subsequent Certificate. See 4.7.1 for the requirements in respect of verifying electronic applications for subsequent Certificates. If these requirements are not met or repeated validation of PSD2 attributes is not successful it is the primary Certificate issuance procedure, which starts with the registration procedure.

4.7.1 Circumstance for certificate re-key

Applications for a subsequent Certificate with a replaced public key (the PKCS#10 structure) must meet the following requirements:

- The attributes under the subject field or the subjectAlternativeName extension must be identical to those in the Certificate which is to be replaced;
- PSD2 attributes must be the same as in the Certificate the public key of which is requested to be replaced. Before issuing the re-keyed Certificate PSD2 attributes must be verified;
- The public key must be different from that in the Certificate which is to be replaced;
- The electronic subsequent Certificate application is verified in accordance with 3.3.1.

4.7.2 Who may request certification of a new public key

Replacement of the public key in a Certificate may be requested by the Certificate's subscriber.

4.7.3 Processing certificate re-keying requests

If the public key replacement requirements are met, the procedure continues in accordance with 4.2 and 4.3.1, otherwise the Certificate issuance procedure is terminated.

4.7.4 Notification of new certificate issuance to subscriber

See 4.3.2.

4.7.5 Conduct constituting acceptance of a re-keyed certificate

See 4.4.1.

4.7.6 Publication of the re-keyed certificate by the CA

See 4.4.2.

4.7.7 Notification of certificate issuance by the CA to other entities

See 4.4.3.

4.8 Certificate modification

Modifying Certificate data under this CP means the issuance of a new Certificate in which a minimum of one change made to the content of the attributes concerning the Certificate's subscriber, under the subject field or the subjectAlternativeName extension or in which one field which requires content validation is deleted or added. The public key must be different from that in the Certificate which is to be modified.

If the whole new Certificate issuance procedure is handled solely electronically without requiring any natural person to be present at an RA office, it is the issuance of a subsequent Certificate. See 4.8.1 for the requirements in respect of verifying electronic applications for subsequent Certificates; if these requirements are not met, it is the primary Certificate issuance procedure, which starts with the registration procedure.

4.8.1 Circumstance for certificate modification

Applications for the issuance of subsequent Certificate (the PKCS#10 structure) with modified data must meet the following requirements:

- The attribute to be changed or added in the subject field or the subjectAlternativeName extension must be duly verified;
- The public key must be different from that in the original Certificate;
- The electronic subsequent Certificate application is verified in accordance with 3.3.1.

4.8.2 Who may request certificate modification

Modification the data in a Certificate may be requested by the Certificate's subscriber.

4.8.3 Processing certificate modification requests

If the certificate data modification requirements are met, the procedure continues in accordance with 4.2 and 4.3.1, otherwise the Certificate issuance procedure is terminated.

4.8.4 Notification of new certificate issuance to subscriber

See 4.3.2.

4.8.5 Conduct constituting acceptance of modified certificate

See 4.4.1.

4.8.6 Publication of the modified certificate by the CA

See 4.4.2.

4.8.7 Notification of certificate issuance by the CA to other entities

See 4.4.3.

4.9 Certificate revocation and suspension

Certificate revocation requests are accepted irrespective of the time of the day if submitted electronically or by post. Submission in person to an RA is only possible during the particular RA's business hours.

I.CA does not provide certificate suspension.

4.9.1 Circumstances for revocation

A Certificate must be revoked as a result of the following, among other things:

- If the private key corresponding to the Certificate's public key is compromised or reasonably suspected to have been compromised;
- If the Certificate's subscriber or the Organization violated Service (under this CP) contract;
- In any event specified in trust services legislation or the relevant technical and other standards, such as invalid Certificate data;
- If such a change of PSD2 attributes took place that the revocation of the Certificate is necessary;
- If the public key in the Certificate application is the same as the public key in a certificate already issued.

I.CA reserves the right to accept also other Certificate revocation situations, which, however, must not be contrary to trust services legislation.

4.9.2 Who can request revocation

Certificate revocation request may be submitted by:

- Certificate's subscriber;
- The entity explicitly specified therefore in the Service (under this CP) contract;
- Subjects designated by legislation through an authorized person;
- Person authorized to act on behalf of the legal successor of the Organization;
- Provider of this Service (CEO of I.CA is the person authorized to request for the revocation of a Certificate issued by I.CA):
 - If the Certificate is issued on the basis of false data;
 - If demonstrably establishes that the private key belonging to the public key specified in the Certificate has been compromised;
 - If establishes that the Certificate is issued in spite of noncompliance with the requirements of trust services legislation;
 - If demonstrably establishes that the Certificate was used contrary to the restrictions defined in 1.4.2;
 - If demonstrably establishes that the Certificate's subscriber has terminated or the data by which the Certificate was issued are no more valid;
 - If the public key in the Certificate application is the same as the public key in a certificate already issued;
 - If NCA sent via the way described in 3.4 information on PSD2 attributes change requiring revocation of the Certificate - information must be duly inquired;
- Supervisory body, and other entities as may be specified in trust services legislation;
- NCA e.g. Czech National Bank.

4.9.3 Procedure for revocation request

If the Certificate revocation request is submitted **by Subscriber** of this Certificate, then the procedure is:

- Any Certificate revocation request delivered to RA in person must include the Certificate's serial number either in decimal or hexadecimal format (introduced by the string '0x'), the full name of the natural person authorized to request for the Certificate's revocation, and the Certificate revocation password. If the natural person authorized to request for revocation does not know the Certificate revocation password, she/he must explicitly state this in the written application, along with the number of the primary personal document submitted in the Certificate application procedure or the number of the new primary personal document if the original document has been replaced. The person must use this primary personal document to prove their identity with the RA employee. If the request is legitimate, the RA employee revokes the Certificate, and the Certificate revocation date and time are the date and time the request is processed by CA's information system. If the Certificate revocation request cannot be accepted (wrong revocation password or no proof of identity of the natural person authorized to request for Certificate revocation) the RA employee seeks to rectify these defects, and dismisses the request if the defects cannot be rectified for any reason. The RA employee always notifies the requestor of the result;

- The following options are available for electronic submission of Certificate revocation requests:

- Using the form on the information web page. The Certificate revocation date and time are the date and time a valid Certificate revocation request is dealt with in the CA's information system. The requestor receives a notice if the request is accepted;
- Electronic message signed or sealed electronically – the body text must contain (in Czech or Slovak with or without diacritics, or in English):

Zadam o zneplatneni certifikatu cislo = xxxxxxxx. [I request revocation of certificate number = xxxxxxxx.],

where 'xxxxxxx' is the Certificate's serial number and must be given either in decimal or hexadecimal format (introduced by the string '0x').

The message must be electronically signed with the private key corresponding to the public key in the signing certificate or sealed with the private key corresponding to the public key in Certificate to be revoked;

- Electronic message not signed electronically – the body text must contain (in Czech or Slovak with or without diacritics, or in English):

Zadam o zneplatneni certifikatu cislo = xxxxxxxx. [I request revocation of certificate number = xxxxxxxx.]

Heslo pro zneplatneni = yyyyyy. [Revocation password = yyyyyy.],

where 'xxxxxxx' is the Certificate's serial number and 'yyyyyy' the revocation password. The Certificate's serial number must be given either in decimal or hexadecimal format (introduced by the string '0x').

- Electronic message signed electronically, or not signed electronically in special cases, and sent by a defined person authorized to represent the Organization in the contractual relationship with I.CA:

Zadam o zneplatneni certifikatu cislo = xxxxxxxx. [I request revocation of certificate number = xxxxxxxx.],

where 'xxxxxxx' is the Certificate's serial number. The Certificate's serial number must be given either in decimal or hexadecimal format (introduced by the string '0x');

Note: If the request meets the requirements of options listed above, the employee in charge immediately revokes the Certificate in the CA's system, and the date and time when the request is processed by the CA's information system are the date and time of the Certificate's revocation. The requestor receives a notice if the request is accepted.

- If Certificate revocation request is sent as a registered post letter, the request must contain the text (in Czech or Slovak with or without diacritics, or in English):

Zadam o zneplatneni certifikatu cislo = xxxxxxxx. [I request revocation of certificate number = xxxxxxxx.]

Heslo pro zneplatneni = yyyyyy. [Revocation password = yyyyyy.]

where 'xxxxxxx' is the Certificate's serial number and 'yyyyyy' the revocation password. The serial number is to be given either in decimal or hexadecimal format (introduced by the string '0x'). If the request meets these requirements, the I.CA employee in charge immediately revokes the Certificate in the CA's system, and the date and time the

request is processed by the CA's information system are the date and time of the Certificate's revocation. If the request cannot be accepted (wrong revocation password), the Certificate revocation request will be rejected. Requestor is informed by a registered letter sent to postal address of request sender how the request was handled.

If the Certificate revocation request is submitted **by NCA**, then the procedure can be one of these:

1. Sending revocation request to the specific e-mail address of I.CA which can be used by NCA for sending:

- Requests for revocation of certain Certificates;
- Information on changing PSD2 attributes of certain PSP which could impact the validity of this PSP's Certificate.

If NCA e-mail address is made public in EBA list of e-mail addresses designated for communication concerning Certificates then I.CA will send to this address its e-mail address designated for Certificate revocation. In an opposite case NCA can ask for this specific e-mail address by sending an e-mail to info@ica.cz and this e-mail:

- Is electronically sealed or electronically signed using qualified certificate (for NCA electronic seal or for the electronic signature of natural person connected with NCA); or
- Contains the request as the PDF attachment secured in the same way as described in the bullet above.

2. Sending revocation request via data box of I.CA.

Revocation request must meet these requirements:

- Revocation request must be the PDF form which:
 - Is electronically sealed or electronically signed using qualified certificate (for NCA electronic seal or for the electronic signature of natural person connected with NCA);
 - Is secured by password (shared secret) which for this purpose I.CA gave to NCA;
- Revocation request must contain:
 - The serial number of Certificate in the decimal or hexadecimal format (introduced by the string '0x');
 - Authorization number of PSP;
 - Reasons for revocation:
 - PSP's authorization was terminated;
 - PSP role indicated in the Certificate was terminated;
- The Certificate specified in the revocation request must contain the identifier of requesting NCA;
- The Certificate with serial number specified in the revocation request must be issued to PSP mentioned in the request.

If the Certificate's revocation request does not contain the reason for revocation or the reason is different from those mentioned above, I.CA will handle the revocation request after additional inquiry. NCA is informed of the way of request handling. If NCA is not authorized to request for the revocation then the Certificate is not revoked.

If the request contains all necessary data and its authenticity is verified (see chapter 3.4 above) then the I.CA employee in charge immediately revokes the Certificate in the CA's information system and the Certificate's revocation date and time are the date and time when the request is processed by the CA's information system.

If NCA informs I.CA of e-mail address where it can be contacted in connection with Certificates then I.CA will send to this address information how this NCA can request for revocation of Certificates containing identifier of this NCA. To this e-mail address I.CA will send information on revoked Certificates containing identifier of this NCA; see also chapter 2 above.

4.9.4 Revocation request grace period

Certificate revocation request must be made immediately.

4.9.5 Time within which CA must process the revocation request

The maximum time allowed between accepting a Certificate revocation request and the Certificate's revocation is 24 hours.

4.9.6 Revocation checking requirement for relying parties

Relying parties must carry out all the operations specified in 4.5.2.

4.9.7 CRL issuance frequency

The certificate revocation list is released immediately after a Certificate revocation request is handled affirmatively. If a Certificate is not revoked, the new CRL is usually released within 8 but no more than 24 hours after the previous CRL is released.

4.9.8 Maximum latency for CRLs

The CRL is always released within 24 hours of the release of the previous CRL.

4.9.9 On-line revocation/status checking availability

Checking Certificate status using the OCSP protocol is a service available to the general public. Every certificate issued under this CP includes a link to the pertinent OCSP responder.

OCSP responses satisfy the RFC 2560 and RFC 5019 standards. The OCSP responder's certificate includes an id-pkix-ocsp-nocheck extension as defined in RFC 2560.

4.9.10 On-line revocation checking requirements

See 4.9.9.

4.9.11 Other forms of revocation advertisements available

Not applicable to this document.

4.9.12 Special requirements re key compromise

The Certificate revocation procedure in the event of private key compromise is not different from the certificate revocation procedure described above.

4.9.13 Circumstances for suspension

Not applicable to this document; Certificate suspension is not provided.

4.9.14 Who can request suspension

Not applicable to this document; Certificate suspension is not provided.

4.9.15 Procedure for suspension request

Not applicable to this document; Certificate suspension is not provided.

4.9.16 Limits on suspension period

Not applicable to this document; Certificate suspension is not provided.

4.10 Certificate status services

4.10.1 Operational characteristics

Lists of public Certificates are provided as published information; certificate revocation lists are provided as published information and by specifying the CRL distribution points in the Certificates issued by Authority.

The fact that the Authority provides Certificate status information as OCSP is specified in the Certificates issued by Authority.

4.10.2 Service availability

The Authority guarantees round-the-clock (24/7) availability and integrity of the list of the Certificates it has issued and the list of revoked certificates (valid CRLs), plus the availability of the OCSP service.

Revocation records on CRL or in OCSP response are kept at least to the end of Certificate's validity period.

Response time to revocation request using CRL or OCSP is normally less than 10 seconds.

4.10.3 Optional features

Not applicable to this document; no other certificate status check characteristics are provided.

4.11 End of subscription

The obligations of I.CA arising from Service contract survive the validity of this contract until the expiration of the last Certificate issued under this contract.

4.12 Key escrow and recovery

Not applicable to this document; the key escrow and recovery service is not provided.

4.12.1 Key escrow and recovery policy and practices

See 4.12.

4.12.2 Session key encapsulation and recovery policy and practices

See 4.12.

5 FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS

Facility, management, and operational controls primarily deal with:

- Trustworthy systems designed to support trust services;
- All processes supporting the provision of the services specified above.

The facility, management, and operational controls are addressed in the fundamental documents Corporate Security Policy, System Security Policy – Trustworthy Systems, Certification Practice Statement, Business Continuity Plan and Recovery Plan as well as the more detailed internal documentation. These documents take account of the results of periodic risk analyses.

5.1 Physical controls

5.1.1 Site location and construction

The operating site buildings are situated in geographically different locations, which are also different from the site of the company headquarters, the business and development sites, the registration authority sites and the points of sale.

The trustworthy systems designed to support trust services are situated on reserved premises of operating sites. These premises are secured in a manner similar to that required by the Classified Information Protection Act for the 'Confidential' category secure areas.

5.1.2 Physical access

Requirements for physical access to the reserved premises (protected with mechanical and electronic features) of operating sites are described in internal documentation. Buildings are protected with intrusion alarm system (IAS), alarm receiving centre (ARC) and, as may be the case, a special system to monitor movement of persons and vehicles.

5.1.3 Power and air conditioning

The premises housing the trustworthy systems supporting trust services have active air-conditioning of adequate capacity, which keeps the temperature at $20^{\circ}\text{C} \pm 5^{\circ}\text{C}$ all year round. The supply of electricity is backed up with a UPS (Uninterruptible Power Supply) and a diesel unit.

5.1.4 Water exposures

The trustworthy systems supporting trust services are so located as to ensure they cannot be flooded with a 100-year flood. Operating sites, where relevant, have water ingress sensors to detect heating water leakage or rainfall leakage through the roof (as a result of heavy rains).

5.1.5 Fire prevention and protection

The buildings of the operating sites and the information storage sites have electronic fire alarm system (FAS). Fireproof insulation is installed in the entrance doors to the restricted areas in which the trustworthy systems designed to support trust services are situated, and fire extinguishers are fitted in these areas.

5.1.6 Media storage

Storage media containing operational backups and electronic records are stored in metal boxes or safes. Copies are kept at a site geographically different from the site of the operating office.

Any paper media required to be kept are stored in a site geographically different from the site of the operating office.

5.1.7 Waste disposal

Any paper office waste is shredded before it leaves I.CA operating sites.

5.1.8 Off-site backup

The copies of operating and working backups are stored in a place designated by the Chief Operating Officer (COO) of I.CA and described in internal documentation.

5.2 Procedural controls

5.2.1 Trusted roles

Trusted roles are defined for selected activities carried out at I.CA. The trusted role employee appointment procedure, the trusted roles and their responsibilities are defined in internal documentation.

No I.CA employee appointed to a trusted role may be in a conflict of interests that could compromise the impartiality of operations of I.CA.

5.2.2 Number of persons required per task

Jobs are defined for the processes related to the key pairs of certification authorities and OCSP responders and these jobs must be performed with more than a single person attending. These jobs include:

- Initialization of cryptographic module;
- Generating key pairs of certification authorities and their OCSP responders;
- Destroying private keys of certification authorities and their OCSP responders;
- Backup and restore of private keys of certification authorities and their OCSP responders;
- Activation and deactivation of private keys of certification authorities and their OCSP responders.

The number of attending persons is not defined for other jobs, but all persons must be authorized persons.

5.2.3 Identification and authentication for each role

Each role's employees are assigned identification (name and certificate) and authentication (password and private key) data for those components which are necessary for their jobs.

Selected jobs require two-factor authentication by the trusted role employees.

5.2.4 Roles requiring separation of duties

The roles requiring separation of duties (and the roles' job descriptions) are described in internal documentation.

5.3 Personnel controls

5.3.1 Qualification, experience, and clearance requirements

Trusted roles employees in I.CA are selected and hired using the following criteria:

- Clean criminal record – statement of criminal conviction records or affirmation is required;
- Bachelor's or master's degree in an accredited university program and ICT job experience of three years or longer, or secondary education and ICT job experience of five years or longer, of which at least one-year job experience in the provision of trust services;
- Knowledge in public key infrastructure and information security.

Any other I.CA employee taking part in providing trust services is accepted using the following criteria:

- Bachelor's or master's degree in an accredited university program, or secondary education;
- Basic orientation in public key infrastructure and information security.

Managers must have job experience or technical training in respect of the trustworthiness of the Service, the knowledge of security procedures with security responsibility, and experience in information security and risk assessment.

5.3.2 Background check procedures

The sources of information about all employees of I.CA are:

- The employees themselves;
- Persons familiar with a particular employee;
- Public sources of information.

Initial information is provided by employees at job interviews, and this information is updated at periodic appraisal interviews with the manager during employment.

5.3.3 Training requirements

I.CA employees receive technical training in the use of specific software and specialized devices. The training takes the form of [self-study] combined with guidance from a trained employee. The training covers information security, personal protection data and other relevant topics.

5.3.4 Retraining frequency and requirements

I.CA employees are provided with the current developments in their spheres of interest two times every 12 months.

Training in the processes related to RA operations is held for RA employees at least once in every three years.

5.3.5 Job rotation frequency and sequence

I.CA employees are encouraged to acquire knowledge necessary for working in other roles at I.CA, in order to ensure substitutability for cases of emergency.

5.3.6 Sanctions for unauthorized actions

If an employee is detected to have been performing unauthorized activity, the employee is subject to the procedure described in internal documentation and governed by the Labour Code (this process does not prevent criminal prosecution if the unauthorized activity exhibits that degree of gravity).

5.3.7 Independent contractor requirements

I.CA may or must procure some activities from independent contractors, and is fully liable for the job they deliver. These business relations are regulated in bilateral business contracts with parties such as contracted registration authorities, application software developers, hardware suppliers, system software suppliers, external auditors and other parties. These parties are required to observe the pertinent certification policies, the relevant parts of internal documentation provided for them, and the required normative documents. Contractual penalties are applied for a breach of the obligations or duties specified in the said documents, or the contract with the contractor in breach is terminated immediately.

5.3.8 Documentation supplied to personnel

In addition to the certification policy, the certificate practice statement and the security and operating documentation, I.CA employees have available any other relevant standard, policy, manual and guidance they may need for their job.

5.4 Audit logging procedures

5.4.1 Types of events recorded

Subject to logging are all the events required by trust services legislation or the relevant technical and other standards to be logged, that is, for example, the life cycle events for the

Certificates, the certificates of the Authority and the root CA and their respective OCSP responders.

The Authority's key pair generation event is a special case of event logging; the following minimum standard is applied at all times:

- The generation is organized according to a pre-determined scenario in a physically secure environment;
- The event is video-recorded where possible.

All audit records are made, kept and processed to the extent as necessary, while preserving the proof of origin and maintaining integrity, availability, confidentiality and time authenticity.

The auditing system is designed and run in a manner ensuring audit data integrity, sufficient space for audit data, automatic non-rewriting of the audit file, user-friendly presentation of audit records, and audit file access limited to the defined users only.

5.4.2 Frequency of processing log

Audit records are checked and assessed at the intervals defined in internal documentation, or immediately when a security incident occurs.

5.4.3 Retention period for audit log

Unless the relevant legislation provides otherwise, audit records are kept for a minimum of 10 years of the day they are made.

5.4.4 Protection of audit log

Both electronic and printed audit records are stored in a manner ensuring they are protected against change, stealing and destruction (willful or accidental).

Electronic audit records are stored in two copies, with each copy kept in a different room of the operating site. These audit records are saved on a medium each month or more frequently and this medium is kept outside the operating premises of I.CA.

Printed audit records are kept outside the operating premises of I.CA.

The protection of the aforesaid types of audit records is described in internal documentation.

5.4.5 Audit log backup procedures

Electronic audit records are backed up similarly to how other electronic information is backed up. No backup of printed audit records takes place.

5.4.6 Audit collection system (internal vs. external)

The audit record collection system is an internal one relative to the CA information systems.

5.4.7 Notification to event-causing subject

Parties are not notified of that an event is registered in an audit record.

5.4.8 Vulnerability assessments

První certifikační autorita, a.s., carries out periodic vulnerability assessments as part of risk assessments. Vulnerability monitoring of the hardware and software related to trust services is described in internal documentation.

5.5 Records archival

The storage of records, i.e. information and documentation, at První certifikační autorita, a.s., is regulated by internal documentation.

5.5.1 Types of records archived

I.CA stores the following electronic or printed records pertaining to the trust services provided, such as:

- Life cycle records for the Certificates issued, the Certificates issued and the certificates related thereto;
- Video recordings, if any, of the generation of the Authority's paired data;
- Other records that may be necessary for issuing Certificates;
- Information handling records, such as takeover, handover, saving, check, conversion from printed to electronic, etc.;
- Application software, operating and security documentation.

5.5.2 Retention period for archive

All records pertaining to the certificates of all I.CA certification authorities and their respective OCSP responders, except for the pertinent private keys, are stored throughout the existence of I.CA. Other records are stored in accordance with 5.4.3.

The record storage procedures are regulated by internal documentation.

5.5.3 Protection of archive

The premises where records are stored are secured in a manner based on risk analysis results and the Classified Information Protection Act.

The procedures to protect the stored records are regulated by internal documentation.

5.5.4 Archive backup procedures

The record backup procedures are regulated by internal documentation.

5.5.5 Requirements for time-stamping of records

If time-stamp tokens are used, they are qualified electronic time-stamp tokens issued by I.CA.

5.5.6 Archive collection system (internal or external)

Records are stored in a place designated by COO of I.CA.

Internal documentation regulates how both electronic and printed records are prepared for storage and stored. Records are kept of collecting the records subject to storage.

5.5.7 Procedures to obtain and verify archive information

Stored information and records are placed at sites designated therefore and are accessible to:

- I.CA employees if they need to have such an access for their job;
- Authorized supervising and inspection entities and law enforcement authorities if required by legislation.

A written record is made of any such permitted access.

5.6 Key changeover

In standard situations (expiration of a certification authority certificate), the key is replaced by issuing a new certificate a good time in advance (no later than one year prior to the expiration). In non-standard situations, for instance such developments in cryptanalytic methods that could compromise the security of certificate issuance (e.g. changes to cryptanalytic algorithms or key length), the key is replaced as soon as possible.

In both standard and non-standard situations, the replacement of the public key in certification authority certificates is suitably notified to the public a good time in advance (if practicable).

5.7 Compromise and disaster recovery

5.7.1 Incident and compromise handling procedures

In the event of incident or compromise, I.CA takes a course of action in accordance with its internal business continuity plan and recovery plan, plus any other relevant internal documentation.

5.7.2 Computing resources, software, and/or data are corrupted

See. 5.7.1.

5.7.3 Entity private key compromise procedures

In the case of reasonable concern that a private key of certification authorities has been compromised, I.CA does the following:

- Stops using the private key;
- Revokes immediately and permanently the pertinent certificate and destroys the corresponding private key;

- Revokes relevant valid Certificates;
- Notifies this and the reason immediately on its web Information Address, and also the list of revoked certificates is used for disclosing this information;
- Notifies the supervisory body of that the pertinent certificate has been revoked and why it has been revoked.

A similar course of action will be taken in the event of such developments in cryptanalytic methods, such as changes to cryptanalytic algorithms or key length that could immediately compromise the security of the trust services.

5.7.4 Business continuity capabilities after a disaster

In the event of accident, I.CA takes a course of action in accordance with its internal business continuity plan and recovery plan, plus any other relevant internal documentation.

5.8 CA or RA termination

The following rules apply to the termination of the Authority's operations:

- The termination of the Authority's operations must be notified in writing to the supervisory body, all subscribers of valid Certificates, and the parties having a contract with I.CA that directly concerns the provision of trust services;
- The termination of the Authority's operations must be published on the web page pursuant to 2.2;
- If the Authority's certificate's expiration is part of termination of operations, this information plus the reason for expiration must be included in that notice;
- The termination of operations is a controlled process following a pre-defined plan, which includes the description of the procedure to preserve and disclose information for judicial or administrative proceedings discovery and for arranging the continuity of services;
- The Authority or its successor must be able to revoke Certificates and publish CRLs as long as any Certificate issued by the Authority is valid;
- After that the Authority must demonstrably destroy its private key, make a record of this destruction and keep this record in accordance with this CP.

In the event of withdrawal of the qualified Service provider status:

- The information must be notified in writing or electronically to all subscribers of valid Certificates, and the parties having a contract with I.CA that directly concerns the provision of trust services;
- The information must be published in accordance with 2.2. at all offices of registration authorities and must also communicate that certification authorities' certificates cannot be used in accordance with the purpose of their issuance any longer;
- The subsequent course of action will be decided by CEO of I.CA while taking account of the decision of the supervisory body.

If a specific RA office closes down, this is published on <http://www.ica.cz>.

6 TECHNICAL SECURITY CONTROLS

6.1 Key pair generation and installation

6.1.1 Key pair generation

Key pairs of certification authorities are generated in designated secured areas of operating sites, according to a pre-defined scenario, in accordance with 5.2 and 5.4.1. Generation is carried out in cryptographic modules assessed under FIPS PUB 140-2, level 3 and is evidenced in a written report.

The generation of key pairs of certification authorities' OCSP responders is carried out in cryptographic modules assessed under FIPS PUB 140-2, level 3.

Key pairs of the employees taking part in the issuance of Certificates to end users are generated on smartcards meeting the QSCD requirements. The private keys of these key pairs are stored on smartcard in non-exportable form and PIN needs to be entered to use the keys.

Key pairs related to Certificates issued under this CP are generated on devices which are under sole control of the respective subscribers. These key pairs may be stored on hardware and in software.

6.1.2 Private key delivery to subscriber

Not applicable to the private keys of certification authorities and their corresponding OCSP responders – private keys are stored in a cryptographic module under the sole control of I.CA.

The service of generating key pairs to end users is not provided.

6.1.3 Public key delivery to certificate issuer

Not applicable to the private keys of certification authorities and their corresponding OCSP responders – public keys as parts of key pairs are generated in a cryptographic module under the sole control of I.CA.

Other public keys are delivered to the Authority in the Certificate application (the PKCS#10 format).

6.1.4 CA public key delivery to relying parties

Certification authorities' public keys are included in these authorities' certificates, and the following options for obtaining the keys are guaranteed:

- Handover from RA;
- Via web information addresses of I.CA, relevant supervisory body or its journal;
- Every subscriber gets relevant certification authorities' certificates together with his primary certificate.

6.1.5 Key sizes

The RSA asymmetric algorithm is solely used for the Service provided under this CP. The size of the key (or the given algorithm's parameters) of I.CA root certification authority is 4096 bits; the minimum size of the keys (or the given algorithm's parameters) in the certificates issued by that root authority is 2048 bits. The minimum size of the keys in the Certificates issued under this CP is 2048 bits.

6.1.6 Public key parameters generation and quality checking

The parameters of the algorithms used in generating public keys of certification authorities and their OCSP responders meet the requirements listed in trust services legislation and the technical and other standards referred to therein.

The parameters of the algorithms used in generating public keys of subscribers must also meet these requirements.

I.CA checks the permitted key length and checks for any duplicate public key occurrence in the Certificates issued. If duplicate occurrence is detected, the pertinent Certificate is revoked immediately and the Certificate's subscriber is immediately and suitably notified and asked to generate new key pair.

6.1.7 Key usage purposes (as per X.509 v3 key usage extension)

The key usage options are specified in the Certificate's extension.

6.2 Private key protection and cryptographic module engineering controls

6.2.1 Cryptographic module standards and controls

Key pairs of certification authorities and their OCSP responders are generated and private keys are stored in cryptographic modules which meet the requirements of trust services legislation, that is, the FIPS PUB 140-2 standard, level 3.

6.2.2 Private key (n out of m) multi-person control

If cryptographic module related operations require the presence of two I.CA management members or employees authorized by them, then each of them knows only some part of the code required for these operations.

6.2.3 Private key escrow

Not applicable to this document; the private key escrow service is not provided.

6.2.4 Private key backup

The cryptographic module used for the administration of certification authorities' and their OCSP responders' key pairs facilitates private key backup. Private keys are backed up using the native features of the cryptographic module in the encrypted form.

6.2.5 Private key archival

When certification authorities' and their OCSP responders' private keys expire, they and their backup copies are destroyed. Because storing these private keys is a security risk, it is prohibited at I.CA.

6.2.6 Private key transfer into or from a cryptographic module

The private keys of subordinate certification authorities are transferred from/into the cryptographic module under direct personal participation of no fewer than two I.CA management members or employees authorized by them.

The private keys of subordinate certification authorities' OCSP responders are transferred from/into the cryptographic module under direct personal participation of no fewer than one I.CA management member or employee authorized by him.

Every actual transfer is documented in a written record.

6.2.7 Private key storage on cryptographic module

The private keys of certification authorities and their OCSP responders are stored in the cryptographic module which meets the requirements of trust services legislation, that is, the FIPS PUB 140-2 standard, level 3.

6.2.8 Method of activating private key

The private keys of certification authorities stored in the cryptographic module are activated under direct personal participation of no fewer than two I.CA management members or employees authorize by them with the use of an activation smartcard and pursuant to a strictly defined procedure described in internal documentation. Every activation is documented in a written record.

The private keys of OCSP responders of subordinate certification authorities stored in the cryptographic module are activated under direct personal participation of one I.CA management member or employee authorize by him with the use of activation smartcard and pursuant to a strictly defined procedure described in internal documentation. Every actual activation is documented in a written record.

6.2.9 Method of deactivating private key

The private keys of certification authorities stored in the cryptographic module are deactivated under direct personal participation of no fewer than two I.CA management members or employees authorized by them with the use of an activation smartcard and pursuant to a strictly defined procedure described in internal documentation. Every actual deactivation is documented in a written record.

The private keys of OCSP responders of subordinate certification authorities stored in the cryptographic module are deactivated under direct personal participation of one I.CA management member or employee authorized by him with the use of an activation smartcard and pursuant to a strictly defined procedure described in internal documentation. Every actual deactivation is documented in a written record.

6.2.10 Method of destroying private key

The private keys of certification authorities and their OCSP responders stored in the cryptographic module are destroyed with the native features of that cryptographic module and under direct personal participation of no fewer than two I.CA management members or employees authorize by them pursuant to a strictly defined procedure described in internal documentation. Every actual destruction is documented in a written record.

Any external medium with a backup copy of those private keys is also destroyed. The destruction, consisting in physical destruction of those data media, is carried out under direct personal participation of no fewer than two I.CA management members or employees authorize by them pursuant to a strictly defined procedure described in internal documentation. Every actual destruction is documented in a written record.

6.2.11 Cryptographic module rating

The cryptographic modules in which key pairs are generated and the private keys of certification authorities and their OCSP responders are stored meet the requirements of trust services legislation, that is, the FIPS PUB 140-2 standard, level 3. The security of the modules is under monitoring as long as they are in use.

6.3 Other aspects of key pair management

6.3.1 Public key archival

All public keys as part of Certificates are stored throughout the existence of I.CA.

6.3.2 Certificate operational periods and key pair usage periods

The maximum period of validity of each certificate issued is specified in the body of that certificate and is the same as key pair usage period.

6.4 Activation data

6.4.1 Activation data generation and installation

The activation data of certification authorities and their OCSP responders are created during the generation of the corresponding key pair.

6.4.2 Activation data protection

The activation data of certification authorities and their OCSP responders are protected by a method described in internal documentation.

6.4.3 Other aspects of activation data

The activation data of certification authorities and their OCSP responders must not be transferred or kept in an open form. All aspects are described in internal documentation.

6.5 Computer security controls

6.5.1 Specific computer security technical requirements

The level of security of the components used in providing trust services is, including the scope of necessary evaluations and assessments and also trustworthy systems configuration checks, and their periodicity, defined in trust services legislation and the technical standards referred to therein.

6.5.2 Computer security rating

The assessment of I.CA computer security is based on the requirements set out in the specified technical and other standards, in particular:

- CEN/TS 419261 Security requirements for trustworthy systems managing certificates and time-stamps.
- ČSN ETSI EN 319 401 Electronic Signatures and Infrastructures (ESI) – Policy and Security Requirements for Trust Service Providers.
- ETSI EN 319 401 Electronic Signatures and Infrastructures (ESI); General Policy Requirements for Trust Service Providers.
- ČSN ETSI EN 319 403 Electronic Signatures and Infrastructures (ESI) – Trust Service Provider Conformity Assessment – Requirements for Conformity Assessment Bodies Assessing Trust Service Providers.
- ETSI EN 319 403 Electronic Signatures and Infrastructures (ESI); Trust Service Provider Conformity Assessment – Requirements for Conformity Assessment Bodies Assessing Trust Service Providers.
- ČSN ETSI EN 319 411-1 Electronic Signatures and Infrastructures (ESI) – Policy and Security Requirements for Trust Service Providers Issuing Certificates – Part 1: General Requirements.
- ETSI EN 319 411-1 Electronic Signatures and Infrastructures (ESI); Policy and Security Requirements for Trust Service Providers Issuing Certificates; Part 1: General Requirements.
- ČSN ETSI EN 319 411-2 Electronic Signatures and Infrastructures (ESI) – Policy and Security Requirements for Trust Service Providers Issuing Certificates – Part 2: Requirements for Trust Service Providers Issuing EU Qualified Certificates.
- ETSI EN 319 411-2 Electronic Signatures and Infrastructures (ESI); Policy and Security Requirements for Trust Service Providers Issuing Certificates; Part 2: Requirements for Trust Service Providers Issuing EU Qualified Certificates.
- ETSI TS 119 312 Electronic Signatures and Infrastructures (ESI); Cryptographic Suites.
- ČSN ISO/IEC 27006 Information Technology – Security Techniques – Requirements for Bodies Providing Audit and Certification of Information Security Management Systems.
- ISO/IEC 17021 Conformity Assessment -- Requirements for Bodies Providing Audit and Certification Of Management Systems.
- ISO/IEC 17065 Conformity Assessment -- Requirements for Bodies Certifying Products, Processes and Services.

The Authority's operations are also governed by the following technical standards:

- FIPS PUB 140-2 Requirements for Cryptographic Modules.
- ISO 3166-1 Codes for the Representation of Names of Countries and Their Subdivisions – Part 1: Country Codes.
- ITU-T - X.501 Information Technology – Open Systems Interconnection – The Directory: Models.
- ITU-T - X.509 Information Technology – Open Systems Interconnection – The Directory: Public-key and Attribute Certificate Frameworks.
- ITU-T - X.520 Information Technology – Open Systems Interconnection – The Directory: Selected Attribute Types.
- RSA Laboratories - PKCS#10: Certification Request Syntax Standard.
- RFC 2560 X.509 Internet Public Key Infrastructure Online Certificate Status Protocol – OCSP.
- RFC 3647 Internet X.509 Public Key Infrastructure Certificate Policy and Certification Practices Framework.
- RFC 5019 The Lightweight Online Certificate Status Protocol (OCSP) Profile for High-Volume Environments.
- RFC 5280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile.
- EN 301 549 Accessibility requirements for ICT products and services.
- REGULATION (EU) 2018/389 of 27 November 2017 supplementing Directive (EU) 2015/2366 of the European Parliament and of the Council with regard to regulatory technical standards for strong customer authentication and common and secure open standards of communication.
- ETSI TS 119 495 Electronic Signatures and Infrastructures (ESI); Sector Specific Requirements; Qualified Certificate Profiles and TSP Policy Requirements under the payment services Directive (EU) 2015/2366.
- ČSN ETSI EN 319 412-1 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 1: Overview and Common Data Structures.
- ETSI EN 319 412-1 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 1: Overview and Common Data Structures.
- ČSN ETSI EN 319 412-2 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 2: Certificate Profile for Certificates Issued to Natural Persons.
- ETSI EN 319 412-2 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 2: Certificate Profile for Certificates Issued to Natural Persons.
- ČSN ETSI EN 319 412-3 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 3: Certificate Profile for Certificates Issued to Legal Persons.
- ETSI EN 319 412-3 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 3: Certificate Profile for Certificates Issued to Legal Persons.
- ČSN ETSI EN 319 412-5 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 5: QC Statements.
- ETSI EN 319 412-5 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 5: QCStatements.

6.6 Life cycle technical controls

6.6.1 System development controls

System development is carried out in accordance with internal documentation.

6.6.2 Security management controls

Information security management and compliance with technical standards are inspected as part of the periodic trust services inspections and also during information security management system (ISMS) audits.

Information security at I.CA is governed by the following standards:

- ČSN ISO/IEC 27000 Information Technology – Security Techniques – Information Security Management Systems – Overview and Vocabulary.
- ČSN ISO/IEC 27001 Information Technology – Security Techniques – Information Security Management Systems – Requirements.
- ČSN ISO/IEC 27002 Information Technology – Security Techniques – Information Security Management Systems – Code of Practice for Information Security Controls.

6.6.3 Life cycle security controls

I.CA takes the Plan-Do-Check-Act (PDCA) procedural approach to life cycle security management; the PDCA approach consists of the following consecutive processes:

- Establishing – defining the scope and the boundaries for information security management, determining a security policy and plans, and choosing security controls depending on the risks identified, all this in accordance with the corporate security policy;
- Implementing and operating – effective and systematic enforcement of the selected security controls;
- Monitoring and reviewing – providing feedback, regular monitoring and evaluation of the successful and the poor aspects of information security management, providing the knowledge gained for the company management for assessment;
- Maintenance and improvement – implementing corrective and improvement measures as decided by the company management.

6.7 Network security controls

In the I.CA environment the trustworthy systems destined for supporting trust services and situated at operating sites of I.CA are not directly accessible from the Internet. These systems are protected with a firewall-type commercial product with an integrated intrusion prevention system (IPS). All communication between RA and the operating sites is encrypted.

6.8 Time-stamping

See 5.5.5 for the time-stamping solution.

7 CERTIFICATE PROFILE, CRL PROFILE AND OCSP PROFILE

7.1 Certificate profile

Table 4 – Basic certificate fields

Field	Content
version	v3 (0x2)
serialNumber	unique serial number of the Certificate
signatureAlgorithm	sha256withRSAEncryption at minimum
issuer	issuer of the Certificate (the Authority)
validity	
notBefore	start of the Certificate's validity (UTC)
notAfter	end of the Certificate's validity (UTC)
subject	see Table 5
subjectPublicKeyInfo	
algorithm	rsaEncryption
subjectPublicKey	2048 bits at minimum
extensions	see Table 6
signature	Authority's electronic sign/seal

Table 5 – Subject field attributes

All attributes¹ of the subject field are taken over from the Certificate application except those created by the Authority. The application must include mandatory attributes.

Subject field attribute	Comments
countryName*	mandatory, country code (ISO 3166), single occurrence: <ul style="list-style-type: none"> state where organization is registered; context of all other subject attributes
serialNumber	unique identification of the Certificate's subscriber in the Authority's system (ICA - xxxxxxxx); also used in automated subsequent certificate issuance
commonName	mandatory; single occurrence, applicable content: <ul style="list-style-type: none"> name under which the Certificate subject (private key owner) commonly acts, does not have to contain full registered name (can contain shortened name of

¹ I.CA reserves the right to modify the set of attributes and the content of the subject field as may be required by updated ETSI standards or third parties (Microsoft, for example).

	<p>organization), identification of equipment or ICT component creating electronic seals can be appended,</p> <ul style="list-style-type: none"> • must not contain FQDN or IP address
organizationName	mandatory; single occurrence
organizationIdentifier	<p>mandatory; single occurrence, UTF8String (SIZE (1..256))</p> <p>PSP's authorization number:</p> <p>1) If NCA states in PSP register the PSP identifier then it will be included in this form:</p> <ul style="list-style-type: none"> ▪ PSDcc-registrarID-PSP_identifier. <p>2) If NCA does not stated PSP identifier in PSP register then the unique PSP identifier from any other respected register will be included in compliance with EN 319 412-1 or TS 119412-1 (prefixes NTR, VAT and the like),</p> <p>where:</p> <ul style="list-style-type: none"> • cc = country code according to ISO 3166, same as countryName attribute; • registrarID = NCA abbreviated name, between 2 and 8 capital letters without delimiter; • PSP_identifier = PSP identifier (usually the number) without prefix defining the type of identifier (NTR, VAT and the like), no restrictions concerning used characters
organizationalUnitName	optional, multiple occurrences permitted
stateOrProvinceName*	optional; single occurrence
localityName*	<p>optional; single occurrence</p> <p>if specified, streetAddress and postalCode must also be specified</p>
streetAddress*	<p>optional; single occurrence</p> <p>if specified, localityName and postalCode must also be specified</p>
postalCode*	<p>optional; single occurrence</p> <p>if specified, localityName and streetAddress must also be specified</p>

* Attributes countryName, stateOrProvinceName, localityName, streetAddress and postalCode relate to registered address of Organization.

7.1.1 Version number(s)

Any Certificate issued complies with standard X.509, version 3.

7.1.2 Certificate extensions

Table 6 – Certificate Extensions²

Extension	Content	Comments
certificatePolicies		non-critical
.policyInformation (1)		
policyIdentifier	see 1.2	
policyQualifiers		
cPSuri	http://www.ica.cz	
userNotice	Tento kvalifikovaný certifikát pro elektronickou pečeť byl vydán v souladu s nařízením EU č. 910/2014. This is a qualified certificate for electronic seal according to Regulation (EU) No 910/2014.	
.policyInformation (2)		
policyIdentifier	one of following options: <ul style="list-style-type: none"> • OID (QCP-I): 0.4.0.194112.1.1 (private key is not generated and stored on QSCD); • OID (QCP-I-qscd): 0.4.0.194112.1.3 (private key is generated and stored on QSCD) 	
CRLDistributionPoints*	http://qcrlp1.ica.cz/2qcaYY_rsa.crl http://qcrlp2.ica.cz/2qcaYY_rsa.crl http://qcrlp3.ica.cz/2qcaYY_rsa.crl	non-critical
authorityInformationAccess		non-critical
id-ad-ocsp*	http://ocsp.ica.cz/2qcaYY_rsa	
id-ad-caIssuers*	http://q.ica.cz/2qcaYY_rsa.cer	
basicConstraints		non-critical
cA	False	
keyUsage	one of following options, according to what is filled in Certificate application: <ul style="list-style-type: none"> • nonRepudiation; ▪ digitalSignature, nonRepudiation; 	critical, mandatory if this extension is missing in the application, the following will be added:

² I.CA reserves the right to modify the set and the content of Certificate extensions as may be required by updated ETSI standards or third parties (Microsoft, for example).

	<ul style="list-style-type: none"> ▪ digitalSignature, nonRepudiation a keyEncipherment 	digitalSignature, nonRepudiation
extendedKeyUsage ³	<p>one of following options, according to what is filled in Certificate application:</p> <ul style="list-style-type: none"> • id-kp-emailProtection; • ms-Document_Signing; • id-kp-emailProtection, ms-Document_Signing 	<p>non-critical, mandatory</p> <p>if this extension is missing from the application, the following will be added:</p> <p>id-kp-emailProtection</p>
subjectKeyIdentifier	hash of the public key (subjectPublicKey) in the Certificate	non-critical
authorityKeyIdentifier		non-critical
keyIdentifier	hash of the Authority's public key	
subjectAlternativeName		non-critical
otherName**	I.CA_User_ID(1.3.6.1.4.1.23624.4.6) : xxxxxxxx	
rfc822Name	e-mail address	optional; multiple occurrences permitted
QCStatements		non-critical
	0.4.0.1862.1.1	Id-etsi-qcs-QcCompliance
	0.4.0.1862.1.4	non-critical; optional – creates Authority when generation and storing of the private key on QSCD was verified
	0.4.0.1862.1.5	id-etsi-qcs-QcPDS; link (URI, https) to PKI Disclosure Statement (PDS)
	0.4.0.1862.1.6 = 0.4.0.1862.1.6.2	id-etsi-qcs-QcType = id-etsi-qct-eseal
	0.4.0.19495.2***	id-etsi-psd2-qcStatement <ul style="list-style-type: none"> ▪ PSD2 attributes

³ This is the list of supported options, specific EKU is taken over from Certificate application.

		in compliance with ETSI TS 119 495
	rolesOfPSP	list of PSP roles
	RoleOfPSP	for every authorized role the two of OID and abbreviated name of the role:
	.roleOfPspOid	OID of PSP role in compliance with ETSI TS 119 495
	.roleOfPspName	PSP role abbreviated name in compliance with ETSI TS 119 495
	nCAName	full NCA name in English
	nCAId	NCA identifier in the format cc-registrarID <ul style="list-style-type: none"> ▪ cc = country code compliant with ISO 3166, same as countryName attribute; ▪ registrarID = abbreviated name of NCA, same entry and format for NCA identification in subject.organizationIdentifier attribute

* YY – the last two digits of the year the Authority’s certificate is issued.

** It is a selected sub-string from the subject field’s serialNumber attribute created by the Authority (see Table 5).

*** Position and content of PSD2 attributes can vary depending on update of relevant legislation/standards, but will always comply with obligatory qualified certificate profile for electronic seal issued to legal persons.

7.1.3 Algorithm object identifiers

The algorithms used in providing trust services are in compliance with the relevant technical standards.

7.1.4 Name forms

Name forms included in the Authority-issued Certificates comply with RFC 5280. The provisions of 3.1 also apply.

7.1.5 Name constraints

Not applicable to Certificates issued to end users.

7.1.6 Certificate policy object identifier

První certifikační autorita, a.s., inserts in the Certificates issued the following certification policy object identifiers:

- OID of the certification policy under which I.CA issues Certificates;
- OID of the relevant certification policy defined by ETSI EN 319 411-2, or ČSN ETSI EN 319 411-2 as applicable, for a certificate issued to an Organization with regard to the storing of the private key and declaring that the Certificate is in compliance with eIDAS.

7.1.7 Usage of Policy Constraints extension

Not applicable to Certificates issued to end users.

7.1.8 Policy qualifier syntax and semantics

See Certificate extensions in 7.1.2 above.

7.1.9 Processing semantics for the critical certificate policies extension

Not applicable to this document – not classified as critical.

7.2 CRL profile

Table 7 – CRL profile⁴

Field	Content
version	v2(0x1)
signatureAlgorithm	sha256withRSAEncryption
issuer	issuer of the CRL (the Authority)
thisUpdate	date and time when the CRL was released (UTC)
nextUpdate	date and expected time when the next CRL will be released (UTC)
revokedCertificates	list of revoked certificates
userCertificate	revoked certificate's serial number

⁴ I.CA reserves the right to modify the set of the fields and the content of the CRL as may be required by updated ETSI standards or third parties (Microsoft, for example).

revocationDate	certificate revocation date and time
crlEntryExtensions	list attribute extensions – see Table 8
crlExtensions	CRL extensions – see Table 8
signature	electronic sign/seal of CRL issuer (Authority)

7.2.1 Version number(s)

Certificate revocation lists are issued pursuant to X.509, version 2.

7.2.2 CRL and CRL entry extensions

Table 8 – CRL Extension³

Extension	Content	Comments
crlEntryExtensions		
CRLReason	certificate revocation reason as the certificateHold reason is not admissible, I.CA does not use it	non-critical, optional
crlExtensions		
authorityKeyIdentifier		
keyIdentifier	hash of the CRL issuer's (Authority's) public key	non-critical
CRLNumber	unique number of the CRL to be released	non-critical

7.3 OCSP profile

Both the OCSP request profile and the OCSP response profile are in accordance with RFC 6960 and RFC 5019.

OCSP responses are of the BasicOCSPResponse type and contain all mandatory fields. An optional revocationReason field is included for revoked certificates. The unAuthorized response is given for any certificate not issued by the relevant CA. Http only is used as the transmission protocol.

See the relevant certification practice statement for more detail.

7.3.1 Version number(s)

Version 1 is specified in a certificate status request and response using the OCSP protocol.

7.3.2 OCSP extensions

The specific extensions for OCSP protocol certificate status requests and responses are given in the relevant certification practice statement.

8 CONFORMITY ASSESSMENTS AND OTHER ASSESSMENTS

8.1 Frequency or circumstances of assessment

The assessment interval and circumstances are defined in trust services legislation and the technical standards referred to therein regulating the assessment procedure.

The Microsoft Trusted Root Program assessment interval and circumstances are strictly defined by Microsoft, and the audit period is no longer than one year.

The intervals for other assessments are specified in the relevant technical standards.

8.2 Identity/qualifications of assessor

The identity (accredited conformity assessment entity) and the qualification of the assessor carrying out the assessment pursuant to trust services legislation are defined in this legislation and the technical standards referred to therein.

The identity (accredited conformity assessment entity) and the qualification of the assessor carrying out assessment defined by Microsoft Trusted Root Program are described in ETSI EN 319 403.

The qualification of the assessor carrying out other assessments is specified in the relevant technical standards.

8.3 Assessor's relationship to assessed entity

Internal assessor is not subordinate to the organizational unit which provides the operation of trust services.

External assessor is an assessor without any relationship to I.CA through property or person.

8.4 Topics covered by assessment

The areas to be assessed in an assessment required under trust services legislation are those as specified in that legislation.

The areas to be assessed in an assessment required for Microsoft Trusted Root Program are strictly given by requirements of Microsoft Company.

The areas to be assessed in any other assessment are specified in the technical standards under which the assessment is made.

8.5 Actions taken as a result of deficiency

The findings in any type of assessment are communicated to the I.CA security manager, who makes sure that any defect identified is remedied. If defects are identified that critically prevent the provision of a specific trust service, I.CA must suspend that service until the defects are remedied.

8.6 Communication of results

Assessment result notification is subject to the requirements of rust services legislation and the relevant technical standards; the notification of Microsoft Trusted Root Program assessment results is subject to Microsoft requirements.

Assessments results are notified as a written report handed over by the assessor to CEO and the security manager of I.CA.

The I.CA security manager calls a security committee meeting as soon as possible and communicates the final report at the meeting; company management members must attend the meeting.

9 OTHER BUSINESS AND LEGAL MATTERS

9.1 Fees

9.1.1 Certificate issuance or renewal fees

The fees for Certificate issuance are given in the current price list, which is available on the web information address of I.CA or in the contract if there is a contract between I.CA and the Organization. Certificate renewal is not provided.

9.1.2 Certificate access fees

No fee is charged by I.CA for electronic access to the Certificates issued under this CP.

9.1.3 Revocation or status information access fees

No fee is charged by I.CA for electronic access to revocation information (CRL) and status information about the Certificates issued by the Authority.

9.1.4 Fees for other services

Not applicable to this document.

9.1.5 Refund policy

Not applicable to this document.

9.2 Financial responsibility

9.2.1 Insurance coverage

První certifikační autorita, a.s., represents it holds a valid business risk insurance policy that covers financial damage.

První certifikační autorita, a.s., has drawn an employee liability insurance policy for each employee, with a scope of coverage as determined by the company's board of directors.

9.2.2 Other assets

První certifikační autorita, a.s., represents it has available financial resources and other financial assurances sufficient for providing trust services given the risk of a liability-for-damage claim.

See the Annual Report of První certifikační autorita, a.s., published in Commercial Register for detailed information on the company's assets.

9.2.3 Insurance or warranty coverage for end-entities

Not applicable to this document.

9.3 Confidentiality of business information

9.3.1 Scope of confidential information

Confidential information of I.CA covers any information other than public information and other than that published in the manner pursuant to 2.2, including:

- All private keys, which are employed in providing trust services;
- Business information of I.CA;
- Any internal information and documentation;
- Any personal data.

9.3.2 Information not within the scope of confidential information

Public information is only the information designated as public and that published in the manner pursuant to 2.2.

9.3.3 Responsibility to protect confidential information

No I.CA employee who comes in contact with confidential information may disclose the same to a third party without consent of CEO of I.CA.

9.4 Privacy of personal information

9.4.1 Privacy plan

I.CA protects personal data and other non-public information in accordance with the relevant legislation, that is ZOOÚ and GDPR in particular.

9.4.2 Information treated as private

Any personal data subject to protection under relevant legislation is treated as private.

I.CA employees or the entities defined by relevant legislation that come into contact with personal data must maintain confidentiality of these data and the security controls the disclosure of which would put the security of these data at risk. The confidentiality duty survives the termination of employment or other similar relationship, or the completion of pertinent work.

9.4.3 Information not deemed private

Any information outside the scope of relevant legislation is not considered personal data.

9.4.4 Responsibility to protect private information

CEO of I.CA is responsible for the protection of personal data.

9.4.5 Notice and consent to use private information

I.CA deals with the notifying of personal data use and consents to personal data processing in accordance with the relevant legislation.

9.4.6 Disclosure pursuant to judicial or administrative process

I.CA discloses personal data for judicial or administrative purpose in accordance with the relevant legislation.

9.4.7 Other Information disclosure circumstances

I.CA provides access to personal data strictly as regulated in relevant legislation.

9.5 Intellectual property rights

This CP, all related documents, the website content and the procedures facilitating the operation of the systems providing trust services are copyrighted by První certifikační autorita, a.s., and are important know-how thereof.

9.6 Representations and warranties

9.6.1 CA Representations and warranties

I.CA warrants that:

- It will use the certification authorities' private keys solely for issuing Certificates to end users (except I.CA root certification authority), releasing certificate revocation lists and issuing OCSP responder certificates;
- It will use the private keys of certification authorities' OCSP responders solely in the processes of providing responses to certificate status requests;
- Certificates issued to end users meet the statutory trust services requirements and those of the relevant technical standards;
- It will revoke any issued Certificate if the revocation request is submitted in the manner defined in this CP.

All warranties and the performance resulting therefrom may only be recognized on condition that:

- The Certificate's subscriber did not violate any obligation arising from Service contract and this CP;
- The relying party did not violate any obligation arising from this CP.

The subscriber of a Certificate issued under this CP must always make his warranty claim with the RA which handled his application for that particular Certificate.

I.CA represents and warrants, vis-à-vis Certificate's subscribers and all relying parties, that I.CA will observe its CPs and CPSs in issuing these Certificates and administering the same throughout their periods of validity.

The warranties include:

- Checking the right to apply for the Certificate;
- Verifying the information given in the Certificate application, checking due completion of the items in the Certificate application (PKCS#10 format) and checking the identity;
- Ensuring that the Service contract meets the requirements of relevant legislation;
- Ensuring that certificate status information repository is maintained 24 hours a day and 7 days a week;
- Ensuring that the Certificate may be revoked for reasons specified in trust services legislation and this CP.

9.6.2 RA representations and warranties

The designated RA:

- Assumes the obligation that the services the RA provides are correct;
- Does not accept the application unless the RA validates all the application items (except those not subject to validation), or the person representing Organization or the Certificate's subscriber provides the required data or is authorized to submit the application;
- Is responsible for passing a hand-delivered Certificate revocation request to an Authority office in due time for the office to handle the application;
- Is responsible for handling objections and complaints.

9.6.3 Subscriber representations and warranties

The subscriber representations and warranties are stated in the contract between I.CA and the Certificate's subscriber.

9.6.4 Relying parties representations and warranties

Relying parties observe this CP.

9.6.5 Representations and warranties of other participants

Not applicable to this document.

9.7 Disclaimers of warranties

První certifikační autorita, a.s., only provides the warranties as given in 9.6.

9.8 Limitations of liability

První certifikační autorita, a.s., is not responsible for any damage suffered by relying parties where the relying party breaches its obligations under trust services legislation and particular CP. První certifikační autorita, a.s., is also not responsible for any damage resulting from breach of obligations of I.CA as a result of force majeure.

9.9 Indemnities

Applicable to the provision of trust services are the relevant provisions of current legislation regulating provider–consumer relations and the warranties agreed between První certifikační autorita, a.s., and the applicant for the Service. The contract must not be in conflict with current legislation and must always take an electronic or printed form.

První certifikační autorita, a.s.:

- Undertakes to discharge all the obligations defined in relevant legislation (including the trust services legislation) and those in the relevant policies;
- Gives the aforesaid warranties throughout the term of the contract of trust services;
- Agrees that the application software suppliers with a valid contract with První certifikační autorita, a.s., for the distribution of the root certificate assume no obligation or liability, except for where damage or loss is directly attributable to the software of that supplier.

První certifikační autorita, a.s., **is not responsible for:**

- Any defect in the services rendered which is due to the Certificate subscriber's incorrect or unauthorized use of the services rendered under the Service contract, particularly for any use contrary to the terms and conditions specified in this CP, and for any defect due to force majeure, including a temporary telecommunication connection failure;
- Any damage resulting from using the Certificate after submitting the request for that certificate's revocation if První certifikační autorita, a.s., meets the defined time limit for publishing the revoked Certificate on the list of revoked certificates (CRL or OCSP).

Claims and complaints may be submitted by:

- E-mail to reklamace@ica.cz;
- Message to data box of I.CA;
- Registered post letter to the registered office of the company;
- Hand at the registered office of the company.

The party making the claim or complaint (subscriber of the Certificate or the relying party) must provide:

- Description of the defect that is as accurate as possible;
- Serial number of the product complained about;
- Suggestion how the claim/complaint should be resolved.

I.CA will decide the claim/complaint within three business days of receiving it. The decision will be communicated to the party making the claim/complaint by e-mail, data box message or registered post letter unless the parties agree to a different method.

The claim/complaint, including the defect, will be dealt with without undue delay, within 30 days of the date of the claim/complaint unless the parties agree otherwise.

The subscriber will be provided with a new Certificate free of charge if:

- There is reasonable suspicion that the certification authority's private key has been compromised;
- The management of I.CA decide so taking account of the circumstances of the case;
- The Authority finds out, in the Certificate application acceptance procedure, that a different Certificate with a duplicate public key exists.

Any other possible compensation is based on the relevant legislation and the amount of damages may be determined by court.

9.10 Term and termination

9.10.1 Term

This CP takes effect on the date specified in chapter 10 and remains in effect no shorter than the expiration of the last Certificate issued under this CP.

9.10.2 Termination

CEO of První certifikační autorita, a.s., is the sole person authorized to approve the termination of this CP.

9.10.3 Effect of termination and survival

The obligations of I.CA arising from this CP survive the expiration thereof until the expiration of the last Certificate issued under this CP.

9.11 Individual notices and communications with participants

For individual notices and communication with the participating parties, I.CA may use the e-mail and postal addresses and the phone numbers provided by the participating parties, personal meetings and other channels.

Communication with I.CA is also possible through the channels specified on the web information address.

9.12 Amendments

9.12.1 Amending procedure

This procedure is a controlled process described in an internal document.

9.12.2 Notification mechanism and period

The release of a new CP version is always notified as published information.

9.12.3 Circumstances under which OID must be changed

CP's OID must be changed when the changes of CP will materially reduce the assurance that the Certificate is trusted and will have a significant effect on the acceptability of the Certificate in compliance with trust services legislation.

Any change to this CP results in a new version of the document.

9.13 Disputes resolution provisions

If the Certificate's subscriber or the relying party disagrees with the proposed way of resolving the dispute, they may use the following levels of appeal:

- RA employee in charge;
- I.CA employee in charge (electronic or written filing is required);
- CEO of I.CA (electronic or written filing is required).

This procedure provides the dissenting party with an opportunity to assert its opinion more swiftly than before a court.

9.14 Governing law

The business of První certifikační autorita, a.s., is governed by the laws of the Czech Republic.

9.15 Compliance with applicable law

The system of providing trust services is in compliance with the statutory requirements of the Czech Republic and all relevant international standards.

9.16 Miscellaneous provisions

9.16.1 Entire agreement

Not applicable to this document.

9.16.2 Assignment

Not applicable to this document.

9.16.3 Severability

If a court or a public authority with jurisdiction over the activities covered by this CP establishes that the implementation of a mandatory requirement is unlawful, the scope of that

requirement will be so limited as to ensure the requirement is lawful and complies with relevant legislation.

9.16.4 Enforcement (attorneys' fees and waiver of rights)

Not applicable to this document.

9.16.5 Force Majeure

První certifikační autorita, a.s., is not responsible for breaching its obligations arising from Service contract if it is the result of force majeure, such as major natural disaster, major disaster caused by human activity, strike or civil unrest always followed by the declaration of a situation of emergency, or the declaration of threat to state or a state of war, or communication failure.

9.17 Other provisions

Not applicable to this document.

10 FINAL PROVISIONS

This certification policy issued by První certifikační autorita, a.s., takes force and effect on date mentioned above in Table1.