První certifikační autorita, s.r.o.



Certification Policy

for Issuing Qualified Certificates for Electronic
Signatures According to the Legislation
of the Slovak Republic

(RSA Algorithm)

The Certification Policy for Issuing Qualified Certificates for Electronic Signatures According to the Legislation of the Slovak Republic (RSA Algorithm) is a public document, which is the property of První certifikační autorita, a.s., and has been prepared as integral part of comprehensive security documentation. No part of this document may be reproduced without the written consent of the copyright holder.

Version 1.00

CONTENT

1	Intro	duction		10	
	1.1	Overvi	ew	11	
	1.2	Docum	nent name and identification	12	
	1.3	PKI Pa	articipants	12	
		1.3.1	Certification authorities	12	
		1.3.2	Registration authorities	12	
		1.3.3	Subscribers	12	
		1.3.4	Relying parties	12	
		1.3.5	Other participants	13	
	1.4	Certific	cate usage	13	
		1.4.1	Appropriate certificate uses	13	
		1.4.2	Prohibited certificate uses	13	
	1.5	Policy	administration	13	
		1.5.1	Organization administering the document	13	
		1.5.2	Contact person	13	
		1.5.3	Person determining CPS suitability for the policy	13	
		1.5.4	CPS approval procedures	13	
	1.6	Definiti	ions and acronyms	13	
2	Publication and repository responsibilities				
	2.1	Repos	18		
	2.2	Publication of certification information			
	2.3	Time o	or frequency of publication	19	
	2.4	Access	s controls on repositories	19	
3	lden	tification	and authentication	20	
	3.1	Namin	g	20	
		3.1.1	Types of names	20	
		3.1.2	Need for names to be meaningful	20	
		3.1.3	Anonymity or pseudonymity of subscribers	20	
		3.1.4	Rules for interpreting various name forms	20	
		3.1.5	Uniqueness of names	20	
		3.1.6	Recognition, authentication, and role of trademarks	20	
	3.2	Initial i	dentity validation	20	
		3.2.1	Method to prove possession of private key	20	
		3.2.2	Authentication of organization identity	21	

		3.2.3	Authentication of individual identity	21
		3.2.4	Non-verified subscriber information	23
		3.2.5	Validation of authority	24
		3.2.6	Criteria for interoperation	24
	3.3	Identifi	cation and authentication for re-key requests	24
		3.3.1	Identification and authentication for routine re-key	24
		3.3.2	Identification and authentication for re-key after revocation	24
	3.4	Identifi	cation and authentication for revocation request	24
4	Cert	ificate lif	e cycle operational requirements	26
	4.1	Certific	cate application	26
		4.1.1	Who can submit a certificate application	26
		4.1.2	Enrollment process and responsibilities	26
	4.2	Certific	ate application processing	27
		4.2.1	Performing identification and authentication functions	27
		4.2.2	Approval or rejection of certificate applications	27
		4.2.3	Time to process certificate applications	27
	4.3	Certificate Issuance		
		4.3.1	CA actions during certificate issuance	27
		4.3.2	Notification to subscriber by the CA of issuance of certificate	28
	4.4	Certific	cate acceptance	28
		4.4.1	Conduct constituting certificate acceptance	28
		4.4.2	Publication of the certificate by the CA	28
		4.4.3	Notification of certificate issuance by the CA to other entities	28
	4.5	Key pa	ir and certificate usage	29
		4.5.1	Subscriber private key and certificate usage	29
		4.5.2	Relying party public key and certificate usage	29
	4.6	Certific	cate renewal	29
		4.6.1	Circumstance for certificate renewal	29
		4.6.2	Who may request renewal	29
		4.6.3	Processing certificate renewal requests	30
		4.6.4	Notification of new certificate issuance to subscriber	30
		4.6.5	Conduct constituting acceptance of a renewal certificate	30
		4.6.6	Publication of the renewal certificate by the CA	30
		4.6.7	Notification of certificate issuance by the CA to other entities	30
	4.7	Certific	cate re-key	30
		4.7.1	Circumstance for certificate re-key	30

	4.7.2	Who may request certification of a new public key	30		
	4.7.3	Processing certificate re-keying requests	31		
	4.7.4	Notification of new certificate issuance to subscriber	31		
	4.7.5	Conduct constituting acceptance of a re-keyed certificate	31		
	4.7.6	Publication of the re-keyed certificate by the CA	31		
	4.7.7	Notification of certificate issuance by the CA to other entities	31		
4.8	Certifica	ate modification	31		
	4.8.1	Circumstance for certificate modification	31		
	4.8.2	Who may request certificate modification	31		
	4.8.3	Processing certificate modification requests	32		
	4.8.4	Notification of new certificate issuance to subscriber	32		
	4.8.5	Conduct constituting acceptance of modified certificate	32		
	4.8.6	Publication of the modified certificate by the CA	32		
	4.8.7	Notification of certificate issuance by the CA to other entities	32		
4.9	Certificate revocation and suspension				
	4.9.1	Circumstances for revocation	32		
	4.9.2	Who can request revocation	32		
	4.9.3	Procedure for revocation request	33		
	4.9.4	Revocation request grace period	34		
	4.9.5	Time within which CA must process the revocation request	35		
	4.9.6	Revocation checking requirement for relying parties	35		
	4.9.7	CRL issuance frequency	35		
	4.9.8	Maximum latency for CRLs	35		
	4.9.9	On-line revocation/status checking availability	35		
	4.9.10	On-line revocation checking requirements	35		
	4.9.11	Other forms of revocation advertisements available	35		
	4.9.12	Special requirements re key compromise	35		
	4.9.13	Circumstances for suspension	35		
	4.9.14	Who can request suspension	35		
	4.9.15	Procedure for suspension request	36		
	4.9.16	Limits on suspension period	36		
4.10	Certifica	ate status services	36		
	4.10.1	Operational characteristics	36		
	4.10.2	Service availability	36		
	4.10.3	Optional features	36		
4.11	End of s	subscription	36		

	4.12	Key escrow and recovery		
		4.12.1	Key escrow and recovery policy and practices	36
		4.12.2	Session key encapsulation and recovery policy and practices	37
5	Facil	ity, mana	agement, and operational controls	38
	5.1	Physica	al controls	38
		5.1.1	Site location and construction	38
		5.1.2	Physical access	38
		5.1.3	Power and air conditioning	38
		5.1.4	Water exposures	38
		5.1.5	Fire prevention and protection	39
		5.1.6	Media storage	39
		5.1.7	Waste disposal	39
		5.1.8	Off-site backup	39
	5.2	Proced	ural controls	39
		5.2.1	Trusted roles	39
		5.2.2	Number of persons required per task	39
		5.2.3	Identification and authentication for each role	40
		5.2.4	Roles requiring separation of duties	40
	5.3	Person	nel controls	40
		5.3.1	Qualification, experience, and clearance requirements	40
		5.3.2	Background check procedures	40
		5.3.3	Training requirements	41
		5.3.4	Retraining frequency and requirements	41
		5.3.5	Job rotation frequency and sequence	41
		5.3.6	Sanctions for unauthorized actions	41
		5.3.7	Independent contractor requirements	41
		5.3.8	Documentation supplied to personnel	41
	5.4	Audit lo	ogging procedures	42
		5.4.1	Types of events recorded	42
		5.4.2	Frequency of processing log	42
		5.4.3	Retention period for audit log	42
		5.4.4	Protection of audit log	42
		5.4.5	Audit log backup procedures	43
		5.4.6	Audit collection system (internal vs. external)	43
		5.4.7	Notification to event-causing subject	43
		5.4.8	Vulnerability assessments	43

	5.5	Record	ds archival	43			
		5.5.1	Types of records archived	43			
		5.5.2	Retention period for archive	43			
		5.5.3	Protection of archive	43			
		5.5.4	Archive backup procedures	44			
		5.5.5	Requirements for time-stamping of records	44			
		5.5.6	Archive collection system (internal or external)	44			
		5.5.7	Procedures to obtain and verify archive information	44			
	5.6	Key ch	angeover	44			
	5.7	Compr	omise and disaster recovery	45			
		5.7.1	Incident and compromise handling procedures	45			
		5.7.2	Computing resources, software, and/or data are corrupted	45			
		5.7.3	Entity private key compromise procedures	45			
		5.7.4	Business continuity capabilities after a disaster	45			
	5.8	CA or I	RA termination	45			
6	Tecl	Technical security controls					
	6.1	Key pa	ir generation and installation	47			
		6.1.1	Key pair generation	47			
		6.1.2	Private key delivery to subscriber	47			
		6.1.3	Public key delivery to certificate issuer	47			
		6.1.4	CA public key delivery to relying parties	47			
		6.1.5	Key sizes	47			
		6.1.6	Public key parameters generation and quality checking	48			
		6.1.7	Key usage purposes (as per X.509 v3 key usage extension)	48			
	6.2	Private	key protection and cryptographic module engineering controls	48			
		6.2.1	Cryptographic module standards and controls	48			
		6.2.2	Private key (n out of m) multi-person control	48			
		6.2.3	Private key escrow	48			
		6.2.4	Private key backup	48			
		6.2.5	Private key archival	49			
		6.2.6	Private key transfer into or from a cryptographic module	49			
		6.2.7	Private key storage on cryptographic module	49			
		6.2.8	Method of activating private key	49			
		6.2.9	Method of deactivating private key	49			
		6.2.10	Method of destroying private key	50			
		6.2.11	Cryptographic module rating	50			

	6.3	Other a	aspects of key pair management	50		
		6.3.1	Public key archival	50		
		6.3.2	Certificate operational periods and key pair usage periods	50		
	6.4	Activat	tion data	51		
		6.4.1	Activation data generation and installation	51		
		6.4.2	Activation data protection	51		
		6.4.3	Other aspects of activation data	51		
	6.5	Compu	uter security controls	51		
		6.5.1	Specific computer security technical requirements	51		
		6.5.2	Computer security rating	51		
	6.6	Life cy	cle technical controls	54		
		6.6.1	System development controls	54		
		6.6.2	Security management controls	54		
		6.6.3	Life cycle security controls	54		
	6.7	Netwo	rk security controls	54		
	6.8	Time-s	stamping	55		
7	Cert	ertificate, CRL and OCSP profiles				
	7.1	Certificate profile				
		7.1.1	Version number(s)	58		
		7.1.2	Certificate extensions	58		
		7.1.3	Algorithm object identifiers	61		
		7.1.4	Name forms	61		
		7.1.5	Name constraints	61		
		7.1.6	Certificate policy object identifier	61		
		7.1.7	Usage of Policy Constraints extension	61		
		7.1.8	Policy qualifier syntax and semantics	62		
		7.1.9	Processing semantics for the critical certificate policies extension	62		
	7.2	CRL p	rofile	62		
		7.2.1	Version number(s)	62		
		7.2.2	CRL and CRL entry extensions	62		
	7.3	OCSP	profile	63		
		7.3.1	Version number(s)	63		
		7.3.2	OCSP extensions	63		
8	Con	formity a	assessments and other assessments	64		
	8.1	Freque	ency or circumstances of assessment	64		
	8.2	Identity	y/qualifications of assessor	64		

	8.3	Assess	sor's relationship to assessed entity	64
	8.4	Topics	covered by assessment	64
	8.5	Actions	s taken as a result of deficiency	64
	8.6	Comm	unication of results	65
9	Othe	er busine	ess and legal matters	66
	9.1	Fees		66
		9.1.1	Certificate issuance or renewal fees	66
		9.1.2	Certificate access fees	66
		9.1.3	Revocation or status information access fees	66
		9.1.4	Fees for other services	66
		9.1.5	Refund policy	66
	9.2	Financ	ial responsibility	66
		9.2.1	Insurance coverage	66
		9.2.2	Other assets	66
		9.2.3	Insurance or warranty coverage for end-entities	67
	9.3	Confid	entiality of business information	67
		9.3.1	Scope of confidential information	67
		9.3.2	Information not within the scope of confidential information	67
		9.3.3	Responsibility to protect confidential information	67
	9.4	Privac	y of personal information	67
		9.4.1	Privacy plan	67
		9.4.2	Information treated as private	67
		9.4.3	Information not deemed private	68
		9.4.4	Responsibility to protect private information	68
		9.4.5	Notice and consent to use private information	68
		9.4.6	Disclosure pursuant to judicial or administrative process	68
		9.4.7	Other Information disclosure circumstances	68
	9.5	Intelled	ctual property rights	68
	9.6	Repres	sentations and warranties	68
		9.6.1	CA Representations and warranties	68
		9.6.2	RA representations and warranties	69
		9.6.3	Subscriber representations and warranties	69
		9.6.4	Relying parties representations and warranties	69
		9.6.5	Representations and warranties of other participants	69
	9.7	Disclai	mers of warranties	70
	9.8	Limitat	ions of liability	70

	9.9	Indemnities		70
	9.10	Term a	and termination	71
		9.10.1	Term	71
		9.10.2	Termination	71
		9.10.3	Effect of termination and survival	71
	9.11	Individu	ual notices and communications with participants	71
	9.12	Amend	lments	72
		9.12.1	Amending procedure	72
		9.12.2	Notification mechanism and period	72
		9.12.3	Circumstances under which OID must be changed	72
	9.13	B Disputes resolution provisions		72
	9.14	Governing law		
	9.15	Compliance with applicable law		
	9.16	Miscella	aneous provisions	72
		9.16.1	Entire agreement	72
		9.16.2	Assignment	73
		9.16.3	Severability	73
		9.16.4	Enforcement (attorneys' fees and waiver of rights)	73
		9.16.5	Force Majeure	73
	9.17	Other p	provisions	73
10	Final	provisio	ons	74

Table 1 – Document history

Version	Date of Release	Approved by	Comments
1.00	15 October 2022	Ing. Ctirad Fischer, Managing Director of První certifikační autorita, s.r.o.	

Version 1.00 Page 9 of 74

1 INTRODUCTION

První certifikační autorita, s.r.o., (also as I.CA SK) is the subsidiary company of První certifikační autorita, a.s., (also as I.CA) and I.CA is one hundred percent owner of I.CA SK. I.CA SK is the qualified service provider and I.CA on the basis of contractual relationship ensures:

- Complete technical infrastructure necessary to ensure providing qualified trust services by I.CA SK;
- Creation and management of documentation related to trust services provided by I.CA SK.
- Management of lists related to trust services provided by I.CA SK (list of issued certificates, CRLs),
- Operation of the on-line revocation/status checking service (OCSP) of the certificates issued by I.CA SK;
- Permanent cooperation in the provision of trust service;
- Methodological assistance.

I.CA SK operation is governed by internal and external documents (policies, directives) of I.CA unless otherwise stated.

This document determines the principles applied by I.CA SK, a qualified provider of trust services, in providing qualified trust service of issuing qualified certificates for electronic signatures according to the legislation of the Slovak Republic (also as the Service or the Certificate) to natural persons. The RSA algorithm is used for the Service provided under this certification policy (also as the CP).

The statutory requirements in respect of the Service are defined in:

- Regulation (EU) no 910/2014 of the European Parliament and of the Council on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC (eIDAS);
- Act of the Slovak Republic No. 272/2016 Coll., on Trust Services for Electronic Transactions in the Internal Market and on Amendment and Supplementing of certain Acts (Trust Services Act);
- Legislation concerning personal data protection in compliance with Regulation (EU) no 2016/679 of the European Parliament and of the Council on the protection of natural persons with regard to the processing of personal data and on the free movement of such data, and repealing Directive 95/46/EC (General Data Protection Regulation).

The Service is provided to all end users on the basis of a contract. I.CA SK imposes no restrictions on potential end users, and the provision of the Service is non-discriminatory and the Service is also available to the disabled.

Note: Any reference to technical standard, norm or legislation is always a reference to that technical standard, norm or legislation or to replacing technical standard, norm or legislation. If this document is in conflict with any technical standard, norm or legislation that replaces the current technical standard, norm or legislation, a new version will be released.

Version 1.00 Page 10 of 74

1.1 Overview

The document Certification Policy for Issuing Qualified Certificates for Electronic Signatures According to the Legislation of the Slovak Republic (RSA Algorithm) prepared by I.CA on behalf of I.CA SK deals with the issues related to life cycle processes of Certificates and follows a structure matching the scheme of valid RFC 3647 standard while taking account of valid technical and other standards and norms of the European Union and the laws of the Slovak Republic pertinent to this sphere (therefore, each chapter is preserved in his document even if it is irrelevant to this sphere). The document is divided into nine basic chapters and these are briefly introduced in the following list:

- Chapter 1 identifies this document with the allocated unique identifier, generally describes the entities and individuals taking part in the provision of this Service, and defines the acceptable use of the Certificates available to be issued;
- Chapter 2 deals with the responsibility for the publication and information or documents;
- Chapter 3 describes the processes of identification and authentication of an applicant for the issuance or revocation of a Certificate, and defines the types and contents of the names used in Certificates;
- Chapter 4 defines life cycle processes of Certificates, i.e., Certificate issuance application, the issuance of the Certificate, Certificate revocation request, the revocation of the Certificate, the services related to checking of Certification status, termination of the provision of the Service, etc.:
- Chapter 5 covers physical, procedural and personal security, including the definition of the set of events subject to logging, the keeping of these records and responses to emergency and compromising situations;
- Chapter 6 focuses on the technical security of the type of generating public and private keys, protection of private keys, including the computer and network protection:
- Chapter 7 defines the profile of issued Certificates and CRL;
- Chapter 8 focuses on assessing the Service delivered;
- Chapter 9 deals with commercial and legal aspects.

More detail on the fulfillment of fields and extensions of Certificates issued under this CP and on Certificate administration may be included in the relevant certification practice statement (also as the CPS).

Note: This is English translation of CP; Czech version always takes precedence.

Version 1.00 Page 11 of 74

1.2 Document name and identification

Document's title: Certification Policy for Issuing Qualified Certificates for

Electronic Signatures According to the Legislation of the

Slovak Republic (RSA Algorithm), version 1.00

Policy OID: 1.3.6.1.4.1.23624.10.1.190.1.0

1.3 PKI Participants

1.3.1 Certification authorities

The root certification authority of I.CA issued a certificate to a subordinate certification authority (also as the Authority) operated by I.CA on behalf of I.CA SK, in a two-tier certification authority structure, in accordance with relevant legislation and technical and other standards. This Authority issues Certificates under this CP and certificates for its own OCSP responder.

1.3.2 Registration authorities

The Service is provided through registration authorities (stationary or mobile), which are either public (providing services for the general public) or client (providing services for their customers). These registration authorities:

- Accept applications for the services listed in this CP (Certificate issuance applications, in particular), arrange the handover of Certificates and certificate revocation lists, provide required information, handle complaints, etc.;
- Are authorized, for urgent operational or technical reasons, to suspend, in whole or in part, the performance of their activities;
- Are authorized to conclude Service contracts on behalf of I.CA SK;
- Are authorized to charge for I.CA SK services provided through RA unless otherwise agreed in a contract;
- If contracted RA, exercise similar duties and responsibilities on behalf of I.CA SK as the RA proper, under a written contract concluded between I.CA SK and the operator of the contracted RA.

1.3.3 Subscribers

Subscriber of a Certificate may be a natural person identified in the Certificate as the owner of the private key connected with the public key specified in the Certificate.

1.3.4 Relying parties

Any entity relying in their operations on the Certificates issued under this CP is a relying party.

Version 1.00 Page 12 of 74

1.3.5 Other participants

Other participating parties are investigative, prosecuting and adjudicating bodies, supervisory bodies and other bodies recognized as such by trust services legislation.

1.4 Certificate usage

1.4.1 Appropriate certificate uses

Certificates issued under this CP may only be used in electronic signature verification processes in accordance with trust services legislation.

1.4.2 Prohibited certificate uses

Certificates issued under this CP may not be used contrary to the acceptable use described in 1.4.1 or contrary to law.

1.5 Policy administration

1.5.1 Organization administering the document

This CP is administered by I.CA SK, corresponding CPS is administered by I.CA.

1.5.2 Contact person

The contact person in respect of this CP and corresponding CPS is specified on the web page – see 2.2.

1.5.3 Person determining CPS suitability for the policy

CEO of I.CA and managing director of I.CA SK are jointly responsible for making decisions about compliance of the procedures of I.CA or I.CA SK as set out in CPS with this CP.

1.5.4 CPS approval procedures

If it is necessary to make changes to a CPS to create a new version thereof, the CEO of I.CA appoints a person authorized to perform such changes. No new CPS version may take force unless it has been approved by CEO of I.CA.

1.6 Definitions and acronyms

Table 2 - Definitions

Term		Explanation
Classified	Information	the Czech Republic's Act No. 412/2005 Coll., regulating
Protection Act		classified information protection and security competence, as

Version 1.00 Page 13 of 74

	amended
contracting partner	provider of services contracted by I.CA for certification services or parts thereof – usually, it is a contracted RA
electronic document	digitally encoded document, stored on physical medium, transferred or processed by technical means, in electronic, magnetic or optical form
electronic seal	advanced electronic seal or qualified electronic seal under trust services legislation
electronic sign	electronic sign under trust services legislation
electronic signature	advanced electronic signature or recognized electronic signature or qualified electronic signature under trust services legislation
hash function	transformation which receives, as an input, a string of characters of arbitrary length, and the result is a string of characters of fixed length (hash)
key pair	private key and corresponding public key
Labour Code	the Czech Republic's Act No. 262/2006 Coll., Labour Code, as amended
OCSP responder	server using the OCSP protocol to provide data on public key certificate status
private key	unique data to create electronic signature / seal
public key	unique data to verify electronic signature / seal
qualified certificate for electronic signature or for electronic seal	certificate defined by trust services legislation
qualified signature / seal creation device	device meeting the requirements of eIDAS, annex II, intended for electronic signature / seal creation
relying party	party relying on a certificate in its operations
root CA	certification authority which issues certificates to subordinate certification authorities
sealing person	legal person creating electronic seal
secure cryptographic device	device on which the private key is stored
softcard	software emulation of smartcard for access to private key stored in HSM
subordinate CA	CA issuing certificates to end users
supervisory body	the body supervising qualified trust services providers
trust service / qualified trust service	trust service / qualified trust service defined by eIDAS
trust services legislation	current legislation on trust services
TWINS/DUAL	commercial product of I.CA or I.CA SK consisting of:

Version 1.00 Page 14 of 74

	 qualified certificate for electronic signature;
	non-qualified certificate
two-factor authentication	authentication employing two of three factors — I know something (the password), I have something (a smartcard or a hardware token) or I am something (fingerprint, retina or iris reading)
written contract	text of the contract in electronic or paper form

Table 3 – Acronyms

Table 3 – Acronyms		
Acronym	Explanation	
ARC	Alarm Receiving Centre	
ASCII	American Standard Code for Information Interchange, table containing binary codes of English alphabets, numbers and other common symbols	
BIH	Bureau International de l'Heure – The International Time Bureau	
bit	from English binary digit – a binary system digit – the fundamental and the smallest unit of information in digital technologies	
CA	certification authority	
CEN	European Committee for Standardization, an association of national standardization bodies	
CEO	Chief Executive Officer	
COO	Chief Operating Officer	
СР	certification policy	
CPS	certification practice statement	
CR	Czech Republic	
CRL	Certificate Revocation List – the list of revoked certificates, which are not held as valid any longer	
ČSN	Czech Technical Norm	
DER, PEM	methods of certificate encoding (certificate formats)	
eIDAS	REGULATION (EU) no 910/2014 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 23 July 2014 on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC	
EN	European Standard, a type of ETSI standard	
ESI	Electronic Signatures and Infrastructures	
ETSI	European Telecommunications Standards Institute, a European standardization institute for information and communication technologies	
EU	European Union	

Version 1.00 Page 15 of 74

FAS	Fire Alarm System
FIPS	Federal Information Processing Standard, standards for information technologies for U.S. non-military state organizations
GDPR	Global Data Protection Regulation, REGULATION (EU) 2016/679 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on the protection of natural persons with regard to the processing of personal data and on the free movement of such data, and repealing Directive 95/46/EC (General Data Protection Regulation)
html	Hypertext Markup Language, markup language for creating hypertext documents
http	Hypertext Transfer Protocol, protocol for exchanging html documents
https	Hypertext Transfer Protocol, protocol for secure exchanging of html documents
I.CA	První certifikační autorita, a.s.
I.CA SK	První certifikační autorita, s.r.o.
IAS	Intrusion Alarm System
IEC	International Electrotechnical Commission, the global organization publishing standards for electrical and electronic engineering, communication technologies and related industries
IPS	Intrusion Prevention System
ISMS	Information Security Management System
ISO	International Organization for Standardization, an international organization of national standardization organizations; designation of standards
IT	Information Technology
ITU	International Telecommunication Union
ITU-T	Telecommunication Standardization Sector of ITU
MPSV	Ministry of Labor and Social Affairs of the Czech Republic
NBÚ SR	National Security Authority of the Slovak Republic
OCSP	Online Certificate Status Protocol, the protocol to identify public key certificate status
OID	Object Identifier
OSVČ	self-employed person
PDCA	Plan-Do-Check-Act, Deming cycle, management method for control and continuous improvement
PDS	PKI Disclosure Statement
PKCS	Public Key Cryptography Standards, designation for a group of standards for public key cryptography
PKI	Public Key Infrastructure

Version 1.00 Page 16 of 74

PTC	Publicly-Trusted Certificate
PUB	Publication, FIPS standard designation
QSCD	Qualified Electronic Signature/Seal Creation Device (defined by eIDAS)
RA	registration authority
RFC	Request for Comments, designation for a range of standards and other documents describing web protocols, systems, etc.
RSA	signing and encrypting public key cipher (acronym from the names of the original authors - Rivest, Shamir and Adleman)
sha, SHA	type of hash function
STN	Slovak Technical Norm
TS	Technical Specification, type of ETSI standard
TSA	Time-Stamping Authority
TSS	Time-Stamp Server
TSU	Time-Stamp Unit
UPS	Uninterruptible Power Supply/Source
URI	Uniform Resource Identifier, defined-structure text string for accurate specification of a source of information
UTC	Coordinated Universal Time, the standard adopted on 1 January 1972 for the global coordinated time – Bureau International de l'Heure (BIH) plays the role of the 'official keeper' of the atomic time for the whole world
ZOOÚ	current personal data protection legislation

Version 1.00 Page 17 of 74

2 PUBLICATION AND REPOSITORY RESPONSIBILITIES

2.1 Repositories

I.CA SK sets up and operates repositories of both public and non-public information.

2.2 Publication of certification information

The basic addresses (also as the Information Addresses) for obtaining information about I.CA SK are as follows:

Registered office:

První certifikační autorita, s.r.o.

Galvaniho 19045/19

821 04 Bratislava – mestská časť Ružinov

The Slovak Republic

- Website: http://www.ica.cz;
- Registered offices of the registration authorities.

Electronic address for contact between general public and I.CA is info@ica.cz.

The aforesaid website provides information about:

- Certificates of certification authorities and time-stamping authorities;
- Public certificates the following information is published (and more information can be obtained from the certificate):
 - Certificate number:
 - □ Content of commonName:
 - □ Valid from date (specifying the hour, minute and second);
 - Link to where the certificate can be obtained in the specified format (DER, PEM, TXT);
- Certificate revocation list (CRL) the following information is published (and more information can be obtained from the CRL):
 - □ Date of CRL release;
 - CRL number;
 - □ Link to where the CRL can be obtained in the specified format (DER, PEM, TXT);
- Certification and other policies, practice statements and other public information.

Http and https are the permitted protocols for access to public information. I.CA SK may terminate or suspend access to some information without cause.

Any revocation of certification authority's certificate because of suspected or actual compromise of a given private key will be announced by I.CA or I.SK on its web Information Address and in Hospodářské noviny or Mladá fronta Dnes and Hospodárske noviny or Sme, daily newspapers with national distribution.

Version 1.00 Page 18 of 74

2.3 Time or frequency of publication

I.CA SK publishes information as follows:

- Certification policy after a new version is approved and issued;
- Certification practice statement immediately;
- List of the certificates issued updated immediately after issuing a new certificate to be published;
- Certificate revocation list (CRL) see 4.9.7;
- Information about certification authority's certificate revocation with the reason of revocation immediately;
- Other public information no specific time limit, the general rule is that this information must correspond to the current state of the services provided.

2.4 Access controls on repositories

All public information is made available by I.CA SK free of charge without any restrictions.

Non-public information is available only to authorized employees of I.CA or I.CA SK or the parties specified by the relevant legislation. Access to such information is governed by the rules defined in internal documentation of I.CA.

Version 1.00 Page 19 of 74

3 IDENTIFICATION AND AUTHENTICATION

3.1 Naming

3.1.1 Types of names

All names are construed in accordance with valid technical and other standards.

3.1.2 Need for names to be meaningful

For a Certificate to be issued, all names which can be validated given in the field subject must carry a meaning. See chapter 7 for the attributes supported for this field.

3.1.3 Anonymity or pseudonymity of subscribers

The Certificates issued under this CP support pseudonyms but do not support anonymity.

3.1.4 Rules for interpreting various name forms

The data specified in a Certificate application (format PKCS#10) are transferred to subject field or subjectAlternativeName extension of the Certificate in the form they are specified in the application.

3.1.5 Uniqueness of names

The Authority guarantees that the subject field in a Certificate of specific subscriber is unique.

3.1.6 Recognition, authentication, and role of trademarks

Any Certificate issued under this CP may only contain a trademark with evidenced ownership or license. The Certificate's subscriber bears any consequence resulting from unauthorized use of a trademark.

3.2 Initial identity validation

The entities authorized to apply for a Certificate are listed in 4.1.1. The following chapters specify the rules for the initial validation of the identity of these entities.

3.2.1 Method to prove possession of private key

The ownership of the private key matching the public key in the Certificate application must be proved by submitting the application in the PKCS#10 format. The application is electronically signed with this private key whereby the subscriber provides evidence that he is the owner of the private key when the electronic signature is created.

Version 1.00 Page 20 of 74

3.2.2 Authentication of organization identity

The following must be submitted to authenticate the identity of a legal entity or a government authority (also as the Organization):

- Original or certified copy of the entry in the Commercial Register or in another register specified by law regulation, of a trade license, of a deed of incorporation, or of another document of the same legal force; or
- Printed extract from public registers to be submitted by the applicant or prepared by the RA operator.

This document must contain full business name, identification number (if any), registered office, the name(s) of the person(s) authorized to act on behalf of the legal entity (authorized representatives).

3.2.3 Authentication of individual identity

This chapter describes the identity authentication procedure of the person applying for the Certificate (the Certificate subscriber). Identity authentication can take place in the following ways:

- In person i.e., on-site (the individual applicant arrives at the RA with the required documents); or
- Remotely, i.e., on-line without the physical presence of the individual applicant at the RA.

In case of **on-site** identity authentication procedure, the individual applicant is required to submit two personal documents, a primary and a secondary one, that show the data specified further in this chapter.

Valid personal identity card or passport must be used as the primary personal document for the citizens of the Slovak Republic. Valid passport is the primary personal document for foreigners; citizens of EU member countries may use their valid personal identity card they use in their country as the proof of their identity.

The following data are validated in this document:

- Full civil name;
- Date and place of birth or the birth certification number if shown in the primary document;
- Number of the primary personal document;
- Permanent address (if shown in the primary document).

The secondary document must contain a unique identification, such as birth certification number or personal identity card number, matching it to the primary document and must show at least one of these items:

- Date of birth (or birth certification number if specified);
- Permanent address;
- Photograph of the face.

The secondary personal document data uniquely identifying the Certificate subscriber must be identical to those in the primary personal document.

Version 1.00 Page 21 of 74

If neither the primary nor the secondary personal document shows permanent address, no permanent address may be specified in the Certificate application and the Certificate issued.

For employees an employment certificate with the Organization is also required. This certificate is to be submitted by the Certificate subscriber to RA, but may be provided in the manner defined in the contract concluded between I.CA SK and the Organization. The person authorized to act for the Organization must prove their identity through the primary personal document — see above, or the signature on the certificate of the Certificate subscriber's employment must be officially authenticated. If this person is not defined by law as a person authorized to represent the Organization, this person must also submit his/her officially authenticated power of attorney, signed by the Organization's authorized representative, for representing the Organization.

Employment certificate can be also submitted electronically. Must be .PDF format electronically signed by the person authorized to act for the Organization. Advanced (at least) electronic signature must be based on qualified certificate.

If an agent represents the Certificate subscriber vis-à-vis RA, officially authenticated authorization to act as agent is required.

If the individual who applies for a Certificate for themselves is self-employed person and this is to be specified in the Certificate, the relevant requirements under 3.2.2 apply.

In case of **on-line** identity authentication procedure, the usage of certified ZealiD TRA Service using ZealiD application installed on the applicant's mobile phone or tablet is required for remote verification of the identity of the natural person applying for the Certificate (Certificate subscriber). For this method of identity authentication, a primary personal document is required, which must be a valid personal identity card or passport for the citizens of the Slovak Republic. Valid passport is the primary personal identity document for foreigners; citizens of EU member countries may use their valid personal identity card they use in their country as the proof of their identity. The guide with detailed instructions can be found at the website https://www.ica.cz/on-line-ziskani-certifikatu. The guide informs the applicant (Certificate subscriber) about the process of issuing the Certificate, including information for users about the conditions under which the Certificate can be issued in this way.

The start of on-line authentication of individual identity process varies depending on whether natural person applies for Certificate for himself (so called self-payer) or issuing the Certificate for applicant asks the contractual partner (for example the employer for his employee).

■ Self-payer can use the service after previous pre-registration, which allows to start individual identity authentication via on-line procedure 24 hours after the pre-registration.

Pre-registration is done on I.CA SK webpage, the applicant enters his first name, surname, his cellular phone number (this cellular phone will be used, after installing ZealiD application, for authentication individual of identity), data from personal identification document which will be used for authentication od individual identity (number, expiration date, issuer of the document) and e-mail address. To this e-mail address is immediately sent the link, which is active 24 hours after pre-registration and stays valid next 72 hours. When using the link in this time interval the process of individual identity authentication and issuing the Certificate starts and as part of this process is checked, whether the data entered in the time of pre-registration are the same as the data obtained by ZealiD application. If the result of any check is negative, the process is stopped and the Certificate is not issued.

Version 1.00 Page 22 of 74

I.CA SK reserves the right to call at random the applicant (subscriber) to whom the Certificate was issued (on his phone number provided during pre-registration) and to check the data specified in Certificate application. This random check may be done no later than seven days after the Certificate issuance. In case of doubts about the data match, I.CA has the right to revoke the Certificate and inform the subscriber. Revoking the Certificate does not establish the right of the subscriber to ask for refund the Certificate fee.

Contractual partner first sends to I.CA SK in a trusted way the list of authorized Certificate applicants, who can use on-line individual identity authentication. List of authorized applicants together with their identification data (first name, surname, e-mail address) is included into the I.CA system and to these e-mail addresses is sent unique link allowing to start the process of individual identity authentication and issuing the Certificate. As part of this process is checked, whether the data sent by contractual partner are the same as the data obtained by ZealiD application. If the result of any check is negative, the process is stopped and the Certificate is not issued.

The actual process of on-line authenticating the applicant's identity and issuing the Certificate takes consists of several successive steps and includes:

- Installation of the ZealiD application on the applicant's mobile device (supported platforms are Apple and Android);
- Registration of the mobile device to the system;
- Biometric facial analysis for the required functionality, it is necessary to allow access to the camera when installing the ZealiD application;
- Verification of the personal document its scanning and further biometric comparison of the photograph from the document with the applicant's face is performed;
- Generating Certificate application;
- Signing of the contact on the issuance and use of the Certificate.

If any of the inspections does not end with a positive result, e.g., if the verification of the form does not take place in required quality, the process is terminated and the Certificate is not issued. The condition for the exposure of the Certificate on the list of issued certificates is the signing of the agreement on the issuance and use of the certificate, otherwise the Certificate is revoked.

Restrictions for usage of the on-line identity authentication procedure of the identity of a natural person:

- The applicant cannot be represented by an agent;
- If the Certificate is to state that it is an employee of the Organization, the contractual relationship between I.CA SK and the Organization is required and the contract must state how the confirmation of employment with the Organization is performed.

3.2.4 Non-verified subscriber information

The information not subject to verification is:

- Pseudonym;
- GenerationQualifier.

Version 1.00 Page 23 of 74

3.2.5 Validation of authority

Electronic mail address may be placed in the Certificate extension, that is, in the rfc822Name attribute of the subjectAlternativeName extension, if this has been validated for the given application during the Certificate issuance procedure.

The attribute that the key pair was generated and stored on QSCD device may only be in the Certificate if this has been validated for the given application during the Certificate issuance procedure.

3.2.6 Criteria for interoperation

Any collaboration between I.CA SK and other trust service providers is always based on a contract in writing.

3.3 Identification and authentication for re-key requests

3.3.1 Identification and authentication for routine re-key

The identification and authentication in routine re-key request (subsequent Certificate issuance) are as follows - the application for the issuance of subsequent Certificate in the PKCS#10 structure must also have an electronic signature with the use of a private key matching the public key contained in the valid Certificate which is to be re-keyed.

3.3.2 Identification and authentication for re-key after revocation

This is irrelevant to this document as the service of re-keying after Certificate revocation is not supported. A new Certificate with a new public key needs to be issued. The same requirements as those in the initial identity validation apply.

3.4 Identification and authentication for revocation request

The entities authorized to request for Certificate revocation are listed in 4.9.2.

If the **Certificate revocation request is submitted to RA by hand**, it must be in writing and signed by a person whose identity must be duly authenticated through the primary personal document (see 3.2.3).

The following methods of identification and authentication are permitted for **Certificate revocation request submitted electronically**:

- Using the form on the company's website (and using the Certificate revocation password);
- Using an unsigned electronic message containing the Certificate revocation password and sent to revoke@ica.cz;
- Using a signed electronic message (the electronic signature must be created with the private key belonging to the Certificate to be revoked) and sending it to revoke@ica.cz;
- Using a defined person assigned to represent the Organization in the contractual relationship with I.CA SK.

Version 1.00 Page 24 of 74

If the **Certificate revocation request is sent as a letter** (using the Certificate revocation password), the letter must be sent by registered post to registered office of I.CA SK.

The data required for Certificate revocation request are listed in 4.9.3.

I.CA SK reserves the right to accept also other Certificate revocation identification and authentication procedures, which, however, must not be contrary to trust services legislation.

Version 1.00 Page 25 of 74

4 CERTIFICATE LIFE CYCLE OPERATIONAL REQUIREMENTS

4.1 Certificate application

4.1.1 Who can submit a certificate application

Individuals may apply for a Certificate for themselves and Organizations may apply for a Certificate for their employee.

4.1.2 Enrollment process and responsibilities

Process is performed only when the primary Certificate is issued. In case of **on-site** identity authentication, the subscriber (or his agent) initiates the registration process by appearing at an RA office and bringing all the required documents plus the Certificate application (if already existing). In case of **on-line** identity authentication, the process is initiated by running Zealid application on the mobile device of the subscriber and connecting this way to the ZealiD TRA Service. When the authentication is finished, the data contained in the submitted documents are entered into I.CA information system and the Certificate application is processed.

The Certificate's subscriber is required to do the following, among other things:

- Get acquainted with this CP and sign an agreement to observe it;
- Provide true and complete information for the issuance of the Certificate;
- Check whether the data specified in the Certificate application and the Certificate issued are correct and correspond to the required data;
- Choose a suitable Certificate revocation password (the minimum/maximum password length is 4/32 characters; permitted characters: 0...9, A...Z, a...z).

The Service provider is required to do the following, among other things:

- Inform the Certificate subscriber or the Organization about the terms and conditions prior to concluding the Certificate issuance contract;
- Conclude with the subscriber or the Organization, such a Certificate issuance contract that meets the requirements imposed by trust services legislation and technical and other standards;
- During the Certificate issuance process, check with RA all the data which can be validated specified in the application against the documents submitted;
- Require the proof of fact that private key was generated and stored on QSCD;
- Issue a Certificate that contains materially correct data on the basis of the information available to the Service provider as at the issuance of the Certificate;
- Publish public information in accordance with 2.2;
- Publish the Authority's certificates and the root CA's certificates;

Version 1.00 Page 26 of 74

Provide any Service-related activity in accordance with trust services legislation, this CP, the relevant CPS, the System Security Policy - Trustworthy Systems and the operating documentation.

4.2 Certificate application processing

4.2.1 Performing identification and authentication functions

The identification and authentication procedure for the **primary Certificate** follows the rules given in 3.2.3, or 3.2.2 where applicable, and the procedure for **subsequent Certificates** follows the rules given in 3.3.1.

4.2.2 Approval or rejection of certificate applications

RA employees (also as the Employees) do the following in the procedure leading to the decision accepting or dismissing the issuance of the **primary Certificate**:

- Make a visual check as to conformity of the data in the Certificate application (the PKCS#10 structure) with the data in the documents submitted;
- Make a visual check as to the formal correctness of data.

The private key ownership verification, competence check and formal data correctness check are also carried out using the RA system software.

If any of these checks gives a fail result, the Certificate issuance procedure is terminated; otherwise, the procedure continues in accordance with 4.3.

See 4.3 for the procedure for the issuance of **subsequent Certificates**.

4.2.3 Time to process certificate applications

I.CA SK must issue the Certificate immediately after Certificate issuance is granted. The following list gives tentative times for issuing Certificates unless other agreement is stipulated in the contract:

- Primary Certificate is usually (only on business days and during business hours) issued within 15 minutes, exceptionally it can take longer;
- Subsequent Certificates within units of minutes.

4.3 Certificate Issuance

4.3.1 CA actions during certificate issuance

CA operators (also as the Operators) carry out the following in the **primary Certificate** issuance procedure:

- Make a visual check as to conformity of the data in the Certificate application (the PKCS#10 structure) and the data entered by an RA employee;
- Make a visual check as to the formal correctness of data.

Version 1.00 Page 27 of 74

The verification of private key ownership, the supported hash function in the Certificate application (no weaker than sha-256), the competence check and the formal data correctness check are carried out by both the software on CA operators' work stations and that on the CA system core. If any of these checks gives a fail result, the Certificate issuance procedure is terminated.

Subsequent Certificate issuance procedure is automatic without Operators' intervention. The verification of private key ownership, the supported hash function in the Certificate application (no weaker than sha-256) and the competence check are carried out by software on the CA system core. If any of these checks gives a fail result, the Certificate issuance procedure is terminated.

4.3.2 Notification to subscriber by the CA of issuance of certificate

During the **primary Certificate** issuance process, the Certificate subscriber receives information from the RA employee or by e-mail. The issued Certificate is sent to the contact e-mail provided during registration as mandatory data.

Subsequent Certificates are sent to the contact e-mail provided during registration as mandatory data.

4.4 Certificate acceptance

4.4.1 Conduct constituting certificate acceptance

If the Certificate issuance requirements are met, the Certificate's subscriber must take the Certificate over. The only way to refuse to take over the Certificate is applying for the Certificate's revocation in accordance with this CP.

I.CA SK may agree with the Organization a procedure different from this provision of CP. However, that must not be contrary to the relevant provisions of the trust services legislation.

4.4.2 Publication of the certificate by the CA

I.CA SK publishes every Certificate it issues, except any Certificate:

- Containing data publication of which could be contrary to relevant legislation, such as the Personal Data Protection Act;
- Required by the subscriber not to be published.

4.4.3 Notification of certificate issuance by the CA to other entities

Chapter 4.4.2 and the requirements set out in trust services legislation apply.

Version 1.00 Page 28 of 74

4.5 Key pair and certificate usage

4.5.1 Subscriber private key and certificate usage

Subscribers must, among other things:

- Observe all relevant provisions of the Service contract;
- Use the private key and corresponding Certificate solely for the purposes defined in this CP;
- Handle the private key corresponding to the public key contained in the Certificate issued under this CP in a manner as to prevent any unauthorized use;
- Inform immediately the Service provider i.e., ICA SK, of everything that leads to the Certificate's revocation, in particular of:
 - Suspected abuse of the private key; and
 - □ Invalid or inaccurate attributes of Certificate;

In this case request for the Certificate's revocation and stop using the pertinent private key.

4.5.2 Relying party public key and certificate usage

Relying parties must, among other things:

- Obtain, from a secure source (e.g., www.ica.cz, RA workplace or relevant trusted list) certification authorities certificates linked with the Certificate issued under this CP, and verify those certificates' fingerprint values and validity:
- Carry out any operation necessary for them to verify that the Certificate is valid;
- Observe all and any provisions of this CP and trust services legislation which relate to the relying party's duties.

4.6 Certificate renewal

Certificate renewal under this CP means the issuance of a subsequent Certificate for a still valid Certificate without changing the public key, or the issuance of other information in the Certificate, or for a revoked Certificate, or for an expired Certificate.

Certificate renewal is not provided by I.CA SK. In respect of this CP, it is always the issuance of a new Certificate with a new public key, with all the information having to be duly validated. The same requirements as those in the initial identity validation apply – see 3.2.

4.6.1 Circumstance for certificate renewal

See 4.6.

4.6.2 Who may request renewal

See 4.6.

Version 1.00 Page 29 of 74

4.6.3 Processing certificate renewal requests

See 4.6.

4.6.4 Notification of new certificate issuance to subscriber

See 4.6.

4.6.5 Conduct constituting acceptance of a renewal certificate

See 4.6.

4.6.6 Publication of the renewal certificate by the CA

See 4.6.

4.6.7 Notification of certificate issuance by the CA to other entities

See 4.6.

4.7 Certificate re-key

Certificate public key replacement under this CP means the issuance of a new Certificate with a different public key but identical content of the attributes under the subject field or the subjectAlternativeName extension of the Certificate the public key of which is requested to be replaced.

If the whole new Certificate issuance procedure is handled solely electronically without requiring any natural person to be present at an RA office, it is the issuance of a subsequent Certificate. See 4.7.1 for the requirements in respect of validating electronic applications for subsequent Certificates; if these requirements are not met, it is the primary Certificate issuance procedure, which starts with the registration procedure.

4.7.1 Circumstance for certificate re-key

Applications for the subsequent Certificate (the PKCS#10 structure) with a replaced public key must meet the following requirements:

- The attributes under the subject field or the subjectAlternativeName extension must be identical to those in the Certificate which is to be replaced;
- The public key must be different from that in the Certificate which is to be replaced;
- The electronic subsequent Certificate application is validated in accordance with 3.3.1.

4.7.2 Who may request certification of a new public key

Replacement of the public key in a Certificate may be requested by the Certificate's subscriber.

Version 1.00 Page 30 of 74

4.7.3 Processing certificate re-keying requests

If the public key replacement requirements are met, the procedure continues in accordance with 4.2 and 4.3.1, otherwise the Certificate issuance procedure is terminated.

4.7.4 Notification of new certificate issuance to subscriber

See 4.3.2.

4.7.5 Conduct constituting acceptance of a re-keyed certificate

See 4.4.1.

4.7.6 Publication of the re-keyed certificate by the CA

See 4.4.2.

4.7.7 Notification of certificate issuance by the CA to other entities

See 4.4.3.

4.8 Certificate modification

Modifying Certificate data under this CP means the issuance of a new Certificate in which a minimum of one modification made to the content of the attributes, concerning the Certificate's subscriber, under the subject field or the subjectAlternativeName extension or in which one field which requires content validation is deleted or added. The public key must be different from that in the Certificate which is to be modified.

If the whole new Certificate issuance procedure is handled solely electronically without requiring any natural person to be present at an RA office, it is the issuance of a subsequent Certificate. See 4.8.1 for the requirements in respect of validating electronic applications for subsequent Certificates; if these requirements are not met, it is the primary Certificate issuance procedure, which starts with the registration procedure.

4.8.1 Circumstance for certificate modification

Application for the subsequent Certificate (the PKCS#10 structure) with modified data must meet the following requirements:

- The attributes to be modified or added in the subject field or the subjectAlternativeName extension must be duly validated;
- The public key must be different from that in the original Certificate;
- The electronic subsequent Certificate application is validated in accordance with 3.3.1.

4.8.2 Who may request certificate modification

Change to the data in a Certificate may be requested by the Certificate's subscriber.

Version 1.00 Page 31 of 74

4.8.3 Processing certificate modification requests

If the certificate data change requirements are met, the procedure continues in accordance with 4.2 and 4.3.1, otherwise the Certificate issuance procedure is terminated.

4.8.4 Notification of new certificate issuance to subscriber

See 4.3.2.

4.8.5 Conduct constituting acceptance of modified certificate

See 4.4.1.

4.8.6 Publication of the modified certificate by the CA

See 4.4.2.

4.8.7 Notification of certificate issuance by the CA to other entities

See 4.4.3.

4.9 Certificate revocation and suspension

Certificate revocation requests are accepted by I.CA SK irrespective of the time of the day if submitted electronically or by post. Submission in person to an RA is only possible during the particular RA's business hours.

I.CA SK does not provide certificate suspension.

4.9.1 Circumstances for revocation

A Certificate must be revoked as a result of the following, among other things:

- If the private key corresponding to the Certificate's public key is compromised or reasonably suspected to have been compromised;
- If the Certificate's subscriber or the Organization violated Service (under this CP) contract;
- In any event specified in trust services legislation or the relevant technical and other standards, such as invalid Certificate data;
- If the public key in the Certificate application is the same as the public key in a certificate already issued.

I.CA SK reserves the right to accept also other Certificate revocation situations, which, however, must not be contrary to trust services legislation.

4.9.2 Who can request revocation

Certificate revocation request may be submitted by:

Certificate's subscriber;

Version 1.00 Page 32 of 74

- Subject explicitly specified therefore in the Service (under this CP) contract;
- Any person who is beneficiary in Certificate's subscriber probate proceedings;
- Subject authorized to act for the legal successor to the original entity (the Organization) to which the Certificate was issued for that entity's employee;
- Provider of this Service (managing director of I.CA SK is the person authorized to request for the revocation of a Certificate issued by I.CA SK):
 - □ If the Certificate is issued on the basis of false data:
 - □ If demonstrably establishes that the private key belonging to the public key specified in the Certificate has been compromised;
 - □ If establishes that the Certificate was issued in spite of nonconformance with the requirements of trust services legislation;
 - □ If demonstrably establishes that the Certificate was used contrary to the restrictions defined in 1.4.2:
 - If demonstrably establishes that the Certificate's subscriber has died or been limited in legal capacity by court or the data according to which the Certificate was issued are no longer valid;
 - □ If the public key in the Certificate application is the same as the public key in a certificate already issued;
- Supervisory body and other entities as may be specified in trust services legislation.

4.9.3 Procedure for revocation request

Any Certificate revocation request delivered to RA in person must include the Certificate's serial number in the decimal or hexadecimal format (introduced by the string '0x'), the full name of the person authorized to request for the Certificate's revocation, and the Certificate revocation password. If the person authorized to request for revocation does not know the Certificate revocation password, s/he must explicitly state this in the written application, along with the number of the primary personal document submitted in the Certificate application procedure or the number of the new primary personal document if the original document has been replaced. The person must use this primary personal document to prove their identity with the RA employee. If the request is legitimate, the RA employee revokes the Certificate, and the Certificate revocation date and time are the date and time when the request is processed by CA's information system. If the Certificate revocation application cannot be accepted (wrong revocation password or no proof of identity of the person authorized to request for Certificate revocation) the RA employee seeks to rectify these defects, and dismisses the request if the defects cannot be rectified for any reason. The RA employee always notifies the requestor of the result.

The following options are available for electronic submission of Certificate revocation request:

- Using the form on the information web page. The Certificate revocation date and time are the date and time a valid Certificate revocation request is dealt with in the CA's information system. The request receives a notice if the request is granted;
- Message signed electronically the body text must contain (in Czech or Slovak with or without diacritics, or in English):

Version 1.00 Page 33 of 74

Zadam o zneplatneni certifikatu cislo = xxxxxxxx. [I request revocation of certificate number = xxxxxxxx.],

where 'xxxxxxx' is the Certificate's serial number and must be given either in the decimal or hexadecimal format (introduced by the string '0x').

The message must be electronically signed with the private key corresponding to the public key in the Certificate to be revoked;

■ Electronic message not signed electronically – the body text must contain (in Czech or Slovak with or without diacritics, or in English):

Zadam o zneplatneni certifikatu cislo = xxxxxxxx. [I request revocation of certificate number = xxxxxxxx.]

Heslo pro zneplatneni = yyyyyy. [Revocation password = yyyyyy.],

where 'xxxxxxx' is the Certificate's serial number and 'yyyyyy' the revocation password. The Certificate's serial number must be given either in the decimal or hexadecimal format (introduced by the string '0x');

Message signed electronically, or not signed electronically in special cases, and sent by a defined person authorized to represent the Organization in the contractual relationship with I.CA SK:

Zadam o zneplatneni certifikatu cislo = xxxxxxxx. [I request revocation of certificate number = xxxxxxxx.],

where 'xxxxxxx' is the Certificate's serial number. The Certificate's serial number must be given in the decimal or hexadecimal format (introduced by the string '0x').

Note:

If the request meets the requirements of the three options listed above, the employee in charge immediately revokes the Certificate in the CA's system, and the date and time the request is processed by the CA's information system are the date and time of the Certificate's revocation. The requestor receives a notice if the request was accepted.

If Certificate revocation request is submitted as a registered post letter, the request must contain following text (in Czech or Slovak with or without diacritics, or in English):

Zadam o zneplatneni certifikatu cislo = xxxxxxxx. [I request revocation of certificate number = xxxxxxxx.]

Heslo pro zneplatneni = yyyyyy. [Revocation password = yyyyyy.],

where 'xxxxxxx' is the Certificate's serial number and 'yyyyyy' the revocation password. The serial number is to be given either in the decimal or hexadecimal format (introduced by the string '0x'). If the request meets these requirements, the I.CA employee in charge immediately revokes the Certificate in the CA's system, and the date and time the request is processed by the CA's information system are the date and time of the Certificate's revocation. If the request cannot be accepted (wrong revocation password), the Certificate revocation request will be rejected. Requestor is informed by a registered letter sent to postal address of request sender how the request was handled.

4.9.4 Revocation request grace period

Certificate revocation request must be made immediately.

Version 1.00 Page 34 of 74

4.9.5 Time within which CA must process the revocation request

The maximum time allowed between accepting a Certificate revocation request and the Certificate's revocation is 24 hours.

4.9.6 Revocation checking requirement for relying parties

Relying parties must carry out all the operations specified in 4.5.2.

4.9.7 CRL issuance frequency

The certificate revocation list is released immediately after a Certificate revocation request is handled affirmatively. If a Certificate is not revoked, the new CRL is usually released within 8 but no more than 24 hours after the previous CRL is released.

4.9.8 Maximum latency for CRLs

The CRL is published immediately after issuing, conditions described in 4.9.5 and 4.9.7 are always met.

4.9.9 On-line revocation/status checking availability

Checking Certificate status using the OCSP protocol is a service available to the general public. Every certificate issued under this CP includes a link to the pertinent OCSP responder.

OCSP responses satisfy the RFC 2560 and RFC 5019 standards. The OCSP responder's certificate includes an id-pkix-ocsp-nocheck extension as defined in RFC 2560.

4.9.10 On-line revocation checking requirements

See 4.9.9.

4.9.11 Other forms of revocation advertisements available

Not applicable to this document.

4.9.12 Special requirements re key compromise

The Certificate revocation procedure in the event of private key compromise is not different from the certificate revocation procedure described above.

4.9.13 Circumstances for suspension

Not applicable to this document; Certificate suspension is not provided.

4.9.14 Who can request suspension

Not applicable to this document; Certificate suspension is not provided.

Version 1.00 Page 35 of 74

4.9.15 Procedure for suspension request

Not applicable to this document; Certificate suspension is not provided.

4.9.16 Limits on suspension period

Not applicable to this document; Certificate suspension is not provided.

4.10 Certificate status services

4.10.1 Operational characteristics

Lists of public Certificates are provided as published information; certificate revocation lists are provided as published information and by specifying the CRL distribution points in the Certificates issued by the Authority.

The fact that the Authority provides Certificate status information in the form of OCSP is specified in the certificates issued by the Authority.

4.10.2 Service availability

The Authority guarantees round-the-clock (24/7) availability and integrity of the list of the Certificates it has issued and the list of revoked certificates (CRLs), plus the availability of the OCSP service.

Revocation records on CRL or in OCSP response are kept at least to the end of Certificate's validity period.

4.10.3 Optional features

Not applicable to this document; no other certificate status check characteristics are provided.

4.11 End of subscription

The contract can be terminated by written agreement of both parties or by the expiration of the last Certificate issued under this contract.

4.12 Key escrow and recovery

Not applicable to this document; the key escrow and recovery service is not provided.

4.12.1 Key escrow and recovery policy and practices

See 4.12.

Version 1.00 Page 36 of 74

4.12.2 Session key encapsulation and recovery policy and practices

See 4.12.

Version 1.00 Page 37 of 74

5 FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS

Facility, management, and operational controls primarily deal with:

- Trustworthy systems designed to support trust services;
- All processes supporting the provision of the services specified above.

The facility, management, and operational controls are addressed in the fundamental documents of I.CA - Corporate Security Policy, System Security Policy - Trustworthy Systems, Certification Practice Statement, Business Continuity Plan and Recovery Plan as well as in the more detailed internal documentation of I.CA. These documents take account of the results of periodic risk analyses.

5.1 Physical controls

5.1.1 Site location and construction

The I.CA operating site buildings are situated in geographically different locations, which are also different from the site of I.CA SK headquarters, the site of I.CA headquarters, the business and development sites, the registration authority sites and the points of sale.

The trustworthy systems designed to support trust services are situated on reserved premises of operating sites. These premises are secured in a manner similar to that required by the Classified Information Protection Act for the 'Confidential' category secure areas.

5.1.2 Physical access

Requirements for physical access to the reserved premises (protected with mechanical and electronic features) of operating sites are described in internal documentation of I.CA. Buildings are protected with intrusion alarm system (IAS), alarm receiving centre (ARC) and, as may be the case, a special system to monitor movement of persons and vehicles.

5.1.3 Power and air conditioning

The premises housing the trustworthy systems supporting trust services have active air-conditioning of adequate capacity, which keeps the temperature at $20^{\circ}\text{C} \pm 5^{\circ}\text{C}$ all year round. The supply of electricity is backed up with a UPS (Uninterruptible Power Supply) and a diesel unit.

5.1.4 Water exposures

The trustworthy systems supporting trust services are so located as to ensure they cannot be flooded with a 100-year flood. Where relevant operating sites have water ingress sensors to detect heating water leakage or rainfall leakage through the roof (as a result of heavy rains).

Version 1.00 Page 38 of 74

5.1.5 Fire prevention and protection

The buildings of the operating sites and the information archiving sites have electronic fire alarm system (FAS). Fireproof insulation is installed in the entrance doors to the restricted areas in which the trustworthy systems designed to support trust services are situated, and fire extinguishers are fitted in these areas.

5.1.6 Media storage

Archiving media containing operational backups and electronic records are stored in metal boxes or safes. Copies are kept at a site geographically different from the site of the operating office.

Any paper media required to be archived are stored in a site geographically different from the site of the operating office.

5.1.7 Waste disposal

Any paper office waste is shredded before it leaves I.CA operating sites.

5.1.8 Off-site backup

The copies of operating and working backups are stored in a place designated by the COO of I.CA and described in internal documentation of I.CA.

5.2 Procedural controls

5.2.1 Trusted roles

Trusted roles are defined for selected activities carried out at I.CA. The trusted role employee appointment procedure, the trusted roles and their responsibilities are defined in internal documentation of I.CA.

I.CA employees appointed to a trusted role may not be in a conflict of interests that could compromise the impartiality of operations of I.CA.

5.2.2 Number of persons required per task

Jobs are defined for the processes related to the key pairs of certification authorities and OCSP responders and these jobs must be performed with more than a single person attending. These jobs include:

- Initialization of cryptographic module;
- Generating key pairs of certification authorities and their OCSP responders;
- Destroying private keys of certification authorities and their OCSP responders including their backups;
- Backup and restore of private keys of certification authorities and their OCSP responders;

Version 1.00 Page 39 of 74

Activation and deactivation of private keys of certification authorities and their OCSP responders.

The number of attending persons is not defined for other jobs, but all persons must be authorized persons.

5.2.3 Identification and authentication for each role

Each role's employees are assigned identification (name and certificate) and authentication (password and private key) data for those components which are necessary for their jobs.

Selected jobs require two-factor authentication by the trusted role employees.

5.2.4 Roles requiring separation of duties

The roles requiring separation of duties (and the roles' job descriptions) are described in internal documentation of I.CA.

5.3 Personnel controls

5.3.1 Qualification, experience, and clearance requirements

Trusted roles employees are in I.CA selected and hired using the following criteria:

- Clean criminal record statement of criminal conviction records or affirmation is required;
- Bachelor's or master's degree in an accredited university program and ICT job experience of three years or longer, or secondary education and ICT job experience of five years or longer, of which at least one-year job experience in the provision of trust services;
- Knowledge in public key infrastructure and information security.

Any other I.CA or I.CA SK employee taking part in providing trust services is accepted using the following criteria:

- Bachelor's or master's degree in an accredited university program, or secondary education;
- Basic orientation in public key infrastructure and information security.

Managers must have job experience or technical training in respect of the trustworthiness of the Service, the knowledge of security procedures with security responsibility, and experience in information security and risk assessment.

5.3.2 Background check procedures

The sources of information about all employees of I.CA or I.CA SK are:

- The employees themselves;
- Persons familiar with a particular employee;
- Public sources of information.

Version 1.00 Page 40 of 74

Initial information is provided by employees at job interviews, and this information is updated at periodic appraisal interviews with the manager during employment.

5.3.3 Training requirements

I.CA or I.CA SK employees receive technical training in the use of specific software and specialized devices. The training takes the form of self-study combined with guidance from a trained employee. The training covers information security, personal protection data and other relevant topics.

5.3.4 Retraining frequency and requirements

I.CA or I.CA SK employees are provided with the current developments in their spheres of interest two times every 12 months.

Training in the processes related to RA operations is held for RA employees at least once in every three years.

5.3.5 Job rotation frequency and sequence

I.CA or I.CA SK employees are encouraged to acquire knowledge necessary for working in other roles at I.CA or I.CA SK, in order to ensure substitutability for cases of emergency.

5.3.6 Sanctions for unauthorized actions

If an employee is detected to have been performing unauthorized activity, the employee is subject to the procedure described in internal documentation of I.CA and governed by the Labour Code (this process does not prevent criminal prosecution if the unauthorized activity exhibits that degree of gravity).

5.3.7 Independent contractor requirements

I.CA or I.CA SK may or must procure some activities from independent contractors, and is fully liable for the job they deliver. These business relations are regulated in bilateral business contracts with parties such as contracted registration authorities, application software developers, hardware suppliers, system software suppliers, external auditors and other parties. These parties are required to observe the pertinent certification policies, the relevant parts of internal documentation of I.CA provided to them, and the required normative documents. Contractual penalties are applied for a breach of the obligations or duties specified in the said documents, or the contract with the contractor in breach is terminated immediately.

5.3.8 Documentation supplied to personnel

In addition to the certification policy, the certificate practice statement and the security and operating documentation, I.CA or I.CA SK employees have available any other relevant standard, policy, manual and guidance they may need for their job.

Version 1.00 Page 41 of 74

5.4 Audit logging procedures

5.4.1 Types of events recorded

Subject to logging are all the events required by trust services legislation or the relevant technical and other standards to be logged, that is, for example, the life cycle events of Certificates.

The certification authorities' key pair generating is a special case of event logging. All this process complies with trust services legislation and the relevant technical and other standards. Generating is carried out according to a pre-determined scenario in a physically secure environment and under the control of more I.CA employees in trusted roles.

Protocol on key generating with data required by technical standards is created on key pair generating and is signed by present I.CA employees in trusted roles.

When the key pair of root certification authority is generated, an auditor qualified in accordance with current technical standards personally attends the process, signs also the created protocol to confirm that the generating followed the pre-determined scenario and the measures to ensure integrity and confidentiality were in place.

All audit records are made, kept and processed to the extent as necessary, while preserving the proof of origin and maintaining integrity, availability, confidentiality and time authenticity.

The auditing system is designed and run in a manner ensuring audit data integrity, sufficient space for audit data, automatic non-rewriting of the audit file, user-friendly presentation of audit records, and audit file access limited to the defined users only.

5.4.2 Frequency of processing log

Audit records are checked and assessed at the intervals defined in internal documentation of I.CA, or immediately when a security incident occurs.

5.4.3 Retention period for audit log

Unless the relevant legislation provides otherwise, audit records are kept for a minimum of ten years of the day they are made.

5.4.4 Protection of audit log

Both electronic and printed audit records are stored in a manner ensuring they are protected against change, stealing and destruction (willful or accidental).

Electronic audit records are archived in two copies. These audit records are archived on a medium each month or more frequently and this medium is kept outside the operating premises of I.CA.

Printed audit records are kept outside the operating premises of I.CA.

The protection of the aforesaid types of audit records is described in internal documentation of I.CA.

Version 1.00 Page 42 of 74

5.4.5 Audit log backup procedures

Electronic audit records are backed up similarly to how other electronic information is backed up. No backup of printed audit records takes place.

5.4.6 Audit collection system (internal vs. external)

The audit record collection system is an internal one relative to the CA information systems.

5.4.7 Notification to event-causing subject

Parties are not notified of that an event is registered in an audit record.

5.4.8 Vulnerability assessments

I.CA carries out periodic vulnerability assessments as part of risk assessments. Vulnerability monitoring of the hardware and software related to trust services is described in internal documentation of I.CA.

5.5 Records archival

The archiving of records, i.e., information and documentation, is at I.CA regulated in internal documentation of I.CA.

5.5.1 Types of records archived

I.CA or I.CA SK archives the following electronic or printed records pertaining to the trust services provided, such as:

- Records / protocols on the course of certification authorities key pair generating;
- Life cycle records for the Certificates;
- Other records that may be necessary for issuing Certificates;
- Information handling records, such as takeover, handover, saving, check, conversion from printed to electronic, etc.;
- Application software, operating and security documentation.

5.5.2 Retention period for archive

All records pertaining to the certificates of all I.CA or I.CA SK certification authorities and their respective OCSP responders, except for the pertinent private keys, are archived throughout the existence of I.CA. Other records are archived in accordance with 5.4.3.

The record archiving procedures are regulated in internal documentation of I.CA.

5.5.3 Protection of archive

The premises where records are archived are secured in a manner based on risk analysis results and the Classified Information Protection Act.

Version 1.00 Page 43 of 74

The procedures to protect the archived records are regulated by internal documentation of LCA.

5.5.4 Archive backup procedures

The record backup procedures are regulated in internal documentation of I.CA.

5.5.5 Requirements for time-stamping of records

If time-stamp tokens are used, they are qualified electronic time-stamp tokens issued by I.CA.

5.5.6 Archive collection system (internal or external)

Records are archived in a place designated by COO of I.CA or by managing director of I.CA SK.

Internal documentation of I.CA regulates how both electronic and printed records are prepared for archiving and stored. Records are kept of collecting the records subject to archiving.

5.5.7 Procedures to obtain and verify archive information

Archived information and records are stored at sites designated therefore and are accessible to:

- I.CA or I.CA SK employees if they need to have such an access for their job;
- Authorized supervising and inspection entities and law enforcement authorities if required by legislation.

A written record is made of any such permitted access.

5.6 Key changeover

In standard situations (expiration of a certification authority certificate), the key is replaced by issuing a new certificate a good time in advance (no later than one year prior to the expiration).

In non-standard situations, for instance such progress in cryptanalytic methods that could compromise the security of certificate issuance (e.g., changes to cryptanalytic algorithms or key length), the key is replaced as soon as possible.

In both standard and non-standard situations, the replacement of the public key in certification authority certificates is suitably notified to the public a good time in advance (if practicable).

Version 1.00 Page 44 of 74

5.7 Compromise and disaster recovery

5.7.1 Incident and compromise handling procedures

In the event of incident or compromise, I.CA takes a course of action in accordance with its internal business continuity plan and recovery plan, plus any other relevant internal documentation.

5.7.2 Computing resources, software, and/or data are corrupted

See. 5.7.1.

5.7.3 Entity private key compromise procedures

In the case of reasonable concern that a private key of certification authorities has been compromised, I.CA or I.CA SK does the following:

- Stops using the private key;
- Revokes immediately and permanently the pertinent certificate and destroys the corresponding private key;
- Revokes all valid certificates issued by pertinent certification authority;
- Notifies this and the reason immediately on its web Information Address, and also the list of revoked certificates is used for disclosing this information;
- Notifies the supervisory body of that the pertinent certificate has been revoked and why it has been revoked.

A similar course of action will be taken in the event of such developments in cryptanalytic methods, such as changes to cryptanalytic algorithms or key length that could immediately compromise the security of the trust services.

5.7.4 Business continuity capabilities after a disaster

In the event of accident, I.CA takes a course of action in accordance with its internal business continuity plan and recovery plan, plus any other relevant internal documentation of I.CA.

5.8 CA or RA termination

The following rules apply to the termination of the Authority's operations:

- The termination of the Authority's operations must be notified in writing to the supervisory body, all subscribers of valid Certificates, and the parties having contract with I.CA SK that directly concerns the provision of trust services;
- The termination of the Authority's operations must be published on the web page pursuant to 2.2;
- If the Authority's certificate's expiration is part of the termination of operations, this information plus the reason for expiration must be included in that notice;

Version 1.00 Page 45 of 74

- The termination of operations is a controlled process following a pre-defined plan, which includes the description of the procedure to preserve and disclose information for judicial or administrative proceedings discovery and for arranging the continuity of services:
- The Authority or its successor must be able to revoke Certificates and publish CRLs as long as any Certificate issued by the Authority is valid;
- After that the Authority must demonstrably destroy its private key, make a record of this destruction and keep this record in accordance with this CP.

In the event of withdrawal of the qualified Service provider status:

- The information must be notified in writing or electronically to all subscribers of valid Certificates, and the parties having contract with I.CA or I.CA SK that directly concerns the provision of trust services;
- The information must be published in accordance with 2.2. at all offices of registration authorities and must also communicate that certification authorities' certificates cannot be used in accordance with the purpose of their issuance any longer;
- The subsequent course of action will be decided by CEO of I.CA or managing director of I.CA SK while taking account of the decision of the supervisory body.

If a specific RA office closes down, this is published on http://www.ica.cz.

Version 1.00 Page 46 of 74

6 TECHNICAL SECURITY CONTROLS

6.1 Key pair generation and installation

6.1.1 Key pair generation

Key pairs of certification authorities and their corresponding OCSP responders are generated in designated secured areas of operating sites, according to a pre-defined scenario, in accordance with 5.2 and 5.4.1. Generating is carried out in cryptographic modules fulfilling requirements of trust service legislation, i.e., ETSI and CEN standards.

Key pairs of the employees taking part in the issuing Certificates are generated on smartcards meeting the QSCD requirements. The private keys of these key pairs are stored on smartcard in non-exportable form and PIN needs to be entered to use the keys.

All requirements concerning generating of key pairs mentioned above are described both in internal and external documentation of I.CA.

Key pairs related to Certificates issued under this CP are generated on devices which are under sole control of the respective subscribers. These key pairs may be stored on QSCD only.

6.1.2 Private key delivery to subscriber

Not applicable to the private keys of certification authorities and their corresponding OCSP responders – private keys are stored in cryptographic modules under the sole control of I.CA.

The service of generating key pairs to end users or to employees taking part in issuing Certificates is not provided.

6.1.3 Public key delivery to certificate issuer

Public keys are delivered to certificate issuer in the certificate application (PKCS#10 format).

6.1.4 CA public key delivery to relying parties

Following options for obtaining the certification authority's public key contained in this certification authority's certificate are guaranteed:

- Handover from RA;
- Via web information addresses of I.CA or I.CA SK, relevant supervisory body or its journal;
- Every subscriber gets relevant certification authorities' certificates together with his primary certificate.

6.1.5 Key sizes

The RSA asymmetric algorithm is solely used for the Service provided under this CP. The size of the key of I.CA root certification authority is 4096 bits; the minimum size of the keys in

Version 1.00 Page 47 of 74

the certificates issued by this root certification authority is 2048 bits. The minimum size of the keys in the Certificates issued under this CP is 2048 bits.

6.1.6 Public key parameters generation and quality checking

The parameters of the algorithms used in generating public keys of certification authorities and their corresponding OCSP responders meet the requirements listed in trust services legislation and the technical and other standards referred to therein. These keys are checked by relevant hardware and software.

The parameters of the algorithms used in generating public keys of other subscribers must also meet these requirements and are check in the same way.

6.1.7 Key usage purposes (as per X.509 v3 key usage extension)

The key usage options are specified in the certificate's extension.

6.2 Private key protection and cryptographic module engineering controls

6.2.1 Cryptographic module standards and controls

Key pairs of certification authorities and their corresponding OCSP responders are generated and private keys are stored in cryptographic modules which meet the requirements of trust services legislation, that is ETSI and CEN standards.

Employees taking part in issuing certificates use the smartcard meeting the QSCD requirements.

End users use the device meeting the QSCD requirements.

6.2.2 Private key (n out of m) multi-person control

If cryptographic module related operations require the presence of more persons, then each of them knows only some part of the code required for these operations.

6.2.3 Private key escrow

Not applicable to this document; the private key escrow service is not provided.

6.2.4 Private key backup

The cryptographic modules used for the administration of certification authorities' and their corresponding OCSP responders' key pairs facilitates private key backup. Encryption of these backups ensures the same level of protection as the cryptographic module does.

Not applicable for private keys of employees taking part in issuing certificates, these private keys are generated on smartcards as non-exportable.

Backup of private keys of end users is fully within the competence of these end users.

Version 1.00 Page 48 of 74

6.2.5 Private key archival

When certification authorities' and their corresponding OCSP responders' private keys expire, they are not archived, but destroyed including their backup copies.

Archiving period of private keys of employees taking part in issuing certificates is limited by the memory capacity of the smartcard

Archiving private keys of end users is fully within the competence of these end users.

6.2.6 Private key transfer into or from a cryptographic module

Private keys of certification authorities and their corresponding OCSP responders are generated (as non-exportable) in cryptographic modules (operated in certified mode) and there is no way to export them outside the cryptographic module¹. Import of private keys into the cryptographic module is not performed.

Not applicable for private keys of employees taking part in issuing certificates, these private keys are generated on smartcards as non-exportable.

Transferring private keys of end users is fully within the competence of these end users.

6.2.7 Private key storage on cryptographic module

Private keys of certification authorities and their corresponding OCSP responders are stored in the cryptographic modules which meets the requirements of trust services legislation, i.e., ETSI and CEN standards.

Private keys of employees taking part in issuing certificates are stored on smartcards meeting the QSCD requirements.

Key pairs of end users are stored on QSCD.

6.2.8 Method of activating private key

Activation of certification authorities' and their corresponding OCSP responders' private keys (allowing the use of these private keys) is done:

- In case of smartcard activation by inserting the smartcard and entering the password;
- In case of softcard activation by entering the softcard and password.

Private keys of employees taking part in issuing certificates are activated by inserting the smartcard and entering PIN.

Activation private keys of end users is fully within the competence of these end users and depends on the way of storing these private keys.

6.2.9 Method of deactivating private key

Deactivation of certification authorities' and their corresponding OCSP responders' private keys is done by removing the smartcard or by terminating the specific application.

Version 1.00 Page 49 of 74

-

¹ Encrypted backup is the only one exception, this backup can be used only in cryptographic module (or in HA/LB modules), where the key was generated.

Private keys of employees taking part in issuing certificates are deactivated by removing the smartcard.

Deactivation private keys of end users is fully within the competence of these end users and depends on the way of storing these private keys.

6.2.10 Method of destroying private key

After expiration of specific certification authority's private key and based on subsequent decision of CEO of I.CA or managing director of I.CA SK this private key is destroyed according to specific procedure including all backups of this key. Destroying is documented in a written record.

Private keys of OCSP responders are destroyed on the decision of I.CA or I.CA SK representative when issuing OCSP responder's certificate. Destroying is documented in a written record.

Destroying private keys of employees taking part in issuing certificates is fully within the competence of these employees.

Destroying private keys of end users is fully within the competence of these end users and depends on the way of storing these private keys.

6.2.11 Cryptographic module rating

Cryptographic modules used for generating of key pairs and storing corresponding private keys of certification authorities and their corresponding OCSP responders meet the requirements of trust services legislation, that is ETSI and CEN standards and are used in compliance with their certification.

Smart card used for generating of key pairs and storing corresponding private keys of employees taking part in issuing certificates meet QSCD requirements.

Key pairs of end users are stored on QSCD.

6.3 Other aspects of key pair management

6.3.1 Public key archival

All public keys as part of Certificates are archived throughout the existence of I.CA.

6.3.2 Certificate operational periods and key pair usage periods

The maximum period of validity of each certificate issued is specified in the body of that certificate and is the same as key pair usage period.

Version 1.00 Page 50 of 74

6.4 Activation data

6.4.1 Activation data generation and installation

Activation data of certification authorities' and their corresponding OCSP responders' private keys (smartcard or softcard) of are created before or during the generating of the corresponding key pair.

Activation data of employees' taking part in issuing certificates private keys is PIN, which is under sole control of these employees.

Usage of activation data by corresponding end users is fully within the competence of these end users.

6.4.2 Activation data protection

Activation data of certification authorities' and their corresponding OCSP responders' private keys are protected by passwords.

Activation data of employees' taking part in issuing certificates private keys protection is fully within the competence of these employees.

Activation data of end users' private keys protection is fully within the competence of these employees.

6.4.3 Other aspects of activation data

Not applicable to this document.

6.5 Computer security controls

6.5.1 Specific computer security technical requirements

The level of security of the components used in providing trust services is, including the scope of necessary evaluations and assessments and also trustworthy systems configuration checks, and their periodicity, defined in trust services legislation and the technical standards referred to therein.

6.5.2 Computer security rating

The assessment of I.CA computer security is based on the requirements set out in the specified technical and other standards, in particular:

- CEN/TS 419261 Security Requirements for Trustworthy Systems Managing Certificates and Time-stamps;
- ČSN ETSI EN 319 401 Electronic Signatures and Infrastructures (ESI) General Policy Requirements for Trust Service Providers:
- ETSI EN 319 401 Electronic Signatures and Infrastructures (ESI); General Policy Requirements for Trust Service Providers;

Version 1.00 Page 51 of 74

- ČSN ETSI EN 319 403 Electronic Signatures and Infrastructures (ESI) Trust Service Provider Conformity Assessment Requirements for Conformity Assessment Bodies Assessing Trust Service Providers;
- ETSI EN 319 403 Electronic Signatures and Infrastructures (ESI); Trust Service Provider Conformity Assessment Requirements for Conformity Assessment Bodies Assessing Trust Service Providers;
- ČSN ETSI EN 319 411-1 Electronic Signatures and Infrastructures (ESI) Policy and Security Requirements for Trust Service Providers Issuing Certificates – Part 1: General Requirements;
- ETSI EN 319 411-1 Electronic Signatures and Infrastructures (ESI); Policy and Security Requirements for Trust Service Providers Issuing Certificates; Part 1: General Requirements;
- ČSN ETSI EN 319 411-2 Electronic Signatures and Infrastructures (ESI) Policy and Security Requirements for Trust Service Providers Issuing Certificates Part 2: Requirements for Trust Service Providers Issuing EU Qualified Certificates;
- ETSI EN 319 411-2 Electronic Signatures and Infrastructures (ESI); Policy and Security Requirements for Trust Service Providers Issuing Certificates; Part 2: Requirements for Trust Service Providers Issuing EU Qualified Certificates;
- ČSN ETSI EN 319 412-1 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 1: Overview and Common Data Structures;
- ETSI EN 319 412-1 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 1: Overview and Common Data Structures:
- ČSN ETSI EN 319 412-2 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 2: Certificate Profile for Certificates Issued to Natural Persons;
- ETSI EN 319 412-2 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 2: Certificate Profile for Certificates Issued to Natural Persons;
- ČSN ETSI EN 319 412-3 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 3: Certificate Profile for Certificates Issued to Legal Persons;
- ETSI EN 319 412-3 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 3: Certificate Profile for Certificates Issued to Legal Persons;
- ČSN ETSI EN 319 412-4 Elektronické podpisy a infrastruktury (ESI) Profily certifikátu
 Část 4: Profil certifikátu pro certifikáty webových stránek;
- ETSI EN 319 412-4 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 4: Certificate profile for web site certificates;
- ČSN ETSI EN 319 412-5 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 5: QC Statements;
- ETSI EN 319 412-5 Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 5: QCStatements;
- ČSN EN 419 221-5 Protection profiles for TSP Cryptographic modules Part 5 Cryptographic Module for Trust Services;
- EN 419 221-5 Protection profiles for TSP Cryptographic modules Part 5 Cryptographic Module for Trust Services;
- FIPS PUB 140-2 Requirements for Cryptographic Modules;

Version 1.00 Page 52 of 74

- ISO/IEC 15408-1:2009 Information technology Security techniques Evaluation criteria for IT security Part 1: Introduction and general model;
- ČSN EN ISO/IEC 15408-2 Information technology Security techniques Evaluation criteria for IT security Part 2: Security functional components;
- ISO/IEC 15408-2:2008 Information technology Security techniques Evaluation criteria for IT security Part 2: Security functional components;
- ČSN EN ISO/IEC 15408-3 Information technology Security techniques Evaluation criteria for IT security — Part 3: Security assurance components;
- ISO/IEC 15408-3:2008 Information technology Security techniques Evaluation criteria for IT security Part 3: Security assurance components;
- ETSI TS 119 312 Electronic Signatures and Infrastructures (ESI); Cryptographic Suites;
- ČSN ISO/IEC 27006 Information Technology Security Techniques Requirements for Bodies Providing Audit and Certification of Information Security Management Systems, resp. STN ISO/IEC 27006 Information Technology Security Techniques Requirements for Bodies Providing Audit and Certification of Information Security Management Systems.
- ISO/IEC 17021 Conformity Assessment -- Requirements for Bodies Providing Audit and Certification of Management Systems;
- ISO/IEC 17065 Conformity Assessment -- Requirements for Bodies Certifying Products, Processes and Services.
- ISO 3166-1 Codes for the Representation of Names of Countries and Their Subdivisions Part 1: Country Codes;
- ITU-T X.501 Information Technology Open Systems Interconnection The Directory: Models;
- ITU-T X.509 Information Technology Open Systems Interconnection The Directory: Public-key and Attribute Certificate Frameworks;
- ITU-T X.520 Information Technology Open Systems Interconnection The Directory: Selected Attribute Types;
- RSA Laboratories PKCS#10: Certification Request Syntax Standard;
- RFC 2560 X.509 Internet Public Key Infrastructure Online Certificate Status Protocol OCSP;
- RFC 3647 Internet X.509 Public Key Infrastructure Certificate Policy and Certification Practices Framework:
- RFC 5019 The Lightweight Online Certificate Status Protocol (OCSP) Profile for High-Volume Environments:
- RFC 5280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile;
- EN 301 549 Accessibility requirements for ICT products and services.

Version 1.00 Page 53 of 74

6.6 Life cycle technical controls

6.6.1 System development controls

System development is carried out in accordance with internal documentation of I.CA.

6.6.2 Security management controls

Information security management and compliance with technical standards are inspected as part of the periodic trust services inspections and also during information security management system (ISMS) audits.

Information security at I.CA is governed by the following standards:

- ČSN ISO/IEC 27000 Information Technology Security Techniques Information Security Management Systems Overview and Vocabulary or STN ISO/IEC 27000 Informačné technológie. Bezpečnostné metódy. Systémy riadenia informačnej bezpečnosti. Prehľad a slovník;
- ČSN ISO/IEC 27001 Information Technology Security Techniques Information Security Management Systems Requirements or STN ISO/IEC 27001 Informačné technológie. Bezpečnostné metódy. Systémy riadenia informačnej bezpečnosti. Požiadavky;
- ČSN ISO/IEC 27002 Information Technology Security Techniques Information Security Management Systems Code of Practice for Information Security Controls or STN ISO/IEC 27002 Informačné technológie. Bezpečnostné metódy. Pravidlá dobrej praxe riadenia informačnej bezpečnosti.

6.6.3 Life cycle security controls

I.CA takes the Plan-Do-Check-Act (PDCA) procedural approach to life cycle security management; the PDCA approach consists of the following consecutive processes:

- Establishing defining the scope and the boundaries for information security management, determining a security policy and plans, and choosing security controls depending on the risks identified, all this in accordance with the corporate security policy;
- Implementing and operating effective and systematic enforcement of the selected security controls;
- Monitoring and reviewing providing feedback, regular monitoring and evaluation of the successful and the poor aspects of information security management, providing the knowledge gained for the company management for assessment;
- Maintenance and improvement implementing corrective and improvement measures as decided by the company management.

6.7 Network security controls

Network infrastructure of the operating site is protected with a firewall-type commercial product with an integrated intrusion prevention system. The detailed network security

Version 1.00 Page 54 of 74

management solution is described in internal documentation of I.CA. All communication between RA and the operating sites is encrypted.

6.8 Time-stamping

See 5.5.5 for the time-stamping solution.

Version 1.00 Page 55 of 74

7 CERTIFICATE, CRL AND OCSP PROFILES

7.1 Certificate profile

Table 4 - Basic certificate fields

Table 4 - Dasic Certificate fields		
Field	Content	
version	v3 (0x2)	
serialNumber	unique serial number of the Certificate	
signatureAlgorithm	sha256withRSAEncryption at minimum	
issuer	issuer of the Certificate	
validity		
notBefore	start of the Certificate's validity (UTC)	
notAfter	notBefore + at maximum 365 days, or 366 days in case of leap year (UTC)	
subject	see Table 5	
subjectPublicKeyInfo		
algorithm	rsaEncryption	
subjectPublicKey	2048 bits at minimum	
extensions	see Table 6	
signature	advanced electronic seal of Certificate's issuer (Authority)	

Table 5 - Subject field attributes

All attributes² of the subject field are taken over from the Certificate application except the attributes created by the Authority. The application must include the mandatory attributes.

Subject field attributes	Comments
countryName**	mandatory, country code (ISO 3166), single occurrence
givenName	mandatory if the pseudonym attribute is not specified; single occurrence
surName	mandatory if the pseudonym attribute is not specified; single occurrence
pseudonym	mandatory if the givenName and the surName attributes are not specified; single occurrence
serialNumber (1)	created by Authority, unique identification of the Certificate's subscriber in the Authority's system (ICA - xxxxxxxx); also

² I.CA SK reserves the right to modify the set of items and the content of the subject field as may be required by updated ETSI standards or third parties (Microsoft, for example).

Version 1.00 Page 56 of 74

	used in automated subsequent certificate issuance	
serialNumber (2)	optional; one of following options:	
	• IDCss-nnnnnnn;	
	PASss-nnnnnnn;	
	PNOss-yyyyyyyyy for the Slovak Republic citizens only;	
	where <i>ss</i> is the country code (ISO 3166) of document's issuer, <i>nnnnnnnn</i> is the document number and <i>yyyyyyyyyy</i> is the birth certification number	
serialNumber (3)	optional and if attribute serialNumber (2) contains birth certification number one of following options:	
	• IDCss-nnnnnnn;	
	PASss-nnnnnnnn;	
	where:	
	 ss is the country code (ISO 3166) of document's issuer (does not have to be same as countryName); and 	
	nnnnnnnn is the document number	
commonName*	mandatory, single occurrence:	
	 if givenName and surName are specified, these must be included in commonName; 	
	 if pseudonym is specified, the string '- PSEUDONYM' is added to the content 	
initials	optional; single occurrence	
emailAddress	this attribute must not be included in the primary Certificate	
name	this attribute must not be included in the primary Certificate	
generationQualifier	optional; single occurrence	
organizationName	employee of the Organization: mandatory; single occurrence;	
	• self-employed natural person: optional; single occurrence;	
	other natural persons: may not be specified	

Version 1.00 Page 57 of 74

organizationIdentifier	optional and only if the organizationName attribute is specified, single occurrence:		
	• NTR <i>ss-id</i> , (<u>National Trade Register</u> , i.e., business/company identification number);		
	where:		
	 ss is the country code (ISO 3166) of the state where the employer of OSVČ is registered (does not have to be same as countryName); 		
	• <i>id</i> is the organization's identification number in the relevant register		
organizationalUnitName	optional; multiple occurrences permitted		
title	optional; multiple occurrences permitted		
stateOrProvinceName**	optional; single occurrence		
localityName**	optional; single occurrence		
	primary Certificate: if specified, streetAddress and postalCode must also be specified		
streetAddress**	optional; single occurrence		
	primary Certificate: if specified, localityName and postalCode must also be specified		
postalCode**	optional; single occurrence		
	primary Certificate: if specified, localityName and streetAddress must also be specified		

^{*} The name under which the Certificate subscriber (private key holder) normally appears, the attribute may also contain validates degrees of the Certificate's subscriber.

7.1.1 Version number(s)

Any Certificate issued complies with standard X.509, version 3.

7.1.2 Certificate extensions

Table 6 – Certificate Extensions³

Table C Collingate Extendions		
Extension	Content	Comments
certificatePolicies		non-critical
.policyInformation (1)		

³ I.CA SK reserves the right to modify the set and the content of Certificate extensions as may be required by updated ETSI standards or third parties (Microsoft, for example).

Version 1.00 Page 58 of 74

^{**} The attributes countryName, stateOrProvinceName, localityName, streetAddress and postalCode relate to data validated during initial identity validation.

policyldentifier	see 1.2	ICA policy OID
policyQualifiers	366 1.2	TOA policy OID
cPSuri	http://www.ica.cz	
.policyInformation (2)	Tittp://www.ica.cz	
policyldentifier	1.3.158.36061701.0.0.0.1.2.2	NBÚ SR policy OID
policyQualifiers	1.0.130.303001701.0.0.3.1.2.2	TABO OIT POINTY OID
userNotice	EN: This is a qualified certificate for electronic signature according to Regulation (EU) No 910/2014. SK: Kvalifikovany certifikat pre elektronicky podpis v sulade s nariadenim (EU) č. 910/2014.	issuer can change the text depending on requirements of the Slovak Republic legislation
.policyInformation (3)		
policyldentifier	OID (QCP-n-qscd): 0.4.0.194112.1.2	ETSI policy OID (private key generated and stored on QSCD)
QCStatements		non-critical
	0.4.0.1862.1.1	Id-etsi-qcs- QcCompliance
	0.4.0.1862.1.4	ld-etsi-qcs- QcSSCD
	0.4.0.1862.1.5	id-etsi-qcs-QcPDS;
		link (URI, https) to disclosure statement (PDS)
	0.4.0.1862.1.6	id-etsi-qcs-QcType
	= 0.4.0.1862.1.6.1	= id-etsi-qct-esign
CRLDistributionPoints*	http://qcrldp1.ica.cz/qcask <i>YY_</i> rsa.crl	non-critical
	http://qcrldp2.ica.cz/qcask <i>YY_</i> rsa.crl	
	http://qcrldp3.ica.cz/qcaskYY_rsa.crl	
authorityInformationAccess		non-critical
id-ad-ocsp*	http://ocsp.ica.cz/qcaskYY_rsa	
id-ad-calssuers*	http://q.ica.cz/qcaskRR_rsa.cer	
id-ad-calssuers	directoryName.serialNumber = TLISK-yyy	optional yyy – number
		assigned by

Version 1.00 Page 59 of 74

		supervisory body
basicConstraints		non-critical
cA	False	
keyUsage	 TWINS/DUAL: digitalSignature, nonRepudiation, other cases: depending on the content of Certificate application one of following options: nonRepudiation; digitalSignature, nonRepudiation; digitalSignature, nonRepudiation and keyEncipherment*** 	critical, mandatory TWINS/DUAL - creates Authority; others - if this extension is missing in the application, the following will be added: digitalSignat ure, nonRepudiat ion
extendedKeyUsage	depending on the content of Certificate application - one of following options: • id-kp-emailProtection; • ms-Document_Signing; • id-kp-emailProtection and ms-Document_Signing	non-critical, mandatory if this extension is missing in the application, the following will be added: • id-kp- emailProtection
subjectKeyIdentifier	hash of the public key (subjectPublicKey) in the Certificate	non-critical
authorityKeyldentifier		non-critical
keyldentifier	hash of the Authority's public key	
subjectAlternativeName		non-critical
otherName**	I.CA_User_ID(1.3.6.1.4.1.23624.4.6): xxxxxxxx	
otherName	MPSV_IK (1.3.6.1.4.1.11801.2.1): numerical identifier supplied by MPSV	optional
rfc822Name	e-mail address	optional; multiple occurrences permitted

Version 1.00 Page 60 of 74

nsComment	QSCD identification number	non-critical; optional — creates Authority when generating and storing of the private key on QSCD (smartcard Starcos type) was verified
I.CA_TWIN_ID: 1.3.6.1.4.1.23624.4.3	Certificate application number	non-critical
I.CA_CERT_INTERCONN ECTION: 1.3.6.1.4.1.23624.4.7	if more certificate types are issued to a single entity (entity's connection to the certificates issued)	non-critical

^{*} YY – the last two digits of the year the Authority's certificate is issued.

7.1.3 Algorithm object identifiers

The algorithms used in providing trust services comply with the relevant technical standards.

7.1.4 Name forms

Name forms in issued Certificates comply with RFC 5280 standard. The provisions of 3.1 also apply.

7.1.5 Name constraints

Not applicable to Certificates issued to end users.

7.1.6 Certificate policy object identifier

I.CA SK inserts in the Certificates issued the following certification policy object identifiers:

- OID of the I.CA SK certification policy under which the Certificate is issued;
- OID of the NBÚ SR certification policy;
- OID of the relevant certification policy defined by ETSI EN 319 411-2 respectively ČSN ETSI EN 319 411-2 respectively ČSN et al. 219 411-2

7.1.7 Usage of Policy Constraints extension

Not applicable to Certificates issued to end users.

Version 1.00 Page 61 of 74

^{**} It is a selected sub-string from the subject field's serialNumber attribute created by the Authority (see Table 5).

Last option (containing setting keyEncipherment bit) for keyUsage cannot be used when the key is generated and stored on Starcos 3.5 (or higher) smartcard.

7.1.8 Policy qualifier syntax and semantics

See Certificate extensions in 7.1.2 above.

7.1.9 Processing semantics for the critical certificate policies extension

Not applicable to this document, extension not classified as critical.

7.2 CRL profile

Table 7 - CRL profile4

Field	Content
version	v2(0x1)
signatureAlgorithm	sha256withRSAEncryption at minimum
issuer	issuer of the CRL (the Authority)
thisUpdate	date and time when the CRL was released (UTC)
nextUpdate*	date and expected time when the next CRL will be released (UTC)
revokedCertificates	list of revoked certificates
userCertificate	revoked certificate's serial number
revocationDate	certificate revocation date and time
crlEntryExtensions	list attribute extensions – see Table 8
crlExtensions	CRL extensions – see Table 8
signature	advanced electronic seal of CRL's issuer (Authority)

^{*} In case of root CA 365 days at maximum, in case of subordinate CA 24 hours at maximum.

7.2.1 Version number(s)

Certificate revocation lists are issued pursuant to X.509, version 2.

7.2.2 CRL and CRL entry extensions

Table 8 - CRL Extension⁵

Extension	Content	Comments
crlEntryExtensions		
CRLReason	certificate revocation reason	non-critical;

⁴ I.CA SK reserves the right to modify the set of the fields and the content of the CRL as may be required by updated ETSI standards or third parties (Microsoft, for example).

Version 1.00 Page 62 of 74

⁵ I.CA SK reserves the right to modify the set and the content of the CRL extensions as may be required by updated ETSI standards or third parties (Microsoft, for example).

	as the <i>certificateHold</i> reason is not admissible, it is not used	optional
	another reason than unspecified (0) is given when subordinate CA's certificate is revoked	
crlExtensions		
authorityKeyldentifier		
keyldentifier	hash of the CRL issuer's public key	non-critical
CRLNumber	unique number of the CRL to be released	non-critical

7.3 OCSP profile

Both the OCSP request profile and the OCSP response profile comply with were RFC 6960 and RFC 5019.

OCSP responses are of the BasicOCSPResponse type and contain all mandatory fields. An optional revocationReason field is included for revoked certificates. The unAuthorized response is given for any certificate not issued by the relevant CA.

Http only is used as the transmission protocol.

See the relevant certification practice statement for more detail.

7.3.1 Version number(s)

Version 1 is specified in a certificate status request and response using the OCSP protocol.

7.3.2 OCSP extensions

The specific extensions for OCSP protocol certificate status requests and responses are given in the relevant certification practice statement.

Version 1.00 Page 63 of 74

8 CONFORMITY ASSESSMENTS AND OTHER ASSESSMENTS

8.1 Frequency or circumstances of assessment

The assessment interval and circumstances are defined in trust services legislation and the technical standards referred to therein regulating the assessment procedure.

The Microsoft Trusted Root Program assessment interval and circumstances are strictly defined by Microsoft, and the audit period is not longer than one year.

The intervals for other assessments are specified in the relevant technical standards.

8.2 Identity/qualifications of assessor

The identity (accredited conformity assessment entity) and the qualification of the assessor carrying out the assessment pursuant to trust services legislation are defined in this legislation and the technical standards referred to therein.

The identity (accredited conformity assessment entity) and the qualification of the assessor carrying out assessment defined by Microsoft Trusted Root Program are described in ETSI EN 319 403.

The qualification of the assessor carrying out other assessments is specified in the relevant technical standards.

8.3 Assessor's relationship to assessed entity

Internal assessor is not subordinate to the organizational unit which provides the operation of trust services.

External assessor is an assessor without any ties to I.CA or I.CA SK both through property and person.

8.4 Topics covered by assessment

The areas to be assessed in an assessment required under trust services legislation are those as specified in that legislation.

The areas to be assessed in an assessment required for Microsoft Trusted Root Program are strictly given by requirements of Microsoft Company.

The areas to be assessed in any other assessment are specified in the technical standards under which the assessment is made.

8.5 Actions taken as a result of deficiency

The findings in any type of assessment are communicated to the I.CA security manager and managing director of I.CA SK, who makes sure that any defect identified is remedied. If

Version 1.00 Page 64 of 74

defects are identified that critically prevent the provision of a specific trust service, I.CA or I.CA SK must suspend that service until the defects are remedied.

8.6 Communication of results

Assessment result notification is subject to the requirements of trust services legislation and the relevant technical standards; the notification of Microsoft Trusted Root Program assessment results is subject to Microsoft requirements.

Assessments results are notified as a written report handed over by the assessor to CEO of I.CA or the security manager of I.CA, or to the managing director of I.CA SK.

The I.CA security manager calls a security committee meeting as soon as possible and communicates the final report at the meeting; company management members must attend the meeting.

Version 1.00 Page 65 of 74

9 OTHER BUSINESS AND LEGAL MATTERS

9.1 Fees

9.1.1 Certificate issuance or renewal fees

The fees for Certificate issuance are given in the current price list, which is available on the web information address of I.CA SK or in the contract if there is a contract between I.CA SK and the Organization. Certificate renewal is not provided.

9.1.2 Certificate access fees

No fee is charged by I.CA or I.CA SK for electronic access to the Certificates issued under this CP.

9.1.3 Revocation or status information access fees

No fee is charged by I.CA or I.CA SK for electronic access to revocation information (CRL) and status information about the Certificates issued by the Authority.

9.1.4 Fees for other services

Not applicable to this document.

9.1.5 Refund policy

Not applicable to this document.

9.2 Financial responsibility

9.2.1 Insurance coverage

I.CA represents that it holds a valid business risk insurance policy that covers financial damage.

I.CA has drawn an employee liability insurance policy for each employee, with a scope of coverage as determined by the company's board of directors.

9.2.2 Other assets

I.CA represents that it has available financial resources and other financial assurances sufficient for providing trust services, including the trust services provided by I.CA SK, given the risk of a liability-for-damage claim.

See the Annual Report of První certifikační autorita, a.s., published in Commercial Register for detailed information on the company's assets.

Version 1.00 Page 66 of 74

9.2.3 Insurance or warranty coverage for end-entities

Not applicable to this document.

9.3 Confidentiality of business information

9.3.1 Scope of confidential information

Confidential information of I.CA or I.CA SK covers any information other than public information and other than that published in the manner pursuant to 2.2, including:

- All private keys, which are employed in providing trust services;
- Business information of I.CA or I.CA SK;
- Any internal information and documentation;
- Any personal data.

9.3.2 Information not within the scope of confidential information

Public information is only the information designated as public and that published in the manner pursuant to 2.2.

9.3.3 Responsibility to protect confidential information

I.CA or I.CA SK employee who comes in contact with confidential information may not disclose the same to a third party without consent of CEO of I.CA or managing director of I.CA SK.

9.4 Privacy of personal information

9.4.1 Privacy plan

I.CA or I.CA SK protects personal data and other non-public information in accordance with the relevant legislation, that is ZOOÚ and GDPR in particular.

9.4.2 Information treated as private

Any personal data subject to protection under relevant legislation is treated as private.

I.CA or I.CA SK employees or the entities defined by relevant legislation that come into contact with personal data must maintain confidentiality of these data and the security controls the disclosure of which would put the security of these data at risk. The confidentiality duty survives the termination of employment or other similar relationship, or the completion of pertinent work.

Version 1.00 Page 67 of 74

9.4.3 Information not deemed private

Any information outside the scope of relevant legislation is not considered personal data.

9.4.4 Responsibility to protect private information

CEO of I.CA or managing director of I.CA SK are responsible for the protection of personal data.

9.4.5 Notice and consent to use private information

I.CA or I.CA SK deals with the notifying of personal data use and consents to personal data processing in accordance with the relevant legislation.

9.4.6 Disclosure pursuant to judicial or administrative process

I.CA or I.CA SK discloses personal data for judicial or administrative purpose in accordance with the relevant legislation.

9.4.7 Other Information disclosure circumstances

I.CA or I.CA SK provides access to personal data strictly as regulated in relevant legislation.

9.5 Intellectual property rights

This CP, all related documents, the website content and the procedures facilitating the operation of trustworthy systems providing trust services are copyrighted by I.CA or I.CA SK and are important know-how thereof.

9.6 Representations and warranties

9.6.1 CA Representations and warranties

I.CA SK warrants that:

- It will use the private keys of certification authorities solely for issuing certificates to end users (except I.CA root certification authority), releasing certificate revocation lists and issuing OCSP responder certificates;
- It will use the private keys of certification authorities' OCSP responders solely in the processes of providing responses to certificate status requests;
- Certificates issued to end users meet the statutory trust services requirements and those of the relevant technical standards;
- It will revoke any issued Certificate if the revocation request is filed in the manner defined in this CP.

All warranties and the performance resulting therefrom may only be recognized on condition that:

Version 1.00 Page 68 of 74

- The Certificate's subscriber did not violate any obligation arising from Service contract and this CP:
- The relying party did not violate any obligation arising from this CP.

The subscriber of a Certificate issued under this CP must always make his warranty claim with the RA which handled his application for that particular Certificate.

I.CA SK represents and warrants, vis-à-vis Certificate's subscribers and all relying parties, that I.CA SK will observe its CPs and corresponding CPS in issuing Certificates and administering the same throughout their periods of validity.

The warranties include:

- Checking the right to apply for the Certificate;
- Validating the information given in the Certificate application, checking due completion of the items in the Certificate application (PKCS#10 format) and checking the identity;
- Ensuring that the Certificate issuance contract meets the requirements of relevant legislation;
- Ensuring that certificate status information repository is maintained 24 hours a day and 7 days a week;
- Ensuring that the Certificate may be revoked for reasons specified in trust services legislation and this CP.

9.6.2 RA representations and warranties

The designated RA:

- Assumes the obligation that the services which the RA provides are correct;
- Does not accept the application unless the RA validates all the application items (except those not subject to validation), or the Certificate's subscriber provides the required data or is authorized to submit the application;
- Is responsible for passing a hand-delivered Certificate revocation application to an Authority office in due time for the office to handle the application;
- Is responsible for handling objections and complaints.

9.6.3 Subscriber representations and warranties

The subscriber representations and warranties are stated in the contract between I.CA SK and the Certificate's subscriber.

9.6.4 Relying parties representations and warranties

Relying parties observe this CP.

9.6.5 Representations and warranties of other participants

Not applicable to this document.

Version 1.00 Page 69 of 74

9.7 Disclaimers of warranties

I.CA SK provides only the warranties as given in 9.6.

9.8 Limitations of liability

I.CA or I.CA SK is not responsible for any damage suffered by relying parties where the relying party breaches its obligations under trust services legislation and particular CP. I.CA or I.CA SK is also not responsible for any damage resulting from breach of its obligations as a result of force majeure.

9.9 Indemnities

Applicable to the provision of trust services are the relevant provisions of the current legislation regulating provider—consumer relations and the warranties agreed between I.CA SK and the applicant for the Service. The contract must not be in conflict with current legislation and must always take an electronic or printed form.

I.CA or I.CA SK:

- Undertakes to discharge all the obligations defined in relevant legislation (including trust services legislation) and those in the relevant policies;
- Gives the aforesaid warranties throughout the term of the contract of trust services;
- Agrees that the application software suppliers with a valid contract with I.CA for the distribution of the root certificate assume no obligation or liability, except for where damage or loss is directly attributable to the software of that supplier.

I.CA or I.CA SK is not responsible for:

- Any defect in the services rendered which is due to the Certificate subscriber's incorrect or unauthorized use of the services rendered under the Service contract, particularly for any use contrary to the terms and conditions specified in this CP, and for any defect due to force majeure, including a temporary telecommunication connection failure;
- Any damage resulting from using the Certificate after filing the application for that certificate's revocation if I.CA SK meets the defined time limit for publishing the revoked Certificate on the list of revoked certificates (CRL or OCSP).

Claims and complaints may be submitted by:

- E-mail to reklamace@ica.cz;
- Registered post letter to the registered office of the company;
- Hand at the registered office of the company.

The party making the claim or complaint (subscriber of the Certificate or the relying party) must provide:

- Description of the defect that is as accurate as possible;
- Serial number of the product complained about;
- Suggestion how the claim/complaint should be resolved.

Version 1.00 Page 70 of 74

I.CA SK will decide the claim/complaint within three business days of receiving it. The decision will be communicated to the party making the claim/complaint by e-mail, data box message or registered post letter unless the parties agree to a different method.

The claim/complaint, including the defect, will be dealt with without undue delay, within 30 days of the date of the claim/complaint unless the parties agree otherwise.

The subscriber will be provided with a new Certificate free of charge if:

- There is reasonable suspicion that the certification authority's private key has been compromised;
- The management of I.CA or managing director of I.CA SK decide so taking account of the circumstances of the case:
- The Authority finds out, in the Certificate application acceptance procedure, that a different Certificate with a duplicate public key exists.

Any other possible compensation is based on the relevant legislation and the amount of damages may be determined by court.

9.10 Term and termination

9.10.1 Term

This CP takes force on the date specified in chapter 10 and remains in force no shorter than the expiration of the last Certificate issued under this CP.

9.10.2 Termination

Jointly CEO of I.CA and managing director of I.CA SK are authorized to approve the termination of this CP.

9.10.3 Effect of termination and survival

The obligations of I.CA SK arising from CP survive the expiration thereof until the expiration of the last Certificate issued under this CP.

9.11 Individual notices and communications with participants

For individual notices and communication with the participating parties, I.CA SK may use the e-mail and postal addresses and the phone numbers provided by the participating parties, personal meetings and other channels.

Communication with I.CA SK is also possible through the channels specified on the web information address.

Version 1.00 Page 71 of 74

9.12 Amendments

9.12.1 Amending procedure

This procedure is a controlled process described in an internal documentation of I.CA.

9.12.2 Notification mechanism and period

The release of a new CP version is always notified as published information.

9.12.3 Circumstances under which OID must be changed

CP's OID must be changed when the changes of CP materially reduce the assurance that the Certificate is trusted and will have a significant effect on the acceptability of the Certificate in compliance with trust services legislation.

Any change to this CP results in a new version of the document.

9.13 Disputes resolution provisions

If the Certificate's subscriber or the relying party disagrees with the proposed way of resolving the dispute, they may use the following levels of appeal:

- RA employee in charge;
- I.CA SK employee in charge (electronic or written filing is required);
- Managing director of I.CA SK or CEO of I.CA (electronic or written filing is required).

This procedure provides the dissenting party with an opportunity to assert its opinion more swiftly than before a court.

9.14 Governing law

The business of I.CA SK is governed by the laws of the Slovak Republic.

9.15 Compliance with applicable law

The system of providing trust services is in compliance with the legislation EU, the Czech Republic, the Slovak Republic and all relevant international standards.

9.16 Miscellaneous provisions

9.16.1 Entire agreement

Not applicable to this document.

Version 1.00 Page 72 of 74

9.16.2 Assignment

Not applicable to this document.

9.16.3 Severability

If a court or a public authority with jurisdiction over the activities covered by this CP establishes that the implementation of a mandatory requirement is unlawful, the scope of that requirement will be so limited as to ensure the requirement is lawful and complies with relevant legislation.

9.16.4 Enforcement (attorneys' fees and waiver of rights)

Not applicable to this document.

9.16.5 Force Majeure

I.CA SK is not responsible for breaching its obligations arising from Service contract if it is the result of force majeure, such as major natural disaster, major disaster caused by human activity, strike or civil unrest always followed by the declaration of a situation of emergency, or the declaration of threat to state or a state of war, or communication failure.

9.17 Other provisions

Not applicable to this document.

Version 1.00 Page 73 of 74

10 FINAL PROVISIONS

This certification policy issued by I.CA SK takes force date mentioned above in Table 1 and effect when status of qualified service provider according to the Act of the Slovak Republic No. 272/2016 Coll. will be granted.

Version 1.00 Page 74 of 74